

# SICV SERİSİ

MODEL NO.	VALVE DIAMETER	MAXIMUM FLOW RATE			CLOSE-OFF PRESSURE	DIFFERENTIAL PRESSURE RANGE	PN RATING
		MM	L/H	M3/H			
SICV015TWL2	DN15	1110	1.11	4.89	800	30 - 800	PN25
SICV015TPL2	DN15	1110	1.11	4.89	800	30 - 800	PN25
SICV015TWH2	DN15	2650	2.7	11.7	800	35 - 800	PN25
SICV015TPH2	DN15	2650	2.7	11.7	800	35 - 800	PN25
SICV020TWL2	DN20	1110	1.11	4.89	800	30 - 800	PN25
SICV020TPL2	DN20	1110	1.11	4.89	800	30 - 800	PN25
SICV020TWH2	DN20	2650	2.7	11.7	800	35 - 800	PN25
SICV020TPH2	DN20	2650	2.7	11.7	800	35 - 800	PN25
SICV025TWH2	DN25	2650	2.7	11.7	800	35 - 800	PN25
SICV025TPH2	DN25	2650	2.7	11.7	800	35 - 800	PN25
SICV032TWH2	DN32	4630	4.6	20.4	800	16 - 800	PN25
SICV032TPH2	DN32	4630	4.6	20.4	800	16 - 800	PN25
SICV040TPH2	DN40	13647	13.6	60.1	800	16 - 600	PN25
SICV050TPL2	DN50	13647	13.6	60.1	800	16 - 600	PN25

## DEBİ KONTROL EĞRİSİ

