

CZHGL-90

High Lumen Marine Location **LED Flood Light**

	P67	
С	lass	
-	-	







Catalog Number	
Notes	
Туре	


Specifications

Height: 12.72"

Width: 14.2"

Depth: 6.42"

Weight: 17.6 lbs



DESCRIPTION

The CZHGL-90 is an efficient, energy saving and long lasting LED flood light. Ideal for new construction or retrofit applications, this LED luminaire can be used in commercial, industrial, and marine environments. The fixture can mount at a broad range of angles with a yoke style arm.

FEATURES

- 10,800 Lumens
- Outperforms 250W metal halide
- Integral 80 to 400VAC power supply
- Stainless steel hardware
- IP 67 wet location rated
- 40F ~ 140F

- 4' power cord option
- Built in surge and thermal protection
- Operating temperature: -40 to 40 C
- Average LED lifetime: 50,000 hours
- Multiple viewing angle options
- Cree/Osram LED Chips

ORDERING INFORMATION

Series Wattage -CZHGL* 90A* (90W)

Color Temperature 5700K* (cool)

Voltage

Beam Angle -

Options IP67*

4000K (neutral)

UNV* (80 to 400VAC)

L60-FL*

5Y* (5 Year Warranty) 4FT* (4'/1.5M cord length)

Example: CZHGL-90A-5700K-UNV-L60-FL-IP67-5Y-4FT

90W LED Flood Light; 5700K color temp; Universal voltage; 60 degree beam angle; IP67; 5 Year Warranty; 4 ft. cord

