



B&B TECHNOSOLUTIONS

CHUCK - SJ TYPE

Dimensional Data of Self-Centring Chucks

Nominal Size	d2 H7	P.C.D.		d5	h1	h2	D	L	K	L1	L2	L3	Thickness of Jaw	Size of Sq of Handle	Weight (Kg)		
		d3	Tol. on d3												SJ3	SJ4	SJ6
80	56	67	± 0.20	16	44	14	3	32	M6	11	6	6	10.5	6	1.3	-	-
100	70	83	± 0.25	20	50	18	3	42	M8	14	8	8	14.0	8	2.4	2.4	-
110	80	94	± 0.25	22	55	18	4	42	M8	14	8	8	14.0	9	3.1	3.5	-
125	95	108	± 0.25	33	60	22	4	48	M8	16	9	9	16.5	9	4	4	4.5
160	125	140	± 0.30	42	67	29	5	65	M10	20	12	12	18.0	10	8	8	9
200	160	176	± 0.35	55	75	31	5	76	M10	24	13	13	22.0	11	13	14	14
250	200	224	± 0.35	76	86	36	6	97	M12	30	13	14	28.5	12	24	24	24
270	220	245	± 0.35	90	86	36	6	97	M12	30	13	14	28.5	12	26	27	27
315	260	286	± 0.40	108	86	36	6	120	M12	38	14	14	28.5	14	36	37	38
375	320	349	± 0.40	140	95	58	6	140	M12	38	25	25	34.0	16	56	62	64
400	330	362	± 0.40	150	105	58	8	160	M16	40	25	25	34.0	16	70	72	78
500	433	465	± 0.50	203	135	63	8	170	M16	48	25	25	40.0	16	102	105	110
610	538	567	± 0.50	260	130	80	10	200	M16	55	35	35	50.0	19	180	182	188

