

Northeast Sled Services LLC
2024 2WD SUPERSTOCK / 5200lbs A&B

Engine Specs:

- 1) Must have SFI engine balancer, no elastomer style balancers allowed.
- 2) Limited to one engine only.
- 3) Gas only - **No nitrous oxide or methanol or compressed air**** Race fuel allowed.
- 4) No blowers or turbos.
- 5) Engine limited to 410 cubic inch.
- 6) May be single plane intake with maximum 2" spacer or adaptor plate allowed. .
- 7) Limited to one carburetor.
- 8) No fuel injection allowed.
- 9) Exhaust must be straight upright or straight back under truck.
- 10) Engine components may be altered by machining, porting, polishing, etc. Aftermarket blocks etc. may be used.

Other Specs:

- 1) Rear suspension not required.
- 2) Rear axle must be a dana 80, or corporate 14 bolt or smaller. **No Rockwells.**
- 3) Chassis must not exceed 15 feet of wheelbase from center of rear axle to forward most point of truck, including weights and brackets.
- 4) Chassis must be mass produced factory built 1 ton or less frame – must be OEM frame – no tube or boxed frames. Except for 5 feet from rear edge of frame rails forward.
- 5) Single gear box only can be manual or automatic. High stall torque converters allowed. No transfer cases or 2 speed rears allowed.
- 6) No quick change transmissions or differentials allowed.
- 7) 34X18 Maximum tire size allowed (puller tires and dot allowed) - No dual wheels.
- 8) Double cut tires not allowed.
- 9) **No weights** allowed in cab.

Hitch Specs:

- 1) Hitch must not exceed more than 45" back from center of rear housing
- 2) No more than 30" high at top of hook point.
- 3) Minimum hole size of 3" and must be easily accessible.
- 4) Hitch may be adjustable, yet solid in all directions once adjusted.
- 5) No more than 1 ½ inches from hook point to terminal end of hitch.

Safety Specs:

- 1) Wheelie bars to be made to be minimum 10 inches behind rear tire and max 10 inches off the ground, to facilitate easier hooking and a more rigid wheelie bar - bump stops required.
- 2) Universal joints must be shielded with a minimum ¼" thick by 6" wide steel straps enclosed 360 degrees – also minimum of one loop per drive shaft.

Also -All General Safety Rules Apply!
**Violation of any rule will be a disqualification for the event in which
the violation occurs!**

Northeast Sled Services LLC
2024 2WD SUPERSTOCK / 5200lbs A&B

- 3) All vehicles using a clutch will have a steel flywheel and are required to have an **SFI APPROVED** steel bellhousing. Automatic transmissions will be covered with 1/8" steel or better scatter shield, blanket, or equivalent material – this includes top and sides completely covered.
- 4) All fans must be shielded 360 degrees with minimum of 1/8" steel. Except electric fans.
- 5) Side shield on engines of 1/8" minimum – at least covering the spark plugs.
- 6) Driver must wear a DOT approved helmet – seat belts required and must be worn.
- 7) Minimum of 2lb fire extinguisher must be loaded and in the vehicle.
- 8) **KILL SWITCHES MANDATORY** – Kill switch must be of the tether type and placed in the center, in an un-obstructed area on the rear of the vehicle.
- 9) Neutral switches mandatory.
- 10) Must have at least a 4 point roll cage on open cabs (T buckets etc.), Recommend a 2 point internal roll cage on trucks with enclosed cabs.
- 11) If zip ties are used to secure kill switch pull tab, tie must break with 25lbs pull or less.
- 12) All other rules in general rules apply.

**** Serious Safety Offence – One year and ten (10) day disqualification.**

Also -All General Safety Rules Apply!
**Violation of any rule will be a disqualification for the event in which
the violation occurs!**