

TOSHIBA

e-STUDIO™ 2525AC/3025AC/3525AC/4525AC

- High-Speed – Up to 25, 30, 35 & 45PPM
- Compact Design
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



e-STUDIO™ 2525AC/3025AC/3525AC/4525AC

MAIN SPECIFICATIONS

Copy System	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	25/30/35/45 PPM (LT)
First Copy Out	Color: Less Than 7.8/7.8/7.8/5.7 Seconds Monochrome: Less Than 5.9/5.9/5.9/4.4 Seconds
Warm-Up Time	From powering on: Approx. 20 Seconds From Sleep & Low Power: Less Than 12 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 5,200 Sheets
Original Feed	300-Sheet DSDf or DSDf with Double Feed Detection or 100-Sheet RADf LD/A3
Max. Original Size	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18"
Paper Feed Sizes	Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-110lb Cover Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-140lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-28lb Bond Opt. 2,000-Sheet External LCF-LT 16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index) 25% to 400% Max. 75K/90K/105K/105K Month (Color: 100%) Max. 150K/180K/210K/210K Month (Monochrome: 100%) Approx. 169lb/172lb 23" (W) x 25.2" (D) x 31" (H) CMY: 38K, K: 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 4GB 128GB Solid State Drive (SSD)
Paper Weights	
Duplex	
Reproduction Ratio	
Max Duty Cycle	
Weight	
Approx. Dimensions	
CMYK Toner Yield	
Power Source	
Power Consumption	
Plug Type	
Memory	
Hard Disk Drive	

e-BRIDGE NEXT PRINT SPECIFICATIONS

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi, 1,200 x 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode
ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65
WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

Scan Speed	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADf Scan: Up to 73 IPM (Monochrome or Color)
Scan Weights	DSDf Simplex or Duplex: 9.3-110lb Bond RADf Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX, Color/Grayscale: JPEG, TIFFMulti/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPSMulti/Single Page, DOCX, XLSX, PPTX
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job

e-FILING SPECIFICATIONS

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

ACCESSORIES (OPTIONS)

Platen & Document Feeder Options	Meta Scan Enabler	GS1010NODE
DSDf	IPSec Enabler	GP1080NODE
DSDf with Double Feed Detection	Unicode Font Enabler	GS1007NODE
RADf	Multi-Station Print Enabler	
Platen Cover	Per Seat License	GS1090NODE
Additional Paper Options	e-BRIDGE Plus for OneDrive	GB2300NODE
Paper Feed Pedestal	e-BRIDGE Plus for SharePoint	GB2310NODE
Drawer Module	e-BRIDGE Plus for Exchange	GB2330NODE
Envelope Cassette Option	Workplace Productivity Bundle	GB2330NODE
Large Capacity Feeder	e-BRIDGE Plus for Gmail	GB2380NODE
External Large Capacity Feeder	e-BRIDGE Plus for Google Workspace	GB2390NODE
Finishing Options	Hardcopy Security Printing	GP1190NODE
50-Sheet Inner Finisher	Security SSD (512GB)	GE1280
65-Sheet Staple Finisher	FIPS HDD (320GB)	GE1260
65-Sheet Saddle-Stitch Finisher	e-BRIDGE Plus Voice Guidance	GB2540NODE
Hole Punch for MJ1048	e-BRIDGE Global Print	GB2550NODE
Hole Punch for MJ1113/MJ1114	Miscellaneous Options	
Bridge Kit	Card Reader Holder	GR1320
Job Separator	Accessory Tray	GR1330
Connectivity/Security Options	Panel 10-Key Option	GR1340
FAX Unit/2 nd Line for FAX Unit	Stand	STANDS015
Wireless LAN/Bluetooth	Work Tray	KK5005
Fax Over IP License Key	Manual Pocket	KK5008
Bluetooth Keyboard	Harness for Coin Controller	GQ1280
2 nd NIC Holder	Accessible Arm	KK2560
USB Hub		

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

business.toshiba.com