

Product Specifications

Marking Engine

Technology	Electrophotogra	phy
Print Speed	8.5" x 11":	Up to 101 ipm
	11" x 17":	Up to 52 ipm
	12" x 18":	Up to 50 ipm
	13" x 19":	Up to 48 ipm
	13" x 30":	Up to 28 ipm
Paper Size	Standard:	3.9" x 5.8" to 13" x 19.2"
	Optional:	5.5" x 7.2" to 13" x 51.2"
Paper Capacity ¹	Standard:	Up to 1,100 Sheets
	Optional:	Up to 11,100 Sheets
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Optional:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Envelopes: ²	No. 10, ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"
Automatic	Paper Size:	Up to 13" x 51.2" ³
Duplexing	Paper Weight:	Up to 150 lb. Cover ⁴ (400 gsm)
Power Source	(2) Single-Phase	200 -240 V, 50/60 Hz, 20 A
Weight	904 lb.	
Dimensions	62.3" W x 34.3"	D x 40.9" H

Input Accessories

Multi-Drawer Paper Deck-E1	Paper Capacity:1	Up to 5,000 Sheets		
	Paper Size:	5.5" x 7.2" to 13" x 19.2"		
	Paper Weight			
	Top/Middle:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		
	Bottom:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)		
	Power Source:	110 – 127 V, 60 Hz, 7 A 392 lb.		
	Weight:			
	Dimensions:	38" W x 31.5" D x 42.5" H		
POD Deck Lite-C1	Paper Capacity:1	Up to 3,500 Sheets		
	Paper Size:	5.5" x 5.8" to 13" x 19.2"		
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)		
	Power Source:	120 – 127 V, 60 Hz, 2.2 A		
	Weight:	168 lb.		
	Dimensions:	28.2" W x 27" D x 22.6" H		
POD Deck	Paper Capacity ¹			
Lite XL-A2	Up to 13" x 19.2":	Up to 3,500 Sheets		
	Up to 13" x 30":	Up to 1,000 Sheets		
	Paper Size:	5.5" x 5.83" to 13" x 30"		
	Paper Weight:			
	Up to 13" x 19.2":	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)		
	Up to 13" x 30":	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)		
	Power Source:	120 – 127 V, 60 Hz, 2.2 A		
	Weight:	249 lb.		
	Dimensions:	43.5" W x 27" D x 22.6" H		

Input Accessories	(Continued):				
Stack	Paper Capacity:	Up to 250 Sheets	Document	Tray Capacity ¹	
Bypass-D1	Paper Size:	3.9" x 5.83" to 13" x 19.2"	Link D15	Upper Tray:	Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 130 lb. Cover		Lower Tray:	Up to 200 Sheets
	Weight:	(52 gsm to 350 gsm) 3 lb.		Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Dimensions:	18" W x 15.1" D x 2.9" H		Paper Size:	7.2" x 7.2" to 13" x 19.2"
				Power Supply:	100 – 240 V, 50/60 Hz, 1.4 A
Long Sheet	Paper Capacity:	Up to 1 Sheet		Weight:	135 lb.
Feeding	Paper Size:	8.3" x 19.2" to 13" x 51.2"		Dimensions:	29.4" W x 31.2" D x 55.4" H
and Catab	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)			
	Weight:	2 lb.	Multi Function Professional Puncher-C1 ⁵	Paper Weight	
	Dimensions:	24.9" W x 56.1" D x 56.1" H		Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm) 110 lb. Text to 110 lb. Cover
Duplex	Image Sensor:	CCD	Puncher-Ci	Creasing:	(157 gsm to 300 gsm)
Color Image	Scan Speed:	Up to 270 opm (Letter, 300 dpi)		Paper Size	(in general regeny
Reader-P1	Document Size:	2.8" x 5.5" to 12" x 24.8"		Punching:	12" x 18", 11" x 17", Letter, Legal,
	Resolution:	Up to 600 x 600 dpi, 256 Gradations			Letter-R, Statement
	Tray Capacity:1	Up 200 Sheets		Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	Weight:	51 lb.		Die Set Patterns:	Loose-Leaf 3-Hole/5-Hole, Velo Bind
_	Dimensions:	25.7" W x 23.3" D x 8.6" H			11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
Finishing A	ccessories			Power Supply:	115 V, 60 Hz, 3.8 A
Sensing Tasks:	Tasks:	Front-to-Back Alignment, Color Accuracy		Weight:	225 lb.
Unit-B1 ⁵		Check, Cross Shade Adjustment, Secondary Transfer Adjustment		Dimensions:	17.5" W x 31.3" D x 40.9" H
	DFE:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later	GBC	Bound Book Size:	¹ 7 to 100 Sheets
	Paper Weight:	14 lb. Bond to 150 lb. Cover	eWire Pro ⁷	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
		(52 gsm to 400 gsm) 5.5" x 5.83" to 13" x 51.2"		Paper Weight:	20 lb. Bond to 110 lb. Cover
	Paper Size: Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A			(75 gsm to 300 gsm)
		222 lb.		Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Weight:	20.3" W x 29.5" D x 48.3" H		Stack Capacity:	Up to 35 Books
	Dimensions:	20.2 W X 29.2 D X 40.2 H		Power Supply:	115 V, 60 Hz, 2.8A
Inspection	Paper Type:	Plain Paper, Coated Paper		Weight:	500 lb.
Unit-A1 ⁵	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)		Dimensions:	35.8" W x 31.3" D x 42.6" H
	Paper Size:	3.9" x 7.2" to 11.9" x 19.2"	Perfect	Finished	
	Detection Size:	0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm	Binder-F1 ⁵	Book Size:	5.4" x 8" to 8.5" x 11.7"
	Scanning Width:	Up to 11.9"		Book Thickness:1	10 to 200 Sheets (Up to 0.98")
	Inspection Works	tation		Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Tool OS: Mode:	Windows [®] 10 Pro Log Only Mode, Purge and		Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	Mode.	Recovery Mode			d: 3-Side Cut/1-Side Cut/No Cut
	Inspection Location:	Up to 64		Trim Range	Side edy i side edy i io ede
	Intensity Level:	·		Top/Bottom:	0.26" to 1.6"
	Objects:	Position Gap, Dot of Dirt, Streak of Dirt		Side:	0.26" to 1.95"
	Auto Recovery:	Yes (Purge and Recovery Mode Only)		Power Source:	208 V, 60 Hz, 3 A
	Purge Unit:	High Capacity Stacker-J1		Weight:	679 lb.
	Power Supply:	120 – 240 V, 50/60 Hz, 1.4 A		Dimensions:	36.3" W x 31.1" D x 51.2" H
	Weight:	109 lb.			
	D'	0.011 M 71.011 D 40.011 II			

9.8" W x 31.2" D x 40.9" H

Dimensions:

	ies (Continuea).				
High	Stack Capacity: 1	Up to 6,000 Sheets	Long Sheet	Stack Capacity: 1	100 Sheets
Capacity Stacker-J1	Top Tray Capacity: ¹	Up to 200 Sheets	Feeding and Catch Tray-D1 ⁹	Paper Size:	4" x 5.83" to 13" x 30"
	Paper Size:	5.5" x 7.2" to 13" x 19.2"			
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)	Long Sheet Catch Tray	Stack Capacity ¹ Up to 30":	Up to 300 Sheets
	Power Source:	100 – 240 V, 50/60 Hz, 2.5 A	XL-B1 ⁹	Up to 51.2":	Up to 10 Sheets
	Weight:	265 lb.		Paper Size:	4" x 5.83" to 13" x 51.2"
	Dimensions:	35.4" W x 29.3" D x 44.9" H		ruper oize.	4 X 3.03 (0 13 X 31.2
	Difficusions.)).4 W X Z /.) D X 44. / 11	Puncher	Paper Sizes	
Plockmatic	Stack Height		Unit-BS1 ¹²	2-Hole:	Legal, Letter-R, Custom Size
Multi Purpose	Sheets < 25.6":	Un to 11.8"			(7.2" x 7.2" to 11.7" x 17")
Stacker ⁸	Sheets > 25.6": Up to 5.3"			3-Hole:	11" x 17", Letter, Executive-R,
	Paper Size:	8.3" x 11" to 13" x 30"			Custom Size (9.5" x 7.2" to 11.7" x 17")
	Paper Weight:	100 lb. Text to 130 lb. Cover (148 gsm to 350 gsm)		Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Source:	100 – 240 V, 50/60 Hz, 2 A		Punch Waste Capacity:	Up to 6,000 Sheets
	Weight:	168 lb.			From the Finisher
	Dimensions:	41.8" W x 35.4" D x 26.8" H		Power Supply:	From the Finisher
		41.0 W X 7 7.4 D X 20.0 11	DFD Adapter	Paper Weight:	14 lb. Bond to 110 lb. Cover
Paper Folding Unit-K1 ⁹	Double Parallel Fold:	Legal, Letter-R	and Finisher Bridge-B1 ⁹	<u> </u>	(52 gsm to 300 gsm)
	C/Accordion Fold: Letter-R		Бладе-Бі	Supported Finishing:	Plockmatic BLM50/35 SDD BLM300C
	Z-Fold:	Letter-R, 11" x 17"		J	Plockmatic Multi Purpose Stacker
	Paper Weight:	14 lb. Bond to 28 lb. Bond		Requirements:	Staple/Booklet Finisher-AF1
	r aper weight.	(52 gsm to 105 gsm)		Weight:	168 lb.
	Power Source:	From Finisher		Dimensions:	35.8" W x 29.3" D x 46.9" H
	Weight:	157 lb.			
	Dimensions:	13.2" W x 31.2" D x 46.9" H	Booklet	Margin Trimming	: Front-edge Trim
			Trimmer-G1 ⁹	Trim Amount:	2 mm to 28 mm
Staple	Tray Capacity 1			Paper Weight:	14 lb. Bond to 110 lb. Cover
Finisher-AF1/	Top Tray:	Up to 1,000 Sheets			(52 gsm to 300 gsm)
Booklet	Lower Tray:	Up to 4,000 Sheets		Power Supply:	From the Finisher
Finisher-AF1	Paper Weight			Weight:	392 lb.
	Stacking:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)		Dimensions:	82.5" W x 31.1" D x 41" H
	Corner Stapling:	14 lb. Bond to 120 lb. Cover (52 gsm to 325 gsm)	Two-Knife	Margin Trimming	: Top and Bottom
	Booklet-	14 lb. Bond to 110 lb. Cover	Trimmer and	Trim Amount:	2 mm to 15 mm
	Making:	(52 gsm to 300 gsm)	Conveyor Set ¹⁰	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
		Corner, Double-Side		Power Supply:	120 V, 50/60 Hz, 2.5 A
	Paper Size Stapling:	7.2" x 8.3" to 11.7" x 17"		Weight:	320 lb.
		r: 8.3" x 11" to 13" x 19.2"		Dimensions:	21.1" W x 30.3" D x 41" H
	Stapling Capacity			Difficusions.	21.1 ** * * > 0.5 * D * +1 * 11
	Corner/ Double Side:1	Up to 100 Sheets	SDD Square-Fold	Booklet Capacity: ¹	Up to 25 Sheets
		Up to 25 Sheets	Square-rold Booklet-Maker ¹⁰		- г
	V-Fold:	Up to 5 Sheets without Stitch		Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Power Source:	120 – 240 V, 50/60 Hz, 8 A		Paper Weight:	16 lb. Bond to 110 lb. Cover
	Weight	ght taple Finisher: 287 lb.			(60 gsm to 300 gsm)
	•			Power Supply:	120 V, 60 Hz, 15 A
	Booklet Finishe	r:397 lb.		Weight:	154 lb.
	Dimensions:	31.5" W x 31.2" D x 48.8" H		Dimensions:	43.3" W x 23.6" D x 44.9" H

Finishing Accessories (Continued):

SDD Square-Fold	Booklet Capacity: ¹	Up to 25 Sheets
Booklet-Maker with Two-Knife Trim ¹⁰	Booklet Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Booklet Output Size:	4.7" x 7.9" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	2 mm to 35 mm
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	573 lb.
	Dimensions:	62.7" W x 27.6" D x 51.2" H
Plockmatic BLM50/35 Professional Booklet-Maker ⁸	Booklet Size:1	Up to 35/50 Sheets
	Paper Size:	8.1" x 10.8" to 12.6" x 18"
	Paper Weight	
	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	Trim Amount	
	Face: ¹¹	1 mm to 25 mm
	Top/Bottom: ¹²	5 mm to 30 mm
	Paper Rotating:12	8.1" x 10.9" to 9.1" x 12.7"
	Weight:	1,049 lb.
	Dimensions:	114.3" W x 33.8" D x 42.5" H

Print Servers

PRISMAsync Print Server ⁷	System Softwa	re: Version 8
	CPU:	Intel [®] Core i7 4770S @ 3.1 GHz
	Memory:	16 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 10
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	Optional:	Advanced Imposition, DP Link

imagePRESS
Server D3000


Fiery System:	FS500 Pro
CPU:	Intel® Core i5-6500 3.2GHz up to 3.6GHz with Turbo
Memory:	8 GB
Hard Drive:	2 TB
OS:	Windows® 10
Standard:	Fiery [®] Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command WorkStation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian

Graphic Arts Pro Package, Fiery Optional:

JobMaster, Color Profiler Suite, Fiery JobFlow, Operator Attention Light, Removable HDD, Integrated Interface,

and Stand-NX GL













As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.



0622R2-iPV1000SS-PDF-IH





¹ Based on 20 lb. Bond.

 $^{^{\}rm 2}$ Envelope Attachment Kit required.

³ POD Deck Lite-XL or Long Sheet Feed and Catch Tray-B1 required.

⁴ Multi Drawer Paper Deck-E1 or POD Deck Lite-C1 required.

⁵ Staple/Booklet Finisher-AF1 or High Capacity Stacker-J1 required.

⁶ High Capacity Stacker-J1 required.

⁷ Multi Function Professional Puncher-C1 required.

⁸ High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-B1 required.

⁹ Staple/Booklet Finisher-AF1 required.

¹⁰ Booklet Trimmer-K1 required.

¹¹ Optional trimmer required.

 $^{^{\}rm 12}$ Optional rotator required.