

# imageRUNNER ADVANCE C356iF C256iF

# imageRUNNER ADVANCE C356iF III Series

Color | Compact | Multifunction

Print up to 36 ppm (BW/color)

Scan up to 100 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" × 14"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



## WORKFLOW

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.




## **SECURITY**

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\* systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control<sup>2</sup> utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>3</sup>



# QUALITY AND

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V<sup>2</sup> color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.







- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR\* certified and rated EPEAT\* Gold.4

## **CONFIGURATION OPTIONS**



## **SPECIFICATIONS**

## Main Unit

Type

Color Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store, Fax (Line One Standard, Line Two Optional)

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory 3.0 GB RAM Hard Disk Drive

250 GB Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Ontional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),

USB 2.0 x1 (Device)

Serial Interface, Copy Control Interface Optional:

Paper Capacity (LTR, 20 lb. Bond) Standard: 650 Sheets

2,300 Sheets Maximum: Paper Sources (LTR, 20 lb. Bond)

550-sheet Paper Cassette, 100-sheet Stack Standard:

Bypass

Optional: 550-sheet Paper Cassette (CASSETTE

MODULE-AEI), 550-sheet Paper Cassette with cabinet (CASSETTE FEEDING UNIT-AJ1), Triple 550-sheet Paper Cassettes (CASSETTE FEEDING UNIT-AKI)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum 500 Sheets (with STAPLE FINISHER-Z1)

Finishing Capabilities

Standard: Collate, Group

With External

Cassette

Finisher: Collate, Group, Offset, Staple

Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy, Cassette: Pre-punched, Bond, Envelope Stack Bypass: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Labels, Bond,

Transparency, Envelope Thin, Plain, Recycled, Color, Heavy,

Module-AE1: Pre-punched, Bond

Cassette

Thin, Plain, Recycled, Color, Heavy, Feeding

Unit-AJ1: Pre-punched, Bond Cassette

Feeding Thin, Plain, Recycled, Color, Heavy,

Unit-AK1: Pre-punched, Bond

Supported Media Sizes

Paper Legal, Letter, Executive, Statement, Cassette 1: Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 7-1/2"

to 8-1/2" x 14")

Legal, Letter, Executive, Statement, Stack Bypass:

Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14"), Custom Size (3-7/8" x 5-7/8" to

8-1/2" x 14")

Cassette Legal, Letter, Executive, Statement,

Module-AE1: Custom Size (3-7/8" x 7-1/2" to

8-1/2" x 14")

Legal, Letter, Executive, Statement, Cassette Custom Size (3-7/8" x 5-7/8" to

Feeding Unit-AJ1: 8-1/2" x 14")

Legal, Letter, Executive, Statement, Cassette Custom Size (3-7/8" x 7-1/2" to

Feeding Unit-AK1: 8-1/2" x 14") Supported Media Weights

16 lb. Bond to 60 lb. Cover (60 to 163 g/m²) 16 lb. Bond to 80 lb. Cover (60 to 220 g/m²) 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²) Cassettes: Stack Bypass: Duplexing:

Print/Copy Speed (BW and Color)

Up to 36 ppm (Letter); C356iF III: Up to 29 ppm (Legal)

C256iF III: Up to 26 ppm (Letter); Up to 21 ppm (Legal)

Warm-up Time

From Power On: Approx. 10 Seconds<sup>5</sup> From Sleep Approx. 10 Seconds<sup>6</sup> Mode: Approx. 4 Seconds<sup>7</sup>

Quick Startup Mode:

Dimensions (W x D x H) Standard 20-1/8" x 25-5/8" x 25-1/8" (Desktop): (511 mm x 651 mm x 639 mm)

With Cassette

20-1/8" x 25-5/8" x 41-7/8" Feeding Unit-AJ1 or AK1: (511 mm x 651 mm x 1064 mm)

Installation Space (W x D) 33-1/2" x 35-3/4" (852 mm x 908 mm)

Basic. With Staple

55-3/8" x 35-3/4" (1407 mm x 908 mm) Finisher-Z1:

Weight<sup>8</sup> Standard

(Desktop): Approx. 108 lb. (49 kg)

With Cassette Feeding Unit-

Approx. 143.3 lb. (65 kg)

With Cassette Feeding Unit-

Approx. 149.9 lb. (68 kg) With Cassette

Module-AE1: Approx. 130.1 lb. (59 kg)

## **Print Specifications**

Print Resolution (dpi)

1200 x 600

Standard Page Description Languages

UFR II, PCL®6, Adobe® PS® 3

**Direct Print** 

Available from USB, Advanced Box, Remote UI,

and Web Access9

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and

Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internetconnected devices and cloud-based services depending on your requirements.10

Fonts

93 Roman, 10 Bitmap fonts, 2 OCR fonts, PCL fonts:

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),11

Barcode Fonts<sup>12</sup> PS fonts: 136 Roman

Operating System<sup>13</sup>

UFRII/PS Windows®/Server 2008/Windows® 7/ Server 2008 R2/Server 2012/Windows 8.1/

Server 2012 R2/Windows 10/MAC OS X (10.9 or later)

PCL: Windows Server 2008/Windows 7/Server

2008 R2/Server 2012/Windows 8.1/Server

2012 R2/Windows 10

PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

## Copy Specifications

First-Copy-Out Time (LTR)

As fast as 5.1 seconds (BW)/ C356iF III:

6.9 seconds (Color) As fast as 6.9 seconds (BW)/ 9.4 seconds (Color)

Copy Resolution (dpi)

Reading: 600 x 600 Printing: 2400 x 600

**Multiple Copies** Up to 999

Magnification

C256iF III:

25%-400% (1% Increments)

Preset Reductions

50%, 64%, 78%

**Preset Enlargements** 

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

**Special Copy Features** 

Two-sided Original, Finishing, Job Build, N on 1, Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Copy ID Card, Skip Blank Pages, Job Done Notice, Copy ID Card, Multi Sheet Feed Detection

## Scan Specifications

Single-pass Duplexing Automatic Document Feeder<sup>14</sup>

**Document Feeder Paper Capacity** 

100 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

Legal, Letter, Statement

**Document Feeder Supported Media Weights** 

BW: 12 lb. Bond to 32 lb. Bond (42 to 128 g/m²) One-sided Scanning: Color: 17 lb. Bond to 32 lb. Bond (64 to 128 g/m²) BW: 13 lb. Bond to 32 lb. Bond (50 to 128 g/m<sup>2</sup>) Two-sided Color: 17 lb. Bond to 32 lb. Bond (64 to 128 g/m²) Scanning:

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 1-1/4"

(30 mm), Weight: Up to 4.4 lb. (2kg)]

Color Network ScanGear2 for both Twain and WIA Supported OS: Windows 7/8.1/10/

Supported OS:

Server 2008/Server 2008 R2/

Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200.

200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (LTR)

Single-sided Scanning (BW and Color): 50 ipm (300 dpi)/30 ipm (600 dpi) Double-sided Scanning (BW and Color): 100 ipm (300 dpi)/50 ipm (600 dpi)

## **Send Specifications**

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail

Box, Super G3 Fax, IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,

200 x 100, 150 x 150, 100 x 100

Communication Protocol FTP (TCP/IP), SMB v3.0, WebDAV SMTP, POP3 File:

Email:

File Format

Standard

TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Limited Color, Device Signature), XPS (Compact, Searchable, Device

Signature), Office Open XML

(PowerPoint®, Word) Optional: PDF(Trace & Smooth, User Signature), XPS

(User Signature)

**Universal Send Features** 

Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

## Fax Specifications

Maximum Number of Connection Lines

2 (Line One Standard, Line Two Optional)

Modem Speed

33.6 Kbps Super G3: G3: 14.4 Kbns Compression Method MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement to Legal Fax Memory Up to 30,000 Pages Speed Dials

Group Dials/Destinations

Max. 199 Dials

Max. 200

Sequential Broadcast Max. 256 Addresses

Memory Backup

Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

#### Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.) SMR-WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

## **Advanced Box Features**

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

## Security Specifications

## Authentication

Standard-Universal Login Manager, uniFLOW Online

Express, 15 User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in,

McAfee Embedded Control<sup>2</sup>

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup

IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Optional: Network

Standard: Encrypted Secure Print, IP/Mac Address

Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermarks, Secure Print, Adobe

LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Device Signature User Signatures, Document Scan Lock

Ontional:

## **Environmental Specifications**

Operating Environment Temperature: 50 to 86 °F

20 to 80 % RH (Relative Humidity) Humidity:

Power Requirements 120-127V AC 60 Hz, 6.9 A Plug (Main Unit)

**NEMA 5-15P** 

**Power Consumption** 

Maximum: Approx. 1,500 W Standby: Approx. 38.9 W16 Sleep Mode: Approx. 0.8 W or Less<sup>17</sup> Typical Electricity Consumption (TEC) Rating<sup>18</sup>

C356iF III: Ó.35 kWh C256iF III: 0.25 kWh

Standards

ENERGY STAR® Certified Rated EPEAT® Gold

## Consumables

Toner

GPR-58 Toner

Toner Yield (Estimated @ 5% Coverage)

Black 23,000 Images Color (C,M,Y): 18,000 Images

- Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
- <sup>2</sup> Requires Unified Firmware Platform v3.9.
- 3 Requires additional option
- <sup>4</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net
- Time from device power-on, until copy ready (not print
- <sup>6</sup> Time from exiting Sleep mode to when printing is operational.
- $^{\prime}$  Time from device power-on to when copy jobs can be programmed.
- Includes consumables
- <sup>9</sup> PDF print from Web sites is supported.
- 10 For more information, including compatibility, please visit https://www.usa.canon.com/mobile-app.
- Requires the optional PCL International Font Set-Al.
- 12 Requires the optional Barcode Printer Kit-D1.
- Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- Detect Feeder Multi Sheet Feed is supported
- $^{\rm 15}$  No charge for this solution; however activation is required.
- 16 Reference value (measured one unit).
- 17 0.8 W sleep mode not available in all circumstances due to certain settings.
- Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C356iF III Series Specifications document.



For more information, call or visit 1.800.815.4000 CSA.CANON.COM







1019R2-CSAiRAC356IISRSB-PDF-IH







As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that was of its features will provide requisit issues. Nothing begins being begins the security in the countries of the security of your devices. and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America Sales Representative for details. Products shown with optional accessories. Canon U.S.A. and Canon Solutions America do not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.







CANON SOLUTIONS AMERICA



Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.