4300C SERIES 14" CONCEALED CASEMENT HINGE 3/8 1 1/4 4 3/8 -7/16 Safety Screw Hole 8 Holes Coined **Brass Pivot** for #7 Flat Hd. $(\emptyset.283 \text{ Min. Hd.})$ Notched Track 4.811 3 5/16 7 5/8 23/32 1 1/4 Track "Slide" opening flared for ease of assembling Sash to Frame. NOTE: Sash arm screw holes are located from end of track. 1/8" High Tensile 1 1/4 Steel Arms-Stainless Steel Slide Clip-7/16 5/16 Stainless Steel Track Extra Sash Arm Support to Left Hand Hinge Shown Prevent Shipping High Strength Damage Low Friction Celcon slide with Stainless Insert. 90° Slide Track 6 53/64 All Steel parts are Zinc PART NUMBERS Dichromate plated, and Powder painted with TRACK 3314B-L/R13 90° Arm Stop ARM ASSEMBLY 4014DC-L/R ASSEMBLED HINGE 4314DC-L/R TGIC Polvester. L METAL STAMPING, INC.



411 W. Spruce St. PO Box 485 Abbotsford, WI 54405 www.AllMetalStamping.com

Phone (715) 223-6324 Fax (715) 223-3352