DROP-ARM CARE CLINER

6550 (STANDARD, NYLON CASTERS) / 6551 (STANDARD, STEEL CASTERS) 6570 (XL, NYLON CASTERS) / 6571 (XL, STEEL CASTERS)



VERSATILITY, VALUE AND QUALITY

Our Dro-Arm Care Cliner comes with all the superior features you might find on higher-priced clinical chairs and make it easier for caregivers to assist their patients!



ANATOMY OF A DROP-ARM CARE CLINER

Trendelenberg release on back with easy-access handle .

Non-porous, fold-down side tray contains small spills. Standard on right and left side.

One-touch release drop-arms

Total-lock and directional-lock casters provide ease of maneuverability. *Available in nylon or steel.



SPECIFICATIONS

MODELS	6550 / 6551	6570 / 6571
DESCRIPTIONS	STANDARD SIZE	XL SIZE
Seat Height	21" (53.3 cm)	21" (53.3 cm)
Seat Width	21" (53.3 cm)	25" (63.5 cm)
Seat Depth	20" (51 cm)	20" (51 cm)
Overall Height	49" (124.5 cm)	49" (124.5 cm)
Overall Width*	33.75" (85.73 cm)	37.75" (95.9 cm)
Back Height above Seat	31.5" (80 cm)	31.5" (80 cm)
Overall Length (Upright)	40" (101.6 cm)	43" (109.2 cm)
Overall Length (Reclined)	76.5" (194.3 cm)	76.5" (194.3 cm)
Armrest Height	27" (68.6 cm)	27" (68.6 cm)
Weight	105 lbs (47 kg)	111 lbs (50.4 kg)
Weight Capacity	275 lbs (124.7 kg)	450 lbs (204 kg)
* Add 9.25" to Overall Chair Width for each raised side table.		

OPTIONS



Leg Extensions (SE)



Side Cushions (SC)



IV Pole (IV)



Heat Only (H)



Heat and Massage (HM)

WARRANTY Contact Winco or visit our website for warranty details.

COLORS Vsit our website or contact Winco for available color selections and/or swatches

NOTE Winco reserves the right to change specifications without notice.

CERTIFICATIONS 1) Winco recliners meet ANSI/BIFMA X5.4 for reliability testing 2) Winco foam meets California Technical Bulletin 117, Flammability Test Procedure for Resilient Filling Materials used in Upholstered Furniture 3) NR or TB options are available. NR meets AB2998 regulations and TB meets NFPA 101 and ASTM E1537-16 Standards for Upholstered Furniture 4) Heat and Massage, Heat Only Options: Meets electrical safety standards, UL 1647 and CAN/CSA-C22.2 No.68-92



CONTACT US

 $\label{thm:contract} \mbox{To arrange a demonstration or to speak with one of our associates, please feel free to contact us at: \\$