



STUDS - RECOMMENDED COIL WIDTHS

Member	Recommended Coil Width (in.)
162S125	4.25

Member	Recommended Coil Width (in.)
250S125	5.125
250S162	6.5

Member	Recommended Coil Width (in.)
350S125	6.125
350S162	7.375
350S200	8.375
350S250	9.375

Member	Recommended Coil Width (in.)
362S125	6.25
362S162	7.5
362S200	8.5
362S250	9.5
362S300	10.5

Member	Recommended Coil Width (in.)
400S125	6.625
400S162	7.875
400S200	8.875
400S250	9.875
400S300	10.875

Member	Recommended Coil Width (in.)
550S125	8.125
550S162	9.375
550S200	10.375

Member	Recommended Coil Width (in.)
600S125	8.625
600S162	9.875
600S200	10.875
600S250	11.875
600S300	12.875

Member	Recommended Coil Width (in.)
800S162	11.875
800S200	12.875
800S250	13.875
800S300	14.875

Member	Recommended Coil Width (in.)
162T125 (S)	4.125
162T150 (S)	4.625

Member	Recommended Coil Width (in.)
250T125 (S)	5
250T150 (S)	5.5
250T200 (S)	6.5
250T250 (S)	7.5

Member	Recommended Coil Width (in.)
350T125 (S)	6
350T150 (S)	6.5
350T200 (S)	7.5
350T250 (S)	8.5

Member	Recommended Coil Width (in.)
362T125 (S)	6.125
362T150 (S)	6.625
362T189 (S)	7.5
362T200 (S)	7.625
362T239 (S)	8.5
362T250 (S)	8.625
362T289 (S)	9.5
362T300 (S)	9.625

Member	Recommended Coil Width (in.)
400T125 (S)	6.5
400T150 (S)	7
400T189 (S)	7.875
400T200 (S)	8
400T239 (S)	8.875
400T250 (S)	9
400T289 (S)	9.875
400T300 (S)	10

Member	Recommended Coil Width (in.)
550T125 (S)	8
550T150 (S)	8.5
550T200 (S)	9.5
550T250 (S)	10.5
550T300 (S)	11.5

Member	Recommended Coil Width (in.)
600T125 (S)	8.5
600T150 (S)	9
600T189 (S)	9.875
600T200 (S)	10
600T239 (S)	10.875
600T250 (S)	11
600T289 (S)	11.875
600T300 (S)	12

Member	Recommended Coil Width (in.)
800T125 (S)	10.5
800T150 (S)	11
800T189 (S)	11.875
800T200 (S)	12
800T239 (S)	12.875
800T250 (S)	13
800T289 (S)	13.875
800T300 (S)	14



NARROW TRACKS - RECOMMENDED COIL WIDTHS

Member	Recommended Coil Width (in.)
362T125 (N)	6
362T150 (N)	6.5
362T199 (N)	7.5
362T249 (N)	8.5
362T299 (N)	9.5

Member	Recommended Coil Width (in.)
400T125 (N)	6.375
400T150 (N)	6.875
400T199 (N)	7.875
400T249 (N)	8.875
400T299 (N)	9.875

Member	Recommended Coil Width (in.)
600T125 (N)	8.375
600T150 (N)	8.875
600T199 (N)	9.875
600T249 (N)	10.875
600T299 (N)	11.875

Member	Recommended Coil Width (in.)
800T125 (N)	10.375
800T150 (N)	10.875
800T199 (N)	11.875
800T249 (N)	12.875
800T299 (N)	13.875