

STUDS

Member	Recommended Coil Width (in.)
362S162	7.5
362S200	8.5
362S250	9.5

Member	Recommended Coil Width (in.)
600S162	9.875
600S200	10.875
600S250	11.875

Member	Recommended Coil Width (in.)
800S162	11.875
800S200	12.875
800S250	13.875

STANDARD TRACKS

Member	Recommended Coil Width (in.)
362T125 (S)	6.25
362T150 (S)	6.75
362T189 (S)	7.5
362T200 (S)	7.75
362T239 (S)	8.5
362T250 (S)	8.75
362T289 (S)	9.5

Member	Recommended Coil Width (in.)
600T125 (S)	8.625
600T150 (S)	9.125
600T189 (S)	9.875
600T200 (S)	10.125
600T239 (S)	10.875
600T250 (S)	11.125
600T289 (S)	11.875

Member	Recommended Coil Width (in.)
800T125 (S)	10.625
800T150 (S)	11.125
800T189 (S)	11.875
800T200 (S)	12.125
800T239 (S)	12.875
800T250 (S)	13.125
800T289 (S)	13.875

NARROW TRACKS

Member	Recommended Coil Width (in.)
362T125 (N)	6
362T150 (N)	6.5
362T199 (N)	7.5
362T249 (N)	8.5
362T299 (N)	9.5

Member	Recommended Coil Width (in.)
600T125 (N)	8.375
600T150 (N)	8.875
600T199 (N)	9.875
600T249 (N)	10.875
600T299 (N)	11.875

Member	Recommended Coil Width (in.)
800T125 (N)	10.375
800T150 (N)	10.875
800T199 (N)	11.875
800T249 (N)	12.875
800T299 (N)	13.875