

BELDEN

Audio Video Solutions



Be certain.

Audio Video Solutions by Belden

A complete set of products designed specifically for audio distribution, video display, automation and lighting control.

Belden is the trusted brand in audio video cabling and connectivity. The AV industry has come to rely on our proven track record of innovation, quality, and consistency. Belden upholds its reputation with warranties unmatched in the industry.

Our product offering includes traditional audio and video, networking and fiber optic cable and connectivity.

Whether integrating analog, digital, fiber transport, or IP-based systems, Belden can offer a solution for your installation needs. Our products are designed to support communications protocols like HDBaseT®, SDVoE, HDMI, and IEEE AVB/TSN.

These products are locally available through one of our channel network's 1600 locations nationwide. Belden and our channel partners also offer a number of technical and value-added services to ensure the successful planning, deployment, and profitability of AV installations.

LEED, or Leadership in Energy and Environmental Design, has changed the way we think about how buildings and communities are planned, constructed, maintained and operated. LEED's purpose is to create buildings that are resource efficient, using less energy and water to reduce greenhouse gas emissions. Through several certification processes, Belden's products are being awarded with EPDs, MHAs, and HPDs to help our customers reach their LEED certification goals.

 LEED Qualified Product

AMX, AXLINK, and DXLink are either trademarks or registered trademarks of AMX, LLC registered in the U.S. and other countries. DMX is either a trademark or a registered trademark of DMX, Inc. EcoSystem, HomeWorks, Grafik Eye, Sivoia, and Lutron are either trademarks or registered trademarks of Lutron Electronics Co., Inc. SDVoE is a trademark of the SDVoE Alliance.

Table of Contents

4K Ultra-High-Definition Media Cable	3	Molded AV Assembly Solutions	14-15
4K Ultra-High-Definition Media Cable	3	Perfect Path™ Locking HDMI - 800 Series	14
4K UHD Media Patch Cords for HDBaseT®	3	High Speed HDMI	14
REVConnect Shielded Jacks and Plugs	3	Mini HDMI to Standard HDMI	14
REVConnect Tools and Accessories	3	Micro HDMI to Standard HDMI	14
Shielded Field-Mount Plug and Tool	3	Dual Link DVI-D	15
		Single Link DVI-D	15
Copper Structured Cabling Solutions	4	Dual Link DVI-I	15
10GX Shielded Cabling System (Category 6A)	4	Single Link DVI-I	15
10GX Unshielded Cabling System (Category 6a)	4	Standard VGA	15
CAT6+ Shielded Cabling System (Category 6)	4		
CAT5E Shielded Cabling System (Category 5e)	4	AV Multimedia Modules and Face Plates	16-17
		KeyConnect AV Multimedia Modules, Copper	16
Modular Connectivity	5	KeyConnect AV Multimedia Modules, Fiber	16
REVConnect 10GX, CAT6+, CAT5E Shielded Jacks, Shielded and Unshielded Plugs	5	KeyConnect Faceplates	17
REVConnect 10GX Category 6A	5	KeyConnect Tamper Resistant Faceplates	17
REVConnect CAT6+ Category 6	5	MediaFlex Angled Inserts	17
REVConnect CAT5E Category 5e	5	MediaFlex Angled Edge Faceplates and Kits	17
REVConnect Tool and Accessories	5	Tools	17
		Copper Patch Cords	18
Audio Cable Solutions	6-7	SmartPart Number Patch Cord Configurator	18
Shielded Audio Cables — Stranded Conductor	6	Traceable Bonded-Pair Patch Cords	18
Shielded Audio Cables — Solid Conductor	6	Small OD Copper Patch Cords	18
Shielded Pro Audio and Intercom Cables — Low Capacitance	6		
Nurse Call Cables	7	Fiber Structured Cabling Solutions	19
SimplexGrinnell™ EZ Care™ Nurse Call System	7	SmartPart Number Bulk Fiber Configurator	19
ASCOM Telligence Nurse Call System	7		
		FiberExpress (FX) Field Termination Connectors	19
Speaker Cable Solutions	8	FX Brilliance Universal Mechanical Connectors	19
Speaker Cables — Stranded Conductor	8	FX Brilliance Accessories	19
High-Flex Speaker Cables - Bare Copper	8	FX Fusion Splice-On Connectors	19
Speaker Cables — Solid Bare Copper Conductor	8	FX Fusion Accessories	19
		FiberExpress (FX) Enterprise Closet X (ECX) 20	
Media Automation and Lighting Control Solutions	9-10	FX ECX Housings	20
AMX® Systems	9	FX ECX Kits/Accessories	20
Lutron® Systems	9	FX ECX Standard Splice Cassettes	20
DMX® Systems	9	FX ECX Tailored Splice Cassettes	20
Crestron® Digital Media (DM) Ultra for HDBaseT®	9	FX ECX Standard Frames/Adapter Strips	20
Crestron® Cresnet™ Systems	9	FX ECX Tailored Frames	20
Crestron® Digital Media (DM) 8G™ Systems	10		
CresFiber 8G™ Systems or HDMI over Fiber	10	Rack and Cabinet Systems	21
		2 and 4 Post Racks	21
50 Ω RF Cables	10	Vertical Cable Managers	21
50 Ω Wireless Transmission Cables	10	Wall-Mount Cabinets	21
50 Ω MIL-C-17G QPL Cables	10		
		Part Number Index	22-23
Video Distribution and Display Solutions	11	Customer Service and Other Belden Contacts	Back Cover
HD-SDI Coax Cables	11		
Mini Hi-Res Coax Cables	11		
CATV Coax Cables	11		
Coaxial Connectivity Solutions	12-13		
BNC Compression Video Connectors	12		
F Compression Video Connectors	13		

Be certain.

4K Ultra-High-Definition Media Cable


Belden 4K UHD Media Cables were designed specifically for optimal performance in 4K HDBaseT® transmission. These shielded cables deliver 4K content over 100 meters in a unique, small, sleek design. Combined with either standard field-mount plugs or Belden's new REVConnect connectivity system, it is the easiest to install, most reliable HDBaseT® cabling solution available!

For maximum transmission distance use Belden 4K UHD Media Patch Cords made with 2183R cable. Testing in Belden labs has proven that to maximize channel reach, patch cords must have the same insertion loss and other characteristics as the horizontal cable. Special lengths and colors available upon request.

HDBT[™]
Recommended Cable

POH[™]
Power over HDBaseT

4K Ultra-High-Definition Media Cable

	Description	Nom. Diameter		Bend Radius		Flame Rating	Belden Part Number		
		Inches	mm	Inches	mm		Blue	White	Black
	Plenum, 4pr 23AWG F/UTP, Reel-in-a-box	0.26	6.6	1	25.4	FT6	2183P D15A1000	2183P 009A1000	2183P 010A1000
	Plenum, 4pr 23AWG F/UTP, Reel-in-a-box	0.26	6.6	1	25.4	FT6	—	—	2183P 010A250
	Plenum, 4pr 23AWG F/UTP, Reel	0.26	6.6	1	25.4	FT6	—	—	2183P 0101000
	Riser, 4pr 23AWG F/UTP, Reel-in-a-box	0.29	7.4	1.2	30.5	FT4	2183R 006A1000	2183R 009A1000	2183R 010A1000
	Riser, 4pr 23AWG F/UTP, Reel	0.29	7.4	1.2	30.5	FT4	—	—	2183R 0101000


Custom colors available upon request, subject to minimum order quantity. Conductor color code: White/Blue and Blue, White/Orange and Orange, White/Green and Green, White/Brown and Brown.

4K UHD Media Patch Cords for HDBaseT®

Example: AV2183R100005 (2183R cable, RJ45 on each end, CMR rated, black, 5 foot)

Part number example from configuration shown below:

AV2183R100005


	AV2183R1		00	005
	Prefix	4K UHD Media Cable - HDBaseT®, CMR	Color Code	Length (ft)
	AV2183R1	4K UHD Media Cable - HDBaseT®, CMR	00	002
			06	003
			09	004



REVConnect Shielded Jacks and Plugs

	Package Size	Shielded Jacks	Shielded Plugs
		Single Pack	RVAMJKSME-S1
	Bulk Pack (24 Modules)	RVAMJKSME-B24	RVAFPSME-B24

REVConnect Tools and Accessories

	Universal Termination Tool	Tool Spare Blade Set	Cable Prep Tool Replacement	Tool Belt Clip	Dust Caps for Jacks	Icons for Jacks	Bulk Pack of REVConnect Cores
		RVUTT01	RVUTB01	RVUCT01	RVUTC01	RVUDCXX-B24	RVUICXX-B24
	Includes tool, cable prep insert and spare blade set	Optional extra set of blades with Allen key included	Optional cable prep tool replacement insert	Optional belt clip for universal tool	Optional dust caps for all jacks; XX is color code, pack of 24	Optional icons for all jacks; XX is color code, pack of 24	Bulk pack of 50 cable managers and caps

Color codes: AL (almond), BK (black), BL (blue), BR (brown), EW (electric white), GN (green), GY (gray), OR (orange), PR (purple), RD (red), YL (yellow), TB (TIA blue), TG (TIA green), TN (TIA brown), TO (TIA orange), TP (TIA purple), TR (TIA red), TY (TIA yellow)

Shielded Field-Mount Plug and Tool

	Description	Belden Part Number
		Shielded Field-Mount Plug T568A/B - Large
	Parallel Plier	CTPFM01

Note: F/UTP = Overall foil shield, unshielded twisted pairs

HDBaseT[™], POH and the HDBaseT[®] Alliance logo are trademarks of the HDBaseT[®] Alliance.

Belden now offers first-of-its-kind HDBaseT[®] System 25-year warranty! For more details on how to find an authorized installer visit www.belden.com/find-a-certified-installer.

Copper Structured Cabling Solutions

10GX Shielded Cabling System (Category 6A)

Description	Belden Part Number				
	Blue	Gray	White	Black	Metallic
10GX, Category 6A, Bonded-Pair, F/UTP, Riser	10GX62F 0061000	10GX62F 0081000	10GX62F 0091000	10GX62F 0101000	—
10GX, Category 6A, Bonded-Pair, F/UTP, Plenum	10GX63F D151000	10GX63F 0081000	10GX63F 0091000	10GX63F 0101000	—
10GX, Category 6A, F/UTP, Riser	10GX52F 0061000	10GX52F 0081000	10GX52F 0091000	10GX52F 0101000	—
10GX, Category 6A, F/UTP, Plenum	10GX53F D151000	10GX53F 0081000	10GX53F 0091000	10GX53F 0101000	—
REVConnect Cat 6A Shielded Plug	—	—	—	—	RVAFPSME-S1
REVConnect Cat 6A Shielded Jack	—	—	—	—	RVAMJKSME-S1
Shielded Field Mount Plug T568A/B - Large	—	—	—	—	CAPFMFL-S1
Shielded Modular Jack	—	—	—	—	AX104562
Shielded Modular Patch Panel, 24-Port, 1U (Empty)	—	—	—	—	AX104563
Shielded Modular Patch Panel, 48-Port, 2U (Empty)	—	—	—	—	AX104564
Shielded Patch Cord, 4-Pair, T568A/B-T568A/B, Non Plenum	CAF1106XXX	CAF1108XXX	CAF1109XXX	CAF1100XXX	—

10GX Unshielded Cabling System (Category 6A)

Description	Belden Part Number				
	Blue	Purple	White	Black	Metallic
10GXS, Small Diameter, Category 6A, Bonded-Pair, UTP, Riser	10GXS32 0061000	10GXS32 0071000	10GXS32 0091000	10GXS32 0101000	—
10GXS, Small Diameter, Category 6A, Bonded-Pair, UTP, Plenum	10GXS33 D151000	10GXS33 0071000	10GXS33 0091000	10GXS33 0101000	—
10GX, Category 6A, Bonded-Pair, UTP, Riser	10GX32 0061000	—	10GX32 0091000	—	—
10GX, Category 6A, Bonded-Pair, UTP, Plenum	10GX33 D151000	—	10GX33 0091000	—	—
REVConnect Cat 6A UTP Plug	—	—	—	—	RVAFPUBK-S1
REVConnect Cat 6A UTP Jack	RVAMJKUBL-S1	RVAMJKUPR-S1	RVAMJKUEW-S1	RVAMJKUBK-S1	—
UTP Field Mount Plug T568A/B - Large	—	—	—	—	CAPFMUL-S1
KeyConnect Modular Jack	AX104156	AX104157	AX102282	AX102283	—
KeyConnect Patch Panel, 24-Port, 1U (Preloaded)	—	—	—	—	AX103254
KeyConnect Patch Panel, 48-Port, 2U (Preloaded)	—	—	—	—	AX103256
KeyConnect Patch Panel, 24-Port, 1U (Empty)	—	—	—	—	AX103114
KeyConnect Patch Panel, 48-Port, 1U (Empty)	—	—	—	—	AX103121
KeyConnect Patch Panel, 48-Port, 2U (Empty)	—	—	—	—	AX103115
Unshielded Patch Cord, 4-pair, 24 AWG Solid, T568A/B - T568A/B, CMR	CA21106XXX	CA21107XXX	CA21109XXX	CA21100XXX	—

CAT6+ Shielded Cabling System (Category 6)

Description	Belden Part Number				
	Blue	Gray	White	Black	Metallic
DataTwist 2400, F/UTP, Riser	2412F 0061000	2412F 0081000	2412F 0091000	2412F 0101000	—
DataTwist 2400, F/UTP, Plenum	2413F D151000	2413F 0081000	2413F 0091000	2413F 0101000	—
DataTwist 6, F/UTP, Riser	1351A 0061000	1351A 0081000	1351A 0091000	—	—
DataTwist 6, F/UTP, Plenum	1352A D151000	1352A 0081000	1352A 0091000	—	—
REVConnect Shielded Plug	—	—	—	—	RVAFPSME-S1
REVConnect Cat 6+ Shielded Jack	—	—	—	—	RV6MJKSME-S1
Shielded Field Mount Plug T568A/B - Large	—	—	—	—	CAPFMFS-S1
Shielded Modular Jack	—	—	—	—	AX104595
Shielded Modular Patch Panel, 24-Port, 1U (Empty)	—	—	—	—	AX104563
Shielded Modular Patch Panel, 48-Port, 2U (Empty)	—	—	—	—	AX104564
Shielded Patch Cord, 4-Pair, T568A/B-T568A/B, Non Plenum	C6F1106XXX	C6F1108XXX	C6F1109XXX	C6F1100XXX	—

CAT5E Shielded Cabling System (Category 5e)

Description	Belden Part Number				
	Blue	Gray	White	Black	Metallic
DataTwist 1200, F/UTP, Riser	1212F 0061000	1212F 0081000	1212F 0091000	1212F 0101000	—
DataTwist 1200, F/UTP, Plenum	1213F D151000	1213F 0081000	1213F 0091000	1213F 0101000	—
DataTwist 5e, F/UTP, Riser	1533R 0061000	1533R F2V1000	1533R 0091000	1533R 0101000	—
DataTwist 5e, F/UTP, Plenum	1533P D151000	1533P 0081000	—	1533P 0101000	—
REVConnect Shielded Plug	—	—	—	—	RVAFPSME-S1
REVConnect Cat 5E Shielded Jack	—	—	—	—	RV5MJKSME-S1
Shielded Field Mount Plug T568A/B - Small	—	—	—	—	CAPFMFS-S1
Shielded Modular Jack	—	—	—	—	AX104595
Shielded Modular Patch Panel, 24-Port, 1U (Empty)	—	—	—	—	AX104563
Shielded Modular Patch Panel, 48-Port, 2U (Empty)	—	—	—	—	AX104564
Shielded Patch Cord, 4-Pair, T568A/B-T568A/B, Non Plenum	C5F1106XXX	C5F1108XXX	C5F1109XXX	C5F1100XXX	—

LEED Qualified Product Use XXX to specify length in feet for Patch Cords. Some products available in additional colors


Be certain.

Modular Connectivity

REVConnect is a revolutionary connectivity system which offers a reliable and easy termination method with unparalleled versatility.

REVConnect 10GX, CAT6+, CAT5E Shielded Jacks, Shielded and Unshielded Plugs

Package Size	10GX Shielded Jacks	CAT6+ Shielded Jacks	CAT5E Shielded Jacks	10GX Shielded Plugs	10GX UTP Plugs
Single Pack	RVAMJKSME-S1	RV6MJKSME-S1	RV5MJKSME-S1	RVAFPSME-S1	RVAFPUBK-S1
Bulk Pack (24 Modules)	RVAMJKSME-B24	RV6MJKSME-B24	RV5MJKSME-B24	RVAFPSME-B24	RVAFPUBK-B24



REVConnect 10GX Category 6A

Description	Elec White	Black	Gray	Ivory	Almond
REVConnect 10GX Jack - Single Pack	RVAMJKUEW-S1	RVAMJKUBK-S1	RVAMJKUGY-S1	RVAMJKUIV-S1	RVAMJKUAL-S1
REVConnect 10GX Jack - Bulk Pack	RVAMJKUEW-B24	RVAMJKUBK-B24	RVAMJKUGY-B24	RVAMJKUIV-B24	RVAMJKUAL-B24

10GX



Description	Brown	Red	Orange	Yellow	Green	Blue	Purple
REVConnect 10GX Jack - Single Pack	RVAMJKUBR-S1	RVAMJKURD-S1	RVAMJKUOR-S1	RVAMJKUYL-S1	RVAMJKUGN-S1	RVAMJKUBL-S1	RVAMJKUPR-S1
REVConnect 10GX Jack - Bulk Pack	RVAMJKUBR-B24	RVAMJKURD-B24	RVAMJKUOR-B24	RVAMJKUYL-B24	RVAMJKUGN-B24	RVAMJKUBL-B24	RVAMJKUPR-B24

REVConnect CAT6+ Category 6

Description	Elec White	Black	Gray	Ivory	Almond
REVConnect CAT6+ Jack - Single Pack	RV6MJKUEW-S1	RV6MJKUBK-S1	RV6MJKUGY-S1	RV6MJKUIV-S1	RV6MJKUAL-S1
REVConnect CAT6+ Jack - Bulk Pack	RV6MJKUEW-B24	RV6MJKUBK-B24	RV6MJKUGY-B24	RV6MJKUIV-B24	RV6MJKUAL-B24

CAT6+



Description	Brown	Red	Orange	Yellow	Green	Blue	Purple
REVConnect CAT6+ Jack - Single Pack	RV6MJKUBR-S1	RV6MJKURD-S1	RV6MJKUOR-S1	RV6MJKUYL-S1	RV6MJKUGN-S1	RV6MJKUBL-S1	RV6MJKUPR-S1
REVConnect CAT6+ Jack - Bulk Pack	RV6MJKUBR-B24	RV6MJKURD-B24	RV6MJKUOR-B24	RV6MJKUYL-B24	RV6MJKUGN-B24	RV6MJKUBL-B24	RV6MJKUPR-B24

REVConnect CAT5E Category 5e

Description	Elec White	Black	Gray	Ivory	Almond
REVConnect CAT5E Jack - Single Pack	RV5MJKUEW-S1	RV5MJKUBK-S1	RV5MJKUGY-S1	RV5MJKUIV-S1	RV5MJKUAL-S1
REVConnect CAT5E Jack - Bulk Pack	RV5MJKUEW-B24	RV5MJKUBK-B24	RV5MJKUGY-B24	RV5MJKUIV-B24	RV5MJKUAL-B24

CAT5E



Description	Brown	Red	Orange	Yellow	Green	Blue	Purple
REVConnect CAT5E Jack - Single Pack	RV5MJKUBR-S1	RV5MJKURD-S1	RV5MJKUOR-S1	RV5MJKUYL-S1	RV5MJKUGN-S1	RV5MJKUBL-S1	RV5MJKUPR-S1
REVConnect CAT5E Jack - Bulk Pack	RV5MJKUBR-B24	RV5MJKURD-B24	RV5MJKUOR-B24	RV5MJKUYL-B24	RV5MJKUGN-B24	RV5MJKUBL-B24	RV5MJKUPR-B24

REVConnect Tool and Accessories

Universal Termination Tool	Tool Spare Blade Set	Cable Prep Tool Replacement	Tool Belt Clip	Dust Caps for Jacks	Icons for Jacks	Bulk Pack of REVConnect Cores
RVUTT01	RVUTB01	RVUCT01	RVUTC01	RVUDCXX-B24	RVUICXX-B24	RVUCOEW-B50
Includes tool, cable prep insert, and spare blade set	Optional extra set of blades with Allen key included	Optional cable prep tool replacement insert	Optional belt clip for universal tool	Optional dust caps for all jacks; XX is color code, pack of 24	Optional icons for all jacks; XX is color code, pack of 24	Bulk pack of 50 cable managers and caps




Color codes: AL (almond), BK (black), BL (blue), BR (brown), EW (electric white), GN (green), GY (gray), IV (ivory), OR (orange), PR (purple), RD (red), YL (yellow), TB (TIA blue), TG (TIA green), TN (TIA brown), TO (TIA orange), TP (TIA purple), TR (TIA red), TY (TIA yellow)


Audio Cable Solutions

Belden offers a wide array of shielded audio cables, including riser, plenum and water blocked. Often used in intercom systems and line level audio applications, Belden's shielded audio solutions offer a number of options for protecting signals from EMI/RFI noise.


Shielded Audio Cables – Stranded Conductor

	Description	Belden Part Number				
		Bare Copper		Tinned Copper		
		Riser	Plenum	Riser	Plenum	Water Blocked
	22 AWG, 1 Pair, Shielded	5500FE	6500FE	5500FH	6500FH	5500F1
	22 AWG, 1 Pair, Shielded, Foil Bonded to Jacket for Easy Stripping	—	—	—	6500PE	—
	22 AWG, 1 Pair, Shielded + 22 AWG, 2 Conductor	5502GE	6502GE	—	—	5502G1
	22 AWG, 3 Conductor, Shielded	5501FE	6501FE	5501FH	6501FH	—
	22 AWG, 4 Conductor, Shielded	5502FE	6502FE	—	—	—
	22 AWG, 2 Pair, Individually Shielded	—	—	1325R	1325A	—
	22 AWG, 3 Pair, Individually Shielded	—	—	1326R	1326A	—
	20 AWG, 1 Pair, Shielded	5400FE	6400FE	5400FH	6400FH	—
	20 AWG, 3 Conductor, Shielded	5401FE	6401FE	5401FH	6401FH	5400F1
	18 AWG, 1 Pair, Shielded	5300FE	6300FE	5300FH	6300FH	5300F1
	18 AWG, 1 Pair, Shielded + 18 AWG, 2 Conductor	5302GE	—	—	—	—
	18 AWG, 3 Conductor, Shielded	5301FE	6301FE	5301FH	6301FH	—
	18 AWG, 4 Conductor, Shielded	5302FE	6302FE	—	—	—
	16 AWG, 1 Pair, Shielded	5200FE	6200FE	5200FH	6200FH	5240F1
	16 AWG, 3 Conductor, Shielded	5201FE	6201FE	5201FH	6201FH	—
	14 AWG, 1 Pair, Shielded	5100FE	6100FE	5100FH	6100FH	5140F1
	14 AWG, 3 Conductor, Shielded	5101FE	6101FE	5101FH	6101FH	—
	12 AWG, 1 Pair, Shielded	5000FE	6000FE	5000FH	6000FH	—

Shielded Audio Cables – Solid Conductor

	Description	Belden Part Number	
		Riser	Plenum
	22 AWG, 2 Conductor	5520FE	6520FE
	22 AWG, 3 Conductor	5521FE	6521FE
	20 AWG, 3 Conductor	5421FE	—
	18 AWG, 2 Conductor	5320FE	6320FE

Shielded Pro Audio and Intercom Cables - Low Capacitance


	Description	Shielding	Belden Part Number
			Plenum
	22 AWG, 2 Conductor	Overall Shield	6500FC
	22 AWG, 4 Conductor	Overall Shield	6502FC
	22 AWG, 2 Pair	Shielded Pairs	6541PA
	22 AWG, 3 Pair	Shielded Pairs	6542PA
	22 AWG, 4 Pair	Shield Pairs	6543PA
	22 AWG, 6 Pair	Shield Pairs	6545PA
	22 AWG, 8 Pair	Shield Pairs	6546PA
	22 AWG, 12 Pair	Shield Pairs	6548PA
	22 AWG, 16 Pair	Shield Pairs	6549PA
	20 AWG, 2 Conductor	Overall Shield	6400FC
	18 AWG, 2 Pair	Shield Pairs	6341PC
	18 AWG, 3 Pair	Shield Pairs	6342PC
	18 AWG, 4 Pair	Shield Pairs	6343PC
	18 AWG, 6 Pair	Shield Pairs	6345PC
	18 AWG, 2 Conductor	Overall Shield	6300FC
	18 AWG, 4 Conductor	Overall Shield	6302FC

 LEED Qualified Product

Be certain.




Audio Cable Solutions (continued)

Nurse Call Cables

	Description	Construction	Belden Part Number	
			Riser	Plenum
	Configured for Nurse Call systems	22 AWG, 4 Conductor	5522UG	–
	Configured for Rauland Borg Responder® IV Cable H (S-Bus)	24 AWG, 6 Conductor	5624UG	6624UG
	Configured for Rauland Borg Responder® IV Cable G (CL-Drop)	24 AWG, 8 Conductor	5626UG	6626UG
	Configured for Rauland Borg Responder® IV Cable F (J Drop), H (S-Bus), or S (Console/Receptacle)	24 AWG, 3 Pair, Category 5e	5662UG	6662UG

Responder® IV is a registered trademark of Rauland-Borg Corporation.

SimplexGrinnell™ EZ Care™ Nurse Call System

Application	EZ Care	Belden Item Number	Description
A. Power Bus	5009-9891	2152AE 0021000	2 Pair 20 AWG (Red/Red, Black/Black), CM Rated, Red Jacket
A. Power Bus	5009-9892	2152PE 0021000	2 Pair 20 AWG (Red/Red, Black/Black), Plenum, Red Jacket
B. Data Bus	5009-9893	2153AE 0091000	1 Pair 22 AWG (Blue/Yellow), CM Rated, White Jacket
B. Data Bus	5009-9894	2153PE 0091000	1 Pair 22 AWG (Blue/Yellow), Plenum, White Jacket
C. Power and Data Bus	5009-9885	2154AE 0081000	3 Pair 20 AWG (Red/Red, Black/Black, Blue/Yellow), CM Rated, Gray Jacket
C. Power and Data Bus	5009-9886	2154PE 0081000 	3 Pair 20 AWG (Red/Red, Black/Black, Blue/Yellow), Plenum, Gray Jacket
D. Unit Audio Bus, Room Call Stations, TV Control, Code Blue Stations	5009-9895BL	2155AE 0061000	2 Pair 22 AWG (Black/Red, Green/White with Green Stripe), CM Rated, Blue Jacket
D. Unit Audio Bus, Room Call Stations, TV Control, Code Blue Stations	5009-9896BL	2155PE 0061000 	2 Pair 22 AWG (Black/Red, Green/White with Green Stripe), Plenum, Blue Jacket
E. Inter-unit Audio, Presence Station, Corridor Lamp	5009-9897	2156AE 0051000	4 Pair 22 AWG (Black/Red, Green/White with Green Stripe, Yellow/White with Yellow Stripe, Blue/White with Blue Stripe), CM Rated, Green Jacket
E. Inter-unit Audio, Presence Station, Corridor Lamp	5009-9898	2156PE 0051000 	4 Pair 22 AWG (Black/Red, Green/White with Green Stripe, Yellow/White with Yellow Stripe, Blue/White with Blue Stripe), Plenum, Green Jacket
F. Unit Audio Bus	5009-9895WH	2155AE 0091000	2 Pair 22 AWG (Red/Black, Green/White with Green Stripe), CM Rated, White Jacket
F. Unit Audio Bus	5009-9896WH	2155PE 0091000	2 Pair 22 AWG (Red/Black, Green/White with Green Stripe), Plenum, White Jacket
G. Emergency Call Stations	5009-9895RD	2155AE 0021000	2 Pair 22 AWG (Red/Black, Green/White with Green Stripe), CM Rated, Red Jacket
G. Emergency Call Stations	5009-9896RD	2155PE 0021000	2 Pair 22 AWG (Red/Black, Green/White with Green Stripe), Plenum, Red Jacket
H. Data Network	710548E	2158AE 0061000	CAT5E (200MHz), 4-Pair, U/UTP-Unshielded, Riser, Blue Jacket
H. Data Network	710536E	2158PE 0061000	CAT5E (200MHz), 4-Pair, U/UTP-Unshielded, Plenum, Blue Jacket

EZ Care and SimplexGrinnell are trademarks of Tyco International Services AG or its affiliates.

ASCOM Telligence Nurse Call System

Description	Belden Part Number
2-16 AWG stranded bare copper pairs with PVC insulation and Lime PVC jacket, Riser-CMR	2157AA T32U1000
2-16 AWG solid stranded copper pairs with PVC insulation and Lime PVC jacket, Plenum-CMP	2157PA T32U1000
2-24 solid bare copper pairs with LS-PVC insulation and Lime LS-PVC jacket, CAT 3, Plenum-CMP	2160PA T32U1000
4-24 solid bare copper pairs with Polyolefin insulation and Lime PVC jacket, CAT 5E, Riser-CMR	2161AA T32U1000
4-24 solid bare copper pairs with dual FRPO/FEP insulation and Lime Flamarrest jacket, CAT 5E, Plenum-CMP	2161PA T32U1000
2-22 AWG stranded bare copper pairs with Flamarrest® insulation and Lime Flamarrest jacket, Plenum-CMP	2162PA T32U1000



Speaker Cable Solutions

Belden offers speaker cables for a wide range of applications, including riser, plenum, indoor/outdoor, direct burial, for commercial and professional installations. We also offer speaker cable with ASTM B170 with ultra-high purity (99.995% pure), sometimes described as “oxygen-free (OFC)” copper.

When deciding between solid and stranded conductors consider the following: Stranded conductors are more flexible, which makes installation easier. Solid conductors have lower resistance and eliminate the possibility of stray strands causing shorts.

Speaker Cables – Stranded Conductor

Description	Belden Part Number				
	Bare Copper		Tinned Copper		
	Riser	Plenum	Riser	Plenum	Water Blocked
22 AWG, 2 Conductor, 7 strand	5500UE	6500UE	5500UH	6500UH	—
22 AWG, 3 Conductor, 7 strand	5501UE	6501UE	5501UH	6501UH	—
20 AWG, 2 Conductor, 7 strand	5400UE	6400UE	5400UH	6400UH	—
20 AWG, 3 Conductor, 7 strand	5401UE	6401UE	5401UH	6401UH	—
18 AWG, 2 Conductor, 7 strand	5300UE	6300UE	5300UH	6300UH	5300U1
18 AWG, 3 Conductor, 7 strand	5301UE	6301UE	5301UH	6301UH	—
18 AWG, 4 Conductor, 7 strand	5302UE	6302UE	5302UH	6302UH	5302U1
16 AWG, 2 Conductor, 19 strand	5200UE	6200UE	5200UH	6200UH	5240U1
16 AWG, 3 Conductor, 19 strand	5201UE	6201UE	5201UH	6201UH	—
16 AWG, 4 Conductor, 19 strand	5202UE	6202UE	5202UH	6202UH	5202U1
14 AWG, 2 Conductor, 19 strand	5100UE	6100UE	5100UH	6100UH	5140U1
14 AWG, 3 Conductor, 19 strand	5101UE	6101UE	5101UH	6101UH	—
14 AWG, 4 Conductor, 19 strand	5102UE	6102UE	5102UH	6102UH	5102U1
12 AWG, 2 Conductor, 19 strand	5000UE	6000UE	5000UH	6000UH	5000U1
12 AWG, 3 Conductor, 19 strand	5001UE	6001UE	5001UH	6001UH	—

High-Flex Speaker Cables - Bare Copper

Description	Belden Part Number	
	Non Plenum	Plenum
18 AWG, 2 Conductor, 42 strand	5300UP	—
18 AWG, 4 Conductor, 42 strand	5302UP	—
16 AWG, 2 Conductor, 65 strand	5200UP	—
16 AWG, 2 Conductor, 65 strand, Oxygen-free, Indoor/Outdoor	1307A	—
16 AWG, 4 Conductor, 65 strand	5202UP	—
16 AWG, 4 Conductor, 65 strand, Oxygen-free, Indoor/Outdoor	1308A	—
14 AWG, 2 Conductor, 42 strand	5100UP	—
14 AWG, 2 Conductor, 105 strand, Oxygen-free, Indoor/Outdoor	1309A	—
14 AWG, 4 Conductor, 42 strand	5102UP	—
14 AWG, 4 Conductor, 105 strand, Oxygen-free, Indoor/Outdoor	1310A	—
12 AWG, 2 Conductor, 65 strand	5000UP	—
12 AWG, 2 Conductor, 168 strand, Oxygen-free, Indoor/Outdoor	1311A	—
12 AWG, 4 Conductor, 65 strand	5002UP	—
12 AWG, 4 Conductor, 168 strand, Oxygen-free, Indoor/Outdoor	1312A	—
10 AWG, 2 Conductor, 65 strand	5T00UP	6T00UP
10 AWG, 2 Conductor, 259 strand, Oxygen-free, Indoor/Outdoor	1313A	—

Speaker Cables – Solid Bare Copper Conductor

Description	Belden Part Number	
	Riser	Plenum
22 AWG, 2 Conductor	5520UE	6520UE
22 AWG, 3 Conductor	5521UE	6521UE
22 AWG, 4 Conductor	5522UE	6522UE
18 AWG, 2 Conductor	5320UE	6320UE
18 AWG, 3 Conductor	5321UE	6321UE
18 AWG, 4 Conductor	5322UE	6322UE










LEED Qualified Product

Be certain.


Media Automation and Lighting Control Solutions

Automation and lighting control are growing rapidly in commercial buildings because of their ability to reduce energy consumption and cost. More sophisticated and complex systems are often integrated with HVAC and/or security systems as well. Belden now offers cables that work seamlessly with AMX®, Lutron®, DMX®, and Crestron® systems.


AMX® Systems

	Systems	Cable Construction	Belden Part Number	
			Riser	Plenum
	Cable Configured for AXLINK™	22 AWG, 1 Shielded Pair (100Ω) + 18 AWG, 2 Conductor	1392A 	1392P 
	Cable Configured for DXLINK™	Category 5e Shielded Cable	1212F 	1213F 
	Cable Configured for DXLINK™	Category 6 Shielded Cable	2412F 	2413F 
	Cable Configured for DXLINK™	10GX / Category 6A Shielded Cable	10GX62F 	10GX63F 


Lutron® Systems

	Systems	Cable Construction	Belden Part Number	
			Riser	Plenum
	Cable Configured for EcoSystem®, Bus Cable	16 AWG, 2 Conductor	2179LA	2179LP
	Cable Configured for EcoSystem®, Sensor Cable	22 AWG, 5 Conductor	1384LA	1384LP
	Cable Configured for Homeworks® and/or Grafik Eye® 3000 Systems	18 AWG, 2 Conductor + 22 AWG, 1 Shielded Pair	2180LA	2180LP
	Cable Configured for Grafik Eye® 4000/5000/6000 Systems	22 AWG, 1 Pair + 12 AWG, 2 Conductor + 18 AWG, 1 Conductor	2181LA	2181LP
	Cable Configured for Sivoia® QS Systems	18 AWG, 2 Conductor + 22 AWG, 1 Shielded Pair	1387LA	1387LP
	Cable Configured for Sivoia® QS Systems, Motor Drive Unit	22 AWG Triad + 16 AWG, 2 Conductor + 18 AWG, 1 Conductor	1388LA	—
	Cable Configured for Homeworks® and/or Sivoia® QED Systems, EDU and Keypad	18 AWG Quad + 16 AWG, 2 Conductor + 18 AWG, 1 Conductor	1389LA	—




DMX® Systems

	Description	Cable Construction	Belden Part Number	
			Riser	Plenum
	RS-485 Cable for Theatrical Lighting Control	1 PR, 24 AWG	9841	82841
		2 PR, 24 AWG	9842	82842
		1 PR, 22 AWG	3105A	—
		2 PR, 22 AWG	3107A	—

Crestron® Digital Media (DM) Ultra for HDBaseT®

	Description	Cable Construction	Belden Part Number	
			Riser	Plenum
	4K UHD Media Cable	23 AWG, 4 Bonded-Pairs, Overall Foil Shield	2183R	2183P

Crestron® Cresnet™ Systems

	Description	Cable Construction	Belden Part Number	
			Riser	Plenum
	Cable Configured for Cresnet	22 AWG, 1 Shielded Pair (100) + 18 AWG, 2 Conductor	1392A 	1392P 
	Cable Configured for Cresnet-DM	22 AWG, 1 Shielded Pair	8451	—

AMX, AXLINK, and DXLink are either trademarks or registered trademarks of AMX, LLC registered in the U.S. and other countries. DMX is either a trademark or a registered trademark of DMX, Inc. EcoSystem, HomeWorks, Grafik Eye, Sivoia, and Lutron are either trademarks or registered trademarks of Lutron Electronics Co., Inc. Cresnet and Digital Media (DM) are trademarks or registered trademarks of Crestron® Electronics, Inc in the U.S. and other countries.

 LEED Qualified Product

Media Automation and Lighting Control Solutions (continued)

Crestron® Digital Media (DM) 8G™ Systems

	Description	Cable Construction	Belden Part Number	
			Riser	Plenum
	Cable Configured for DM-CBL-8G	Category 5e Shielded, Nonbonded Pair	1212F 	1213F 

For enhanced POE/POH performance review Belden's 2400 Series Copper Cable.

CresFiber 8G™ Systems or HDMI over Fiber


	Description	Cable Construction	Belden Part Number			
			Riser	Plenum	Field Installable Connector OM3 / OM4 for 900 µm	
					LC	SC
	Cable Configured for CresFiber 8G	4 Graded-Index Multimode Fibers	F14B004RBA 	F14B004PBA 	AX105202-B25*	AX105207-B25*

*2 mm jacketed boot required AX105214-B25


CresFiber and Digital Media (DM) are trademarks or registered trademarks of Crestron® Electronics, Inc in the U.S. and other countries.

50 Ω RF Cables

50 Ω Wireless Transmission Cables

	Description	Key Attributes	Belden Part Number
	RG-8, 10 AWG, Solid BC, Foil + 95% TC Braid	Outdoor, 6 GHz	7810A
	RG-8/U, 10 AWG, Solid BC, Foil + 90% TC Braid		9913
	RG-8X, 15 AWG, Solid BC, Foil + 95% TC Braid	RF240, Outdoor, 6 GHz	7808A
	RG-8X, 16 AWG, Stranded BC, 95% BC Braid	CM, AWM 1354	9258
	RG-58, 19 AWG, Solid BC, Foil + 90% TC Braid	RF195, Outdoor, 6 GHz	7806A
	RG-58/U, 20 AWG, Solid BC, 95% TC Braid	CMP, High Temp	88240
	RG-58/U, 20 AWG, Solid BC, 78% BC Braid		9201
	RG-58A/U, 20 AWG, Solid BC, 95% TC Braid	CMX, AWM 1354	8240
	RG-58A/U, 20 AWG, Stranded TC, 95% TC Braid	Flexible CM, AWM 1354	8219
	RG-58A/U, 20 AWG, Stranded TC, 95% TC Braid	Flexible	8259
	RG-174/U, 26 AWG, Stranded CCS, 90% TC Braid	AWM 1354	8216

50 Ω MIL-C-17G QPL Cables

	Description	Key Attributes	Belden Part Number
	RG-58C/U, 20 AWG, Stranded TC, 95% TC braid	Non-Contaminating PVC Jacket	8262
	RG-142B/U, 19 AWG, Solid SCCCS, Double SCC 95% braids	CMP, High Temp	83242
	RG-142/U, 19 AWG, Solid SCCCS, Double SCC 95% braids	CMP, High Temp	84142
	RG-178B/U, 30 AWG, Stranded SCCCS, 95% SCC braid	High Temp	83265
	RG-213/U, 13 AWG, Stranded BC, 96% BC braid	Non-Contaminating PVC Jacket, CMX, AWM 1354	8267
	RG-214/U, 13 AWG, Stranded SCC, Double SCC 95% braids	Non-Contaminating PVC Jacket, CMX, AWM 1354	8268
	RG-223/U, 19 AWG, Solid SCC, Double SCC 95% braids	Non-Contaminating PVC Jacket, CMX, AWM 1354	9273
	RG-316/U, 26 AWG, Stranded SCCCS, 95% SCC braid	High Temp	83284

CCS = Copper Covered Steel
 SCC = Silver Coated Copper
 SCCCS = Silver Coated Copper Covered Steel
 TC = Tinned Copper
 BC = Bare Copper

 LEED Qualified Product

Be certain.

Video Distribution and Display Solutions

Belden's High-Definition (HD) Coax cable design includes a tinned copper braid shield (85% coverage) and bonded Duofoil® shield (100% coverage) for effective shielding. The bonded foil shield simplifies termination with one-piece connectors.

The new coax design uses very high-velocity dielectrics so the plenum and non-plenum versions are close in size, allowing selection of a single type of compression connector for both.

Belden's best-in-class, high-density foaming technology ensures reliable signal integrity and better video images while also providing superior crush resistance, concentricity and conductor adhesion for more stable performance.

The cables are available in 10 colors: Black, White, Red, Green, Blue, Yellow, Orange, Violet, Brown and Gray.

Designed specifically for use with compression connectors, Belden HD Coax cables feature a foil shield that is securely bonded to the core, making stripping and terminating easier.



HD-SDI Coax Cables

Description	Belden Part Number				
	Riser	Plenum	BNC	Comp Tool	Strip Tool
Miniature 23 AWG SDI Coax	1371R	1371P	FSNS15BNC-25	CPSNSCT-596	PS59/6/RGB
RG-59, 20 AWG SDI Coax	1370R	1370P	FSNS59BNCPL-25	CPSNSCT-596	PSA59/6
RG-6, 18 AWG SDI Coax	1369R	1369P	FSNS6BNCPL-25	CPSNSCT-596	PSA59/6

RCA and F connectors are also available

Mini Hi-Res Coax Cables

Description	Key Attributes	Belden Part Number				
		Riser	Plenum	BNC	Comp Tool	Strip Tool
(3) 25 AWG Mini Hi-Res Coax w/Bonded Foil	Overall Jacket	1393R	1393P	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB
(4) 25 AWG Mini Hi-Res Coax w/Bonded Foil	Overall Jacket	1394R	1394P	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB
(5) 25 AWG Mini Hi-Res Coax w/Bonded Foil	Overall Jacket	1395R	1395P	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB
(6) 25 AWG Mini Hi-Res Coax w/Bonded Foil	Overall Jacket	1396R	1396P	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB
(5) 25 AWG Mini Hi-Res Coax w/Bonded Foil	Banana Peel	1397S5	1398S5	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB
(6) 25 AWG Mini Hi-Res Coax + (2) STP 22 AWG	Banana Peel	5788AV	6788AV	FS1BNC-25	CPLCCT-SLMR	PS59/6/RGB

RCA and F connectors are also available

CATV Coax Cables

Description	Belden Part Number			
	Non Plenum	F Male	Comp Tool	Strip Tool
RG-6 Coax, 18 AWG Solid CCS, foil + 60% Alum. Braid	9116	FSNS6U-25	CPSNSCT-596	PSA59/6
RG-6 Coax, 18 AWG Solid CCS + Alum. Quad Shield	1189A	FSNS1P6QS-25	CPSNSCT-596	PSA59/6
RG-11 Coax, 14 AWG Solid CCS, Dual Shield	1523A	716SNS1P11H-25	SNSUNI	PS11
RG-59 Coax, 20 AWG Solid CCS, Bonded foil + 65% Alum. Braid	9104	FSNS59U-25	CPSNSCT-596	PSA59/6
	Plenum	F Male	Comp Tool	Strip Tool
RG-6 Coax, 18 AWG Solid CCS, Foil + 60% Alum. Braid	9116P	FSNS6PLQ-25	CPSNSCT-596	PSA59/6
RG-6 Coax, 18 AWG Solid CCS + Alum. Quad Shield	1189AP	FSNS6U-25	CPSNSCT-596	PSA59/6
RG-11 Coax, 14 AWG Solid CCS, Dual Shield	1523AP	716SNS1P11PL-25	SNSUNI	PS11

BNC and RCA connectors are also available






Coaxial Connectivity Solutions

Belden is the brand professional cable installers trust as a world-class manufacturer of signal transmission products and connectivity solutions. Belden offers quality products to provide superior signal performance for the Professional Audio-Video, Security, and

Satellite/CATV markets. The ProSNS™/FS Series and Double Bubble™ connector brands feature F, RCA and BNC connectors for RG11, RG6, RG59 and RGB/Mini Coax for standard through quad-shield (universal) and plenum cables. These connector brands, coupled with Belden

cables, cable prep tools, and compression tools are all designed specifically to maximize signal integrity, ensure quality, performance and durability while providing customers with unparalleled end-to-end performance.

BNC Compression Video Connectors

	Description	Cable Type	Impedance (ohms)	Color Band	Belden Part Number			
					ProSNS	ProSNS Tool	DB	DB Tool
	1-Piece BNC Compression Connector for 24-26AWG Cable	Mini Coax	75	Orange	FS1BNC-25	CPLCCT-SLMR	DB1BNC-25	DCPLCRBC-BR
	Multi-Piece BNC Compression Connector for 24-26AWG Cable	Mini Coax	75	Orange	FSBNC1RGB	CPLCCT-SLMR	—	—
	Splice BNC Compression Connector for 24-26AWG Cable	Mini Coax	75	Orange	FS1BNCSSST	CPLCCT-SLMR	—	—
	1-Piece BNC Compression Connector for 22-24AWG Cable	Mini Coax	75	Purple	FSNS15BNC-25*	CPLCCT-SLMR	DB15BNCHD-25	CPLCRBC-BR
	Multi-Piece BNC Compression Connector for 22-24AWG Cable	Mini Coax	75	Purple	FSBNC15RGB	CPLCCT-SLMR	—	—
	Right Angle BNC Compression Connector for 22-24AWG Cable	Mini Coax	75	Purple	FSBNC15RA	CPLCCT-SLMR	—	—
	Splice BNC Compression Connector for 22-24AWG Cable	Mini Coax	75	Purple	FS15BNCSSST	CPLCCT-SLMR	—	—
	Universal BNC Compression Connector for HD-SDI Coax	RG-59	75	Red	FSNS59BNCU-25	CPSNSCT-596	DB59BNCU-25	CPLCRBC-BR
	BNC Compression Connector for RG-59 Plenum Cable	RG-59	75	Red	FSNS59BNCPL-25	CPSNSCT-596	DB59BNCPL2/4-25	CPLCRBC-BR
	BNC Compression Connector for RG-59 Plenum Size 3 with 23 AWG Center Conductor	RG-59	75	Red	FSNS59BNCPL	CPSNSCT-596	DB59BNCPL3-25	CPLCRBC-BR
	BNC Compression Connector for RG-59 CCTV Security Cable	RG-59	75	Red	FSNS59BNCPL-25	CPSNSCT-596	DB59BNCPL-25	CPLCRBC-BR
	Universal BNC Right Angle Compression Connector	RG-59	75	Red	FSBNC59URA	CPLCCT-SLMR	—	—
	Universal BNC Splice Compression Connector	RG-59	75	Red	FS59BNCUS	CPLCCT-SLMR	—	—
	Universal BNC Compression Connector for Standard through Quad-Shield Cable	RG-6	75	Green	FSNS6BNCPL-25	CPSNSCT-596	DB6BNCU-25	CPLCRBC-BR
	BNC Compression Connector for RG-6 Plenum Cable	RG-6	75	Green	FSNS6BNCPL-25	CPSNSCT-596	DB6BNCPL2-25	CPLCRBC-BR
	Universal BNC Right Angle Compression Connector	RG-6	75	Green	FSBNC6URA	CPLCCT-SLMR	—	—
	Universal BNC Splice Compression Connector	RG-6	75	Green	FS6BNCUS	CPLCCT-SLMR	—	—
	Universal BNC Connector for Standard through Quad-Shield Cable	RG-11	75	Black	FSNS11HBNC	SNSUNI	—	—
	BNC Compression Connector for RG-11 Plenum Cable	RG-11	75	Gray	FSNS11BNCPL-25	SNSUNI	—	—
	BNC Compression Connector for RG-11 Quad-Shield Cable	RG-11	75	Purple	FSNS11QHBNC-25	SNSUNI	—	—

*1-Piece mini coax connectors are designed for solid center conductor wire only

"FS" Series connectors use compression tool CPLCCT-SLMR



"FSNS" Series connectors use either compression tool CPLCCT-SLMR or CPSNSCT-596

Belden offers RCA connectors for most coaxial cable constructions including the cables referenced in the chart above. For more information on available RCA connectors, [click here](#) or please call 1-800-BELDEN-1.

Be certain.

Coaxial Connectivity Solutions (continued)

F Compression Video Connectors

	Description	Cable Type	Impedance (ohms)	Color Band	Part Number			
					ProSNS	ProSNS Tool	DB	DB Tool
	1-Piece F Compression Connector for 22-24AWG Cable	Mini Coax	75	Purple	FSNS15-25*	CPSNSCT-596	DB15-25	CPLCRBC-BR
	Universal BNC Compression Connector for HD-SDI Coax	RG-59	75	Red	FSNS59U-25	CPSNSCT-596	DB59U-25	CPLCRBC-BR
	F Compression Connector for RG-59 Plenum Cable	RG-59	75	Red	FSNS59PL-25	CPSNSCT-596	DB59PL2/4-25	CPLCRBC-BR
	Universal F Right Angle Compression Connector	RG-59	75	Red	FSNS59URA-25	CPSNSCT-596	—	—
	Universal F Splice Compression Connector	RG-59	75	Red	FS59US	CPLCCT-SLMR	—	—
	Universal F Compression Connector for Standard through Quad-Shield Cable	RG-6	75	Green	FSNS6U-25	CPSNSCT-596	DB6U-25	CPLCRBC-BR
	RG-6 Quad-Shield F Connector	RG-6	75	Purple	FSNS1P6QS-25	CPSNSCT-596	—	—
	F Compression Connector for RG-6 Plenum Cable	RG-6	75	Green	FSNS6PL-25	CPSNSCT-596	DB6PL2-25	CPLCRBC-BR
	Universal F Right Angle Compression Connector	RG-6	75	Green	FSNS6URA-25	CPSNSCT-596	—	—
	Universal F Splice Compression Connector	RG-6	75	Green	FS6US	CPLCCT-SLMR	—	—
	7/16" Universal F Compression Connector for Standard through Quad-Shield Cable	RG-11	75	Black	716SNS1P11H-25	SNSUNI	—	—
	7/16" F Compression Connector for RG-11 Plenum Cable	RG-11	75	Gray	716SNS1P11PL-25	SNSUNI	—	—
	7/16" F Compression Connector for RG-11 Quad-Shield Cable	RG-11	75	Purple	716SNS1P11HQ-25	SNSUNI	—	—
	7/16" F Right Angle Compression Connector for Standard through Quad-Shield Cable	RG-11	75	Black	90SNS1P11H	SNSUNI	—	—
	9/16" Universal F Connector for Standard through Quad-Shield Cable	RG-11	75	Black	SNS1P11H	SNSUNI	—	—

*1-Piece mini coax connectors are designed for solid center conductor wire only

"FS" Series connectors use compression tool CPLCCT-SMLR

"FSNS" Series connectors use either compression tool CPLCCT-SMLR or CPSNSCT-596

Belden offers RCA connectors for most coaxial cable constructions including the cables referenced in the above chart. For more information on available RCA connectors, [click here](#) or please call 1-800-BELDEN-1.

Molded AV Assembly Solutions

Belden, the leader in professional audio/video signal transmission technology, introduces high performance Molded AV Assemblies to its portfolio of products. Belden now offers HDMI, DVI, and VGA assemblies, in a wide variety of lengths to meet the increasing needs of commercial and professional AV installations. All assemblies meet Belden's rigorous performance standards to ensure reliability in the field.


Patented PerfectPath™ Locking High Speed HDMI stays connected with up to 25 lbs of retention in the port.

To engage the lock, push the connector


body forward. To disengage, pull connector body backward.



Perfect Path™ Locking HDMI - 800 Series


	Description	Belden Part Number
	High Speed HDMI w/ PerfectLock™ Connectors, 2 ft.	HD-800-2
	High Speed HDMI w/ PerfectLock™ Connectors, 4 ft.	HD-800-4
	High Speed HDMI w/ PerfectLock™ Connectors, 8 ft.	HD-800-8
	High Speed HDMI w/ PerfectLock™ Connectors, 16 ft.	HD-800-16
	High Speed HDMI w/ PerfectLock™ Connectors, 25 ft.	HD-800-25
	High Speed HDMI w/ PerfectLock™ Connectors, 35 ft.	HD-800-35
	High Speed HDMI w/ PerfectLock™ Connectors, 50 ft.	HD-800-50

High Speed HDMI

	Description	Belden Part Number
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 1 m	HDE001MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 1.5 m	HDE002MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 3 m	HDE003MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 5 m*	HDE005MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 7 m*	HDE007MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 10 m*	HDE010MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 15 m*	HDE015MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 20 m*	HDE020MB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 1.5 ft.	HDE002FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 3 ft.	HDE003FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 6 ft.	HDE006FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 8 ft.	HDE008FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 10 ft.	HDE010FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 15 ft.	HDE015FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 25 ft.*	HDE025FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 35 ft.*	HDE035FB
	High Speed HDMI with Ethernet Channel, 3D and UHD/4K ready, 50 ft.*	HDE050FB

* Assemblies over 5 meters are active and directional.

Mini HDMI to Standard HDMI

	Description	Belden Part Number
	Mini HDMI to Standard HDMI, 1 m	HDM001MB
	Mini HDMI to Standard HDMI, 1.5 m	HDM002MB
	Mini HDMI to Standard HDMI, 3 m	HDM003MB


Micro HDMI to Standard HDMI

	Description	Belden Part Number
	Micro HDMI to Standard HDMI, 1 m	HDC001MB
	Micro HDMI to Standard HDMI, 1.5 m	HDC002MB
	Micro HDMI to Standard HDMI, 3 m	HDC003MB


Be certain.

Molded AV Assembly Solutions (continued)


Dual Link DVI-D

	Description	Belden Part Number
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 1 m	DDD001MB
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 2 m	DDD002MB
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 3 m	DDD003MB
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 5 m	DDD005MB
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 1.5 ft.	DDD002FB
	Dual Link DVI-D, digital, supports resolutions up to 2560 x 1600 pixels, 13 ft.	DDD013FB


Single Link DVI-D

	Description	Belden Part Number
	Single Link DVI-D, digital, supports resolutions up to 1920 x 1200 pixels, 3 ft.	DSD003FB
	Single Link DVI-D, digital, supports resolutions up to 1920 x 1200 pixels, 6 ft.	DSD006FB
	Single Link DVI-D, digital, supports resolutions up to 1920 x 1200 pixels, 10 ft.	DSD010FB
	Single Link DVI-D, digital, supports resolutions up to 1920 x 1200 pixels, 13 ft.	DSD013FB
	Single Link DVI-D, digital, supports resolutions up to 1920 x 1200 pixels, 15 ft.	DSD015FB


Dual Link DVI-I

	Description	Belden Part Number
	Dual Link DVI-I, analog/digital, supports resolutions up to 2560 x 1600 pixels, 2 m	DDI002MB
	Dual Link DVI-I, analog/digital, supports resolutions up to 2560 x 1600 pixels, 3 m	DDI003MB
	Dual Link DVI-I, analog/digital, supports resolutions up to 2560 x 1600 pixels, 5 m	DDI005MB

Single Link DVI-I

	Description	Belden Part Number
	Single Link DVI-I, analog/digital, supports resolutions up to 1920 x 1200 pixels, 2 m	DSI002MB
	Single Link DVI-I, analog/digital, supports resolutions up to 1920 x 1200 pixels, 3 m	DSI003MB
	Single Link DVI-I, analog/digital, supports resolutions up to 1920 x 1200 pixels, 5 m	DSI005MB

Standard VGA

	Description	Belden Part Number
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 3 ft.	VGA003FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 6 ft.	VGA006FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 10 ft.	VGA010FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 12 ft.	VGA012FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 15 ft.	VGA015FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 20 ft.	VGA020FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 25 ft.	VGA025FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 35 ft.	VGA035FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 40 ft.	VGA040FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 50 ft.	VGA050FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 75 ft.	VGA075FB
	Standard VGA, supports resolutions up to 2048 x 1536 pixels, 100 ft.	VGA100FB


AV Multimedia Modules and Face Plates

Belden offers a variety of AV multimedia connector modules, including both copper and fiber, along with a full line of faceplates, adapters and boxes. Compatible with all REVConnect and Multimedia Modules, KeyConnect Faceplates are designed for maximum flexibility, durability, aesthetics and manageability. Two Tamper-Resistant KeyConnect Faceplates are available, one for

dust and water resistance and another, Secure Outlet, for any application where access to network connections need to be controlled. The MediaFlex Faceplate Kits offer flexibility in configuring multimedia workstation outlets for current and future network needs. They feature a front access design that allows inserts to be easily snapped in and out of openings for fast installation and upgrades.

Both KeyConnect and MediaFlex Faceplates are available in a variety of styles, colors and port configurations. Several innovative tools and accessories that ease termination and simplify installation are also available. For more information on our full line of products please visit www.belden.com or call 1.800.BELDEN1 to request a Belden Copper Catalog.

KeyConnect AV Multimedia Modules, Copper

	Description	Belden Part Number		
		Almond	Elec. White	Black
	3.5mm Audio Coupler, F/F, Gold	AX105334-AL	AX105334-EW	AX105334-BK
	3.5mm Audio Coupler, F/Solder, Gold	AX105335-AL	AX105335-EW	AX105335-BK
	S-video Coupler, F/F	AX105336-AL	AX105336-EW	AX105336-BK
	RCA Gold-plated Coupler, F/F, Red	AX105337-AL	AX105337-EW	AX105337-BK
	RCA Gold-plated Coupler, F/F, White	AX105338-AL	AX105338-EW	AX105338-BK
	RCA Gold-plated Coupler, F/F, Yellow	AX105339-AL	AX105339-EW	AX105339-BK
	RCA Gold-plated Coupler, F/F, Green	AX105340-AL	AX105340-EW	AX105340-BK
	RCA Gold-plated Coupler, F/F, Blue	AX105341-AL	AX105341-EW	AX105341-BK
	Video F Coax 3 GHz, Recessed, Gold-Plated	AX105346-AL	AX105346-EW	AX105346-BK
	Video F Coax, Recessed	AX102903	AX102904	AX102905
	Video F Coax, Flush	AX102906	AX102907	AX102908
	Video BNC Coax 4 GHz, Flush	AX104573	AX104575	AX104574
	USB 3.0 Coupler, A to A	AX105342-AL	AX105342-EW	AX105342-BK
	USB 2.0 Coupler, B to B	AX105344-AL	AX105344-EW	AX105344-BK
HDMI Coupler (Version 1.4)	AX105345-AL	AX105345-EW	AX105345-BK	

KeyConnect AV Multimedia Modules, Fiber


	Description	Belden Part Number		
		Almond	Elec. White	Black
	LC Duplex OM3 (Aqua Adapter)	AX104937	AX104938	AX104939
	LC Duplex OM4 (Erika Violet Adapter)	AX105641-AL	AX105641-EW	AX105641-BK
	ST (Metal) Compatible MM/SM	AX102242	AX102243	AX102244

Note: KeyConnect AV Multimedia Modules may be used with either KeyConnect or MediaFlex faceplates.


Be certain.

AV Multimedia Modules and Face Plates (continued)


KeyConnect Faceplates

	Description	Belden Part Number			
		Stainless Steel	Almond	Elec. White	Black
	1-Port, with ID windows, Single-gang	AX104230	AX103922	AX102660	AX104160
	2-Port, with ID windows, Single-gang	AX104231	AX103923	AX102655	AX104161
	4-Port, with ID windows, Single-gang	AX104232	AX102248	AX102249	AX104163
	6-Port, with ID windows, Single-gang	AX104233	AX102250	AX102251	AX104164
	4-Port, with ID windows, Double-gang	AX104479	—	—	—
	6-Port, with ID windows, Double-gang	AX104480	AX102670	AX102671	AX104166
	12-Port, with ID windows, Double-gang	AX104234	AX102256	AX102257	—
	Single-gang Back Box, 1.89 in.*	—	AX104127	AX102657	AX106683
	Double-gang Back Box, 1.89 in.*	—	AX104130	AX104131	AX106685


KeyConnect Tamper Resistant Faceplates

	Description	Belden Part Number
		White
	4-Port, Single-gang with locking cover, patch cord seal and wall gasket (dust and water resistant)	AX104687
	4-Port, Single-gang with locking cover (secure outlet)	AX104688
	Secure screw driver bit (Drilled Spanner 1/4")	AX104689

MediaFlex Angled Inserts


	Description	Belden Part Number			
		Gray	Almond	Elec. White	Black
	3-Port RCA (IDC interface) for 110 punchdown	AX101877	AX101878	AX101879	AX101880
	SVHS Module (IDC interface) for 110 punchdown	AX101881	AX101882	AX101883	AX101884
	SVGA Module (IDC interface) for 110 punchdown	AX101885	AX101886	AX101887	AX101888
	SVGA Feedthrough	AX102334	AX102335	AX102336	AX102337
	SVGA Feedthrough, 3.5 mm Audio	AX105158-GY	AX105158-AL	AX105158-EW	AX105158-BK

MediaFlex Angled Edge Faceplates and Kits

	Description	Belden Part Number			
		Gray	Almond	Elec. White	Black
	2-Port, Flush, Single-gang Kit	AX106617	AX106618	AX106619	AX106620
	4-Port, Flush, Single-gang Kit	AX106621	AX106622	AX106623	AX106624
	6-Port, Flush, Single-gang Kit	AX106625	AX106626	AX106627	AX106628
	2-Port, Angled Insert, Single-gang Kit	AX106629	AX106630	AX106631	AX106632
	4-Port, Angled Insert, Single-gang Kit	AX106633	AX106634	AX106635	AX106636
	6-Port, Flush, Double-gang Kit	AX106637	AX106638	AX106639	AX106640
	Single-gang, no insert	AX106669	AX106670	AX106671	AX106672
	Double-gang, no insert	AX106673	AX106674	AX106675	AX106676

*Note: KeyConnect Single-gang and Double-gang back boxes above can be used with these MediaFlex Faceplates and Kits.

Tools

	Description	Belden Part Number
		Rapid Termination Tool Assembly for KeyConnect Jacks
	Rapid Termination Tool Headset for KeyConnect Jacks	AX105568
	Rapid Termination Tool Pouch	AX105569
	110 Connecting Tool for IDC termination	AX100749
	Termination Station - secures and holds KeyConnect modules and MediaFlex inserts during termination	AX101852
	Outlet Release Tool - releases and extracts MediaFlex outlets, KeyConnect Modules and REVConnect cores from jacks or plug	AX101185

Copper Modular Patch Cords

SmartPart Number Modular Patch Cord Configurator

Example: AV2183R100005 (2183R cable, RJ45 on each end, CMR rated, black, 5 foot)

Part number example from configuration shown below:


AV2183R100005

AV2183R1		00	005
Prefix		Color Code	
AV2183R1	4K UHD Media Cable - HDBaseT®, CMR	00	002
CA211	Cat6A Unshielded, Bonded, CMR	06	003
CA221	Cat6A Unshielded, Bonded, CMP	09	004
CAF11	Cat6A, Shielded, Bonded CMR		005
CAF21	Cat6A, Shielded, Bonded, CMP		007
CAD11	Cat6A Small OD, Unshielded, Nonbonded, CMR		010
CAT11	Cat6A, Traceable, Unshielded, Bonded, CMR		017
C6F11	Cat 6+, Shielded, Nonbonded, CMR		050
C6F21	Cat 6+, Shielded, Nonbonded, CMP		
C6T11	Cat 6+, Traceable, Unshielded, Bonded, CMR		
C6D11	Cat 6+, Small OD, Unshielded, Nonbonded, CMR		

Other lengths and colors available upon request

Traceable Bonded-Pair Modular Patch Cords

Belden Traceable Bonded-Pair Modular Patch Cords have several unique features that make them an exceptional alternative to other patch cords on the market. They feature a highly-efficient and bright LED with a battery life expectancy of seven years, or 1,000 activations (battery is also replaceable). When activated, the LED blinks for 20 seconds and can be stopped at any time with a second press of the button. The LED and its tracing wires are integrated right into the patch cord, eliminating the need for a separate power source.



Small-Diameter Modular Patch Cords

The new small OD Patch Cords offer a great solution for large data center cross-connects and server enclosures as well as for enterprise networks installed crowded telecom rooms. The 28 AWG stranded conductors will provide standard-compliant performance when up to 6.3 meters (20.7 ft) of patch cord is used in a standard 90 meter (295 ft) channel.

- Available in Cat 6 and Cat 6A for 1G and 10G applications
- Reduce congestion and allow tight bend radius and improve airflow
- Work for all applications (including POE+)
- Easier access for maintenance and Improve overall network administration
- Offered in 3,4,5,7,10,15 and 25-ft standard lengths and customizable with smart item number (C6D11xxxx) for optimal cable management
- Available in, blue, white, black as standard colors as well as red, yellow, green and gray for color-coded services



Small OD Patch Cord

Be certain.

Fiber Structured Cabling Solutions

SmartPart Number Bulk Fiber Configurator

To use the configuration matrices, make a selection from each category (some selections will require measurements) and combine to form a custom part number.

Part number example from configuration shown below:

FI1D004R9

FI	1	D	004	R	9	
FX Fiber Cable	Fiber Type	Family	Fiber Count	Fire Rating and Protection	Subunit Type/Configuration	
Non-Utilized Distribution Cable						
FI	Indoor Cable	1 OM1	B Breakout	002 2 Fibers	Plenum Group	9 900 μm Fiber
FD	Indoor/Outdoor Cable	3 OM3	D Distribution	004 4 Fibers	P Plenum (OFNP)	B 2.0 mm
		4 OM4		006 6 Fibers	A Plenum Interlocked Aluminum Armor (OFCP)	C 3.0 mm
		S OS2 (G.657.A1)		012 12 Fibers	Riser Group	
				024 24 Fibers	R Riser (OFNR)	
					F Riser Interlocked Aluminum Armor (OFRCR)	

FiberExpress (FX) Field Termination Connectors

Brilliant in design and universal in implementation, FX Brilliance Universal no-epoxy, no-polish, no-crimp field-installable connectors make fiber field termination faster, easier and better with our industry-leading design.



FX Brilliance Universal Mechanical Connectors

Description	Brilliance Connector Part Number			
	Multimode, OM3	Multimode, OM4	Singlemode, OS2	Singlemode, OS2/APC
LC with 900 μm Boot, 1/Pack	AX105202-B25	AX105252-B25	AX105203-B25	—
SC with 900 μm Boot, 1/Pack	AX105207-B25	AX105253-B25	AX105208-B25	AX105209-B25

FX Brilliance Accessories

Description	Belden Part Number
Precision Install Kit	AX104271
Precision Cleaver	AX104286
Fiber/Cable Stripper	AX103151
Support Handle with Adapters	AX104276
Visual Fault Locator (VFL-125) LC-LC Adapter Cord	AX203567
Visual Fault Locator (VFL-250) SC-SC Adapter Cord (valid for ST also)	AX203569

Belden's FX Fusion connectors enable splice-on technology. They combine the benefits of fusion splicing with the simplicity of a field-installable connector to expand your options for field-termination and improve installation performance and reliability over mechanical splice connectors. No crimping, polishing, or adhesives are required for termination, minimizing installation errors.



FX Fusion Splice-On Connectors

Description	FX Fusion Connector Part Number					
	Multimode, OM1	Multimode, OM3/OM4	Multimode, OM4 - Erika Violet	Singlemode, OS2	Singlemode, OS2/APC	
LC with 900 μm Boot, 1/Pack	FT1LC900FS01	FT3LC900FS01	FT4LC900FS01	FTSLC900FS01	FTSLB900FS01	
SC with 900 μm Boot, 1/Pack	FT1SC900FS01	FT3SC900FS01	FT4SC900FS01	FTSSC900FS01	FTSSB900FS01	

FX Fusion Accessories

Description	Belden Part Number
FX Fusion Splicer Kit	FXFSTOSPL
Precision Tool Kit	FXFSTOPTK
Standard Tool Kit	FXFSTOSTK
Precision Cleaver	FXFSTOPCL
Standard Cleaver	FXFSTOSCL
Splice Holder Family 1	FXFSSHFM1*
Splice Holder Family 2	FXFSSHFM2
Slitter for Jacketed Fiber	FXFSTOSLT

*FXFSSHFM1 Holder compatible with Fujikura 60S, Fujikura 70S, Sumitomo Q101, among many others. Visit www.belden.com/splice-on for more details.

For more information on our Fiber products please visit www.belden.com/products/catalogs

FiberExpress (FX) Enterprise Closet X (ECX)

Belden's new FX ECX System is an elegant, intuitive and flexible solution that has been designed to maximize installer flexibility when compared to industry-leading solutions. FX ECX has been optimized for LAN environments, and provides an easy-to-deploy, efficient solution for installers.

FX ECX Housings

Description	Max Capacity	Belden Part Number
1U Housing	2 Cassettes or Frames	ECX-01U
2U Housing	4 Cassettes or Frames	ECX-02U
4U Housing	12 Cassettes or Frames	ECX-04U

FX ECX Kits/Accessories

Description	Belden Part Number
3 Inch Bracket Mount (4U)	ECX-BRKTMT-3
Flush Bracket Mount (4U)	ECX-BRKTMT-0
Lock Kit (1U/2U/4U)	ECX-LOCKKIT

Additional resources available, see belden.com/ecx for more information.

FX ECX Standard Splice Cassettes

Description	Belden Part Number			
	OM3 Aqua Adapters	OM4 Erika Violet Adapters	OS2 Blue Adapters	OS2 APC Green Adapters
LC Duplex				
12 (24)	FC3X12LDFS	FC4X12LDFS	FCSX12LDFS	FCSX12LAFS
SC Duplex				
06 (12)	FC3X06SDFS	FC4X06SDFS	FCSX06SDFS	FCSX06SAFS

Please see table below for more adapter/port count options!

To use the configuration matrices, make a selection from each category and combine to form a custom part number. See examples below.

FX ECX Tailored Splice Cassettes

Part number example from configuration shown below:

FCSX06SCFS

FC	S		X		06		SC		FS	
	Fiber Type		Family		Port Count (Patch Side)		Connector (Patch Side)		Connector (Trunk Side)	
	1	OM1	X	ECX	03	3 ports	LD	LC Duplex	FS	Splice Cassette
	3	OM3			06	6 ports	LA	LC Duplex APC		
	4	OM4			08	8 ports	SD	SC Duplex		
	S	OS2			12	12 ports	SC	SC Simplex		
							SA	SC Duplex APC		
							SB	SC Simplex APC		
							ST	ST		

FX ECX Standard Frames/Adapter Strips

Description	Belden Part Number			
	OM3 Aqua Adapters	OM4 Erika Violet Adapters	OS2 Blue Adapters	OS2 APC Green Adapters
LC Duplex				
12 (24)	FF3X12LD	FF4X12LD	FFSX12LD	FFSX12LA
SC Duplex				
06 (12)	FF3X06SD	FF4X06SD	FFSX06SD	FFSX06SA


Please see table below for more adapter/port count options!

FX ECX Tailored Frame Options

Part number example from configuration shown below:

FFSX06SC

FF	S		X		06		SC	
	Fiber Type		Family		Port Count (Patch Side)		Connector (Patch Side)	
	1	OM1	X	ECX	03	3 ports	LD	LC Duplex
	3	OM3			06	6 ports	LA	LC Duplex APC
	4	OM4			08	8 ports	SD	SC Duplex
	S	OS2			12	12 ports	SC	SC Simplex
					16	16 ports	SA	SC Duplex APC
							SB	SC Simplex APC
							ST	ST




For more information on our ECX products please visit www.belden.com

Be certain.

Rack and Cabinet Systems


2 and 4 Post Racks



Description (H x W x D)	Model	RU	Width (in)	Depth (in)	Screw	Type	Belden Part Number
84" x 19" x 3" Channel Knock down	BHRR	45	19	-	12-24	Alum	BHRR194
84" x 19" x 6" Channel Knock down	BHRR	45	19	-	12-24	Alum	BHRR6194
84" x 23" x 3" Channel Knock down	BHRR	45	23	-	12-24	Alum	BHRR234
84" x 19" x 3" Channel Knock down	XDR	44	19	-	12-24	Steel	XDR8419-312
84" x 19" x 3" Channel Knock down	XDR	44	19	-	10-32	Steel	XDR8419-310
84" x 19" x 3" Channel Knock down	XDR	44	19	-	10-32	Steel	XDR8419-310N
84" x 19" x 3" Channel Knock down w/Vertical Manager (1)	XDR	44	19	-	10-32	Steel	XDR8419-310N1M
84" x 19" x 3" Channel Knock down w/Vertical Managers (2)	XDR	44	19	-	10-32	Steel	XDR8419-310N2M
84" x 19" x 3" Channel Knock down	XDR	44	19	-	12-24	Steel	XDR8419-312N
84" x 19" x 3" Channel Knock down w/Vertical Manager (1)	XDR	44	19	-	12-24	Steel	XDR8419-312N1M
84" x 19" x 3" Channel Knock down w/Vertical Managers (2)	XDR	44	19	-	12-24	Steel	XDR8419-312N2M
84" x 19" x 3" Channel Welded	XDR	44	19	-	10-32/12-24	Steel	XDR8419-3##W
84" x 23" x 3" Channel Welded	XDR	44	23	-	10-32/12-24	Steel	XDR8423-3##W
84" x 19" x 6" Seismic	XDR	44	19	-	10-32	Steel	XDRS8419-610
84" x 19" x 3" Channel 4 Post Knock down	XDR	44	19	24,28,32,36	10-32/12-24	Steel	XDR8419-3##XX
84" x 23" x 3" Channel 4 Post Knock down	XDR	44	23	24,28,32,36	10-32/12-24	Steel	XDR8423-3##XX

= Screw size variable 10=10-32, 12=12-24 Screws. XX = Depth - Depth 24, 28, 32, 36


Vertical Cable Managers



Description	Model	Width (in)	Depth (in)	Belden Part Number
Single Sided Vertical organizer low density	BHVL	3.6,6,10,12	8.75	BHVLOXX
Single Sided Vertical organizer high density	BHVH	3.6,6,10,12	8.75	BHVHOXX
Double Sided Vertical organizer high/low density	BHVHL	3.6,6,10,12	17.37	BHVHLXX
Double Sided Vertical organizer high/high density	BHVHH	3.6,6,10,12	17.37	BHVHHXX
Vertical manager with cover 4"W x 4"D (for 84" 2 Post rack)	VCM	4	4	VCMFDR4X4

XX = Width Variable 03=3.6", 06=6", 10=10", 12=12"

Wall-Mount Cabinets



Description	Model	RU'S	Width (in)	Depth (in)	Belden Part Number
21" W x 20.125" H x 22.875" D, black, glass door with lock – no removable side panels	XWM	9	21	22.875	XWM-2109-GD
21" W x 20.125" H x 22.875" D, black, solid door with lock – no removable side panels	XWM	9	21	22.875	XWM-2109-SD
23" W x 25.250" H x 27.5" D, black, glass door with lock – removable side panels	XWM	12	23	27.5	XWM-2312-GD
23" W x 25.250" H x 27.5" D, black, solid door with lock – removable side panels	XWM	12	23	27.5	XWM-2312-SD
23" W x 39.250" H x 27.5" D, black, glass door with lock – removable side panels	XWM	20	23	27.5	XWM-2320-GD
23" W x 39.250" H x 27.5" D, black, solid door with lock – removable side panels	XWM	20	23	27.5	XWM-2320-SD

Consult Belden Cable Management Catalog to access enclosure configuration matrix and accessories listing. NEMA compliant enclosures also available.

For more information on our Catalogs please visit www.belden.com/products/catalogs

Part Number Index

Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
10GX32 0061000	4	1523A	11	5140F1	6	6101UE	8	8262	10
10GX32 0091000	4	1523AP	11	5140U1	8	6101UH	8	8267	10
10GX33 0091000	4	1533P 0081000	4	5200FE	6	6102UE	8	8268	10
10GX33 D151000	4	1533P 0101000	4	5200FH	6	6102UH	8	82841	9
10GX52F 0061000	4	1533P D151000	4	5200UE	8	6200FE	6	82842	9
10GX52F 0081000	4	1533R 0061000	4	5200UH	8	6200FH	6	83242	10
10GX52F 0091000	4	1533R 0091000	4	5200UP	8	6200UE	8	83265	10
10GX52F 0101000	4	1533R 0101000	4	5201FE	6	6200UH	8	83284	10
10GX53F 0081000	4	1533R F2V1000	4	5201FH	6	6201FE	6	84142	10
10GX53F 0091000	4	2152AE 0021000	7	5201UE	8	6201FH	6	8451	9
10GX53F 0101000	4	2152PE 0021000	7	5201UH	8	6201UE	8	88240	10
10GX53F D151000	4	2153AE 0091000	7	5202U1	8	6201UH	8	90SNS1P11H	13
10GX62F	9	2153PE 0091000	7	5202UE	8	6202UE	8	9104	11
10GX62F 0061000	4	2154AE 0081000	7	5202UH	8	6202UH	8	9116	11
10GX62F 0081000	4	2154PE 0081000	7	5202UP	8	6300FC	6	9116P	11
10GX62F 0091000	4	2155AE 0021000	7	5240F1	6	6300FE	6	9201	10
10GX62F 0101000	4	2155AE 0061000	7	5240U1	8	6300FH	6	9258	10
10GX63F	9	2155AE 0091000	7	5300F1	6	6300UE	8	9273	10
10GX63F 0081000	4	2155PE 0021000	7	5300FE	6	6300UH	8	9841	9
10GX63F 0091000	4	2155PE 0061000	7	5300FH	6	6301FE	6	9842	9
10GX63F 0101000	4	2155PE 0091000	7	5300U1	8	6301FH	6	9913	10
10GX63F D151000	4	2156AE 0051000	7	5300UE	8	6301UE	8	AV2183R100005	3, 18
10GXS32 0061000	4	2156PE 0051000	7	5300UH	8	6301UH	8	AX100749	17
10GXS32 0071000	4	2157AA T32U1000	7	5300UP	8	6302FC	6	AX101185	17
10GXS32 0091000	4	2157PA T32U1000	7	5301FE	6	6302FE	6	AX101852	17
10GXS32 0101000	4	2158AE 0061000	7	5301FH	6	6302UE	8	AX101877	17
10GXS33 0071000	4	2158PE 0061000	7	5301UE	8	6302UH	8	AX101878	17
10GXS33 0091000	4	2160PA T32U1000	7	5301UH	8	6320FE	6	AX101879	17
10GXS33 0101000	4	2161AA T32U1000	7	5302FE	6	6320UE	8	AX101880	17
10GXS33 D151000	4	2161PA T32U1000	7	5302GE	6	6321UE	8	AX101881	17
1189A	11	2162PA T32U1000	7	5302U1	8	6322UE	8	AX101882	17
1189AP	11	2179LA	9	5302UE	8	6341PC	6	AX101883	17
1212F	9, 10	2179LP	9	5302UH	8	6342PC	6	AX101884	17
1212F 0061000	4	2180LA	9	5302UP	8	6343PC	6	AX101885	17
1212F 0081000	4	2180LP	9	5320FE	6	6345PC	6	AX101886	17
1212F 0091000	4	2181LA	9	5320UE	8	6400FC	6	AX101887	17
1212F 0101000	4	2181LP	9	5321UE	8	6400FE	6	AX101888	17
1213F	9, 10	2183P	9	5322UE	8	6400FH	6	AX102242	16
1213F 0081000	4	2183P 009A1000	3	5400F1	6	6400UE	8	AX102243	16
1213F 0091000	4	2183P 010A250	3	5400FE	6	6400UH	8	AX102244	16
1213F 0101000	4	2183P 010A1000	3	5400FH	6	6401FE	6	AX102248	17
1213F D151000	4	2183P 0101000	3	5400UH	8	6401FH	6	AX102249	17
1307A	8	2183P D15A1000	3	5400UH	8	6401UE	8	AX102250	17
1308A	8	2183R	9	5401FE	6	6401UH	8	AX102251	17
1309A	8	2183R 006A1000	3	5401FH	6	6500FC	6	AX102256	17
1310A	8	2183R 009A1000	3	5401UE	8	6500FE	6	AX102257	17
1311A	8	2183R 010A1000	3	5401UH	8	6500FH	6	AX102282	4
1312A	8	2183R 0101000	3	5421FE	6	6500UE	6	AX102283	4
1313A	8	2412F	9	5500F1	6	6500UE	8	AX102334	17
1325A	6	2412F 0061000	4	5500FE	6	6500UH	8	AX102335	17
1325R	6	2412F 0081000	4	5500FH	6	6501FE	6	AX102336	17
1326A	6	2412F 0091000	4	5500UE	8	6501FH	6	AX102337	17
1326R	6	2412F 0101000	4	5500UH	8	6501UE	8	AX102655	17
1351A 0061000	4	2413F	9	5501FE	6	6501UH	8	AX102657	17
1351A 0081000	4	2413F 0081000	4	5501FH	6	6502FC	6	AX102660	17
1351A 0091000	4	2413F 0091000	4	5501UE	8	6502FE	6	AX102670	17
1352A 0081000	4	2413F 0101000	4	5501UH	8	6502GE	6	AX102671	17
1352A 0091000	4	2413F D151000	4	5502FE	6	6520FE	6	AX102903	16
1352A D151000	4	3105A	9	5502G1	6	6520UE	8	AX102904	16
1369P	11	3107A	9	5502GE	6	6521FE	6	AX102905	16
1369R	11	5100UP	8	5520FE	6	6521UE	8	AX102906	16
1370P	11	5000FE	6	5520UE	8	6522UE	8	AX102907	16
1370R	11	5000FH	6	5521FE	6	6541PA	6	AX102908	16
1371P	11	5000U1	8	5521UE	8	6542PA	6	AX103114	4
1371R	11	5000UE	8	5522UE	8	6543PA	6	AX103115	4
1384LA	9	5000UH	8	5522UG	7	6545PA	6	AX103121	4
1384LP	9	5000UP	8	5624UG	7	6546PA	6	AX103151	19
1387LA	9	5001UE	8	5626UG	7	6548PA	6	AX103254	4
1387LP	9	5001UH	8	5662UG	7	6549PA	6	AX103256	4
1388LA	9	5002UP	8	5788AV	11	6624UG	7	AX103922	17
1389LA	9	5100FE	8	6100UP	8	6626UG	7	AX103923	17
1392A	9	5100FH	6	6000FE	6	6662UG	7	AX104127	17
1392P	9	5100UE	8	6000FH	6	6788AV	11	AX104130	17
1393P	11	5100UH	8	6000UE	8	716SNS1P11H-25	11, 13	AX104131	17
1393R	11	5100UP	8	6000UH	8	716SNS1P11HQ-25	13	AX104156	4
1394P	11	5101FE	6	6001UE	8	716SNS1P11PL-25	11, 13	AX104157	4
1394R	11	5101FH	6	6001UH	8	7806A	10	AX104160	17
1395P	11	5101UE	8	6100FE	6	7808A	10	AX104161	17
1395R	11	5101UH	8	6100FH	6	7810A	10	AX104163	17
1396P	11	5102U1	8	6100UE	8	8216	10	AX104164	17
1396R	11	5102UE	8	6100UH	8	8219	10	AX104166	17
1397S5	11	5102UH	8	6101FE	6	8240	10	AX104230	17
1398S5	11	5102UP	8	6101FH	6	8259	10	AX104231	17

Be certain.

Part Number Index

Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
AX104232	17	AX106624	17	DSD006FB	15	FXFSTOSTK	19	RV6MJKURD-S1	5
AX104233	17	AX106625	17	DSD010FB	15	HD-800-2	14	RV6MJKUYL-B24	5
AX104234	17	AX106626	17	DSD013FB	15	HD-800-4	14	RV6MJKUYL-S1	5
AX104271	19	AX106627	17	DSD015FB	15	HD-800-8	14	RVAFPSME-B24	3, 5
AX104276	19	AX106628	17	DSIO02MB	17	HD-800-16	14	RVAFPSME-S1	3, 4, 5
AX104286	19	AX106629	17	DSIO03MB	15	HD-800-25	14	RVAFPUBK-B24	5
AX104479	17	AX106630	17	DSIO05MB	15	HD-800-35	14	RVAFPUBK-S1	4, 5
AX104480	17	AX106631	17	ECX-01U	20	HD-800-50	14	RVAMJKSME-B24	3, 5
AX104562	4	AX106632	17	ECX-02U	20	HDC001MB	14	RVAMJKSME-S1	3, 4, 5
AX104563	4	AX106633	17	ECX-04U	20	HDC002MB	14	RVAMJKUAL-B24	5
AX104564	4	AX106634	17	ECX-BRKT MNT-0	20	HDC003MB	14	RVAMJKUAL-S1	5
AX104573	16	AX106635	17	ECX-BRKT MNT-3	20	HDE001MB	14	RVAMJKUBK-B24	5
AX104574	16	AX106636	17	ECX-LOCKKIT	20	HDE002FB	14	RVAMJKUBK-S1	4, 5
AX104575	16	AX106637	17	FC3X06SDFS	20	HDE002MB	14	RVAMJKUBL-B24	5
AX104595	4	AX106638	17	FC3X12LDFS	20	HDE003FB	14	RVAMJKUBL-S1	4, 5
AX104687	17	AX106639	17	FC4X06SDFS	20	HDE003MB	14	RVAMJKUBR-B24	5
AX104688	17	AX106640	17	FC4X12LDFS	20	HDE005MB	14	RVAMJKUBR-S1	5
AX104689	17	AX106669	17	FCSX06SAFS	20	HDE006FB	14	RVAMJKUEW-B24	5
AX104937	16	AX106670	17	FCSX06SDFS	20	HDE007MB	14	RVAMJKUEW-S1	4, 5
AX104938	16	AX106671	17	FCSX12LAFS	20	HDE008FB	14	RVAMJKUGN-B24	5
AX104939	16	AX106672	17	FCSX12LDFS	20	HDE010FB	14	RVAMJKUGN-S1	5
AX105158-AL	17	AX106673	17	FF3X06SD	20	HDE010MB	14	RVAMJKUGY-B24	5
AX105158-BK	17	AX106674	17	FF3X12LD	20	HDE015FB	14	RVAMJKUGY-S1	5
AX105158-EW	17	AX106675	17	FF4X06SD	20	HDE015MB	14	RVAMJKUIV-B24	5
AX105158-GY	17	AX106676	17	FF4X12LD	20	HDE020MB	14	RVAMJKUIV-S1	5
AX105202-B25	19	AX106683	17	FFSX06SA	20	HDE025FB	14	RVAMJKUOR-B24	5
AX105202-B25*	10	AX106685	17	FFSX06SD	20	HDE035FB	14	RVAMJKUOR-S1	5
AX105203-B25	19	AX203567	19	FFSX12LA	20	HDE050FB	14	RVAMJKUPR-B24	5
AX105207-B25	19	AX203569	19	FFSX12LD	20	HDMM001MB	14	RVAMJKUPR-S1	4, 5
AX105207-B25*	10	BHRR194	21	FI4B004PBA	10	HDMM002MB	14	RVAMJKURD-B24	5
AX105208-B25	19	BHRR234	21	FI4B004RBA	10	HDMM003MB	14	RVAMJKURD-S1	5
AX105209-B25	19	BHRR6194	21	FS1BNC-25	12	PS11	11	RVAMJKUYL-B24	5
AX105252-B25	19	BHVH0XX	21	FS1BNC-25	11	PS59/6/RGB	11	RVAMJKUYL-S1	5
AX105253-B25	19	BHVHXX	21	FS1BNCSS1	12	PSA59/6	11	RVUC0EW-B50	3, 5
AX105334-AL	16	BHVHLXX	21	FS15BNCSS1	12	RV5MJKSME-B24	5	RVUC0T01	3, 5
AX105334-BK	16	BHVLOXX	21	FS59BNCUS	12	RV5MJKSME-S1	4, 5	RVUDCCX-B24	3, 5
AX105334-EW	16	CSF1100XXX	4	FS59BUS	13	RV5MJKUAL-B24	5	RVUICXX-B24	3, 5
AX105335-AL	16	CSF1106XXX	4	FS6BNCUS	12	RV5MJKUAL-S1	5	RVUT001	3, 5
AX105335-BK	16	CSF1108XXX	4	FS6US	13	RV5MJKUBK-B24	5	RVUT001	3, 5
AX105335-EW	16	CSF1109XXX	4	FSBNC1RGB	12	RV5MJKUBK-S1	5	RVUT0101	3, 5
AX105336-AL	16	C6F1100XXX	4	FSBNC6URA	12	RV5MJKUBL-B24	5	SNS1P1TH	13
AX105336-BK	16	C6F1106XXX	4	FSBNC15RA	12	RV5MJKUBL-S1	5	SNSUNI	11, 12, 13
AX105336-EW	16	C6F1108XXX	4	FSBNC15R6B	12	RV5MJKUBR-B24	5	VCMFDR4X4	21
AX105337-AL	16	C6F1109XXX	4	FSBNC59URA	12	RV5MJKUBR-S1	5	VGA003FB	15
AX105337-BK	16	CA21100XXX	4	FSNS1P6QS-25	11, 13	RV5MJKUEW-B24	5	VGA006FB	15
AX105337-EW	16	CA21106XXX	4	FSNS6BNCPL-25	12	RV5MJKUEW-S1	5	VGA010FB	15
AX105338-AL	16	CA21107XXX	4	FSNS6BNCPL-25	11, 12	RV5MJKUGN-B24	5	VGA012FB	15
AX105338-BK	16	CA21109XXX	4	FSNS6PL-25	13	RV5MJKUGN-S1	5	VGA015FB	15
AX105338-EW	16	CAF1100XXX	4	FSNS6PLQ-25	11	RV5MJKUGY-B24	5	VGA020FB	15
AX105339-AL	16	CAF1106XXX	4	FSNS6U-25	13	RV5MJKUGY-S1	5	VGA025FB	15
AX105339-BK	16	CAF1108XXX	4	FSNS6U-25	11	RV5MJKUIV-B24	5	VGA035FB	15
AX105339-EW	16	CAF1109XXX	4	FSNS6URA-25	13	RV5MJKUIV-S1	5	VGA040FB	15
AX105340-AL	16	CAPFMFL-S1	3, 4	FSNS11BNCPL-25	12	RV5MJKUIV-S1	5	VGA050FB	15
AX105340-BK	16	CAPFMFS-S1	4	FSNS11HBNC	12	RV5MJKUIV-S1	5	VGA075FB	15
AX105340-EW	16	CAPFMUL-S1	4	FSNS11QBNC-25	12	RV5MJKUPR-B24	5	VGA100FB	15
AX105341-AL	16	CPLCCT-SLMR	11, 12, 13	FSNS15-25*	13	RV5MJKUPR-S1	5	XDR8419-3##W	21
AX105341-BK	16	CPLCRBC-BR	12, 13	FSNS15BNC-25	11	RV5MJKURD-B24	5	XDR8419-3##XX	21
AX105341-EW	16	CPSNSCT-596	11, 12, 13	FSNS15BNC-25*	12	RV5MJKURD-S1	5	XDR8419-310	21
AX105342-AL	16	CTPFM01	3	FSNS59BNCPL	12	RV5MJKUYL-B24	5	XDR8419-310N	21
AX105342-BK	16	DB1BNC-25	12	FSNS59BNCPL-25	11, 12	RV5MJKUYL-S1	5	XDR8419-310N1M	21
AX105342-EW	16	DB15-25	13	FSNS59BNCPL-25	12	RV6MJKSME-B24	5	XDR8419-310N2M	21
AX105344-AL	16	DB15BNCCHD-25	12	FSNS59BNCU-25	12	RV6MJKSME-S1	4, 5	XDR8419-312	21
AX105344-BK	16	DB59BNCPL2/4-25	12	FSNS59PL-25	13	RV6MJKUAL-B24	5	XDR8419-312N	21
AX105344-EW	16	DB59BNCPL3-25	12	FSNS59U-25	13	RV6MJKUAL-S1	5	XDR8419-312N1M	21
AX105345-AL	16	DB59BNCPL-25	12	FSNS59U-25	11	RV6MJKUBK-B24	5	XDR8419-312N2M	21
AX105345-BK	16	DB59BNCU-25	12	FSNS59URA-25	13	RV6MJKUBK-S1	5	XDR8423-3##W	21
AX105345-EW	16	DB59PL2/4-25	13	FT1LC900FS01	19	RV6MJKUBK-S1	5	XDR8423-3##XX	21
AX105346-AL	16	DB59U-25	13	FT13C900FS01	19	RV6MJKUBL-S1	5	XDR8419-610	21
AX105346-BK	16	DB6BNCPL2-25	12	FT13LC900FS01	19	RV6MJKUBR-B24	5	XWM-2109-GD	21
AX105346-EW	16	DB6BNCU-25	12	FT13SC900FS01	19	RV6MJKUBR-S1	5	XWM-2109-GD	21
AX105566	17	DB6PL2-25	13	FT14LC900FS01	19	RV6MJKUEW-B24	5	XWM-2312-GD	21
AX105568	17	DB6U-25	13	FT14SC900FS01	19	RV6MJKUEW-S1	5	XWM-2312-GD	21
AX105569	17	DCPLCRBC-BR	12	FTSLB900FS01	19	RV6MJKUGN-B24	5	XWM-2320-GD	21
AX105641-AL	16	DDD001MB	15	FTSLC900FS01	19	RV6MJKUGN-S1	5	XWM-2320-GD	21
AX105641-BK	16	DDD002FB	15	FTSSB900FS01	19	RV6MJKUGY-B24	5	XWM-2320-GD	21
AX105641-EW	16	DDD002MB	15	FTSSC900FS01	19	RV6MJKUGY-S1	5	XWM-2320-GD	21
AX106617	17	DDD003MB	15	FXFSSHFM1*	19	RV6MJKUIV-B24	5		
AX106618	17	DDD005MB	15	FXFSSHFM2	19	RV6MJKUIV-S1	5		
AX106619	17	DDD013FB	15	FXFSTOPL	19	RV6MJKUIV-S1	5		
AX106620	17	DDIO02MB	15	FXFSTOPTK	19	RV6MJKUIV-S1	5		
AX106621	17	DDIO03MB	15	FXFSTOSCL	19	RV6MJKUIV-S1	5		
AX106622	17	DDIO05MB	15	FXFSTOSLT	19	RV6MJKUPR-B24	5		
AX106623	17	DSD003FB	15	FXFSTOSPL	19	RV6MJKUPR-S1	5		
						RV6MJKURD-B24	5		



GLOBAL LOCATIONS

For worldwide Sales and Technical Support, visit: www.belden.com



UNITED STATES

Division Headquarters

401 Pennsylvania Parkway, #200
Indianapolis, IN 46280
USA
Phone: +1 317-818-6300
Inside Sales: 800-235-3361
Fax: +1 317-818-6382
info@belden.com

CANADA

National Business Center

2310 Alfred-Nobel
St-Laurent Quebec H4S 2B4
Canada
Phone: +1 514-822-2345
Fax: +1 514-822-7979
info@belden.com

MEXICO

Regional Office

Insurgentes Sur #1602
Piso 1 Oficina 102
Código Constructor Del.
Benito Juárez , C.P. 03940
Mexico
Phone: +52 55-5523-7733
Fax: +52 55-5528-8077
ventas.mexico@belden.com