





KEY FEATURES:

17.5 kWh battery
28" tyres with steel wheels
575kg load bed capacity
Towbar & 1500kg tow capacity
Three seats
Electronic 4x2 to 4x4 system
5000lbs winch
Glass windscreen with wash wipe





BASIC PARAMETERS

CATEGORY

ENERGY TYPE

RANGE

CHARGING TIME

DIMENSIONS (L x W x H)

MAX. SPEED

FULL-SIZE UTV

LITHIUM BATTERY

100km (BASED ON AVE. SPEED OF 40km/H)

6 HRS AT 3.3 kW (US/EURO STANDARDS)

3149 x 1632 x 2010 mm

90km/H

SUSPENSION AND STEERING

DRIVE TYPE REAR-MOUNTED REAR-WHEEL DRIVE
FOUR WHEEL DRIVE TYPE PART-TIME 4WD
FRONT SUSPENSION TYPE DOUBLE WISHBONE INDEPENDENT SUSPENSION
REAR SUSPENSION TYPE DOUBLE WISHBONE INDEPENDENT SUSPENSION
ELECTRONIC POWER STEERING EPS

ELECTRIC SYSTEMS

MOTOR TYPE PERMANENT MAGNET SYNCHRONOUS
RATED / PEAK POWER 35 / 80 kW
RATED / PEAK TORQUE 90 I 230 N-M
NUMBER OF DRIVE MOTORS I
BATTERY TYPE LITHIUM BATTERY
BATTERY COOLING METHOD LIQUID-COOLED
BATTERY CAPACITY 17.5 kWH
BATTERY PRE-HEATING STANDARD

BRAKES

FRONT BRAKE TYPE

REAR BRAKE TYPE

DUAL HYDRAULIC VENTED DISC

ELECTRONIC PARKING BRAKE

FRONT TYRE SIZE

S*9.0 R14

REAR TYRE SIZE

28*11.0 R14

STEEL HUB (MATTE BLACK)

ALUMINIUM HUB (MATTE BLACK)

STANDARD

BODY

WHEELBASE 2050 MM FRONT WHEEL TRACK 1365 мм REAR WHEEL TRACK 1256 мм MINIMUM GROUND CLEARANCE 280 MM (WHEN FULLY LOADED) MAXIMUM INCLINE ANGLE >60% MINIMUM TURNING RADIUS 2-Door, 3-Seat DOOR OPENING STYLE FRONT-HINGED NUMBER OF DOORS NUMBER OF SEATS CARGO BOX CAPACITY 900 kg **CURB WEIGHT** MAXIMUM FULLY LOADED WEIGHT 1600 KG CARGO BOX LOAD CAPACITY **BODY STRUCTURE** LOAD-BEARING



0333 358 2175



ENQUIRIES@VOLCONMOTORS.CO.UK



VOLCONMOTORS.CO.UK







KEY FEATURES:

17.5 kWh battery
28" tyres with steel wheels
575kg load bed capacity
Towbar & 1500kg tow capacity
Three seats
Electronic 4x2 to 4x4 system
5000lbs winch
Glass windscreen with wash wipe





BASIC PARAMETERS

CATEGORY FULL-SIZE UTV
ENERGY TYPE LITHIUM BATTERY
RANGE 100KM (BASED ON AVE. SPEED OF 40KM/H)

CHARGING TIME 6 HRS AT 3.3 KW (US/Euro Standards)

Dimensions (L x W x H) 3149 x 1632 x 2010 mm

MAX. SPEED 90KM/H

BRAKES

FRONT BRAKE TYPE

REAR BRAKE TYPE

DUAL HYDRAULIC VENTED DISC

DUAL HYDRAULIC VENTED DISC

ELECTRONIC PARKING BRAKE

STANDARD

FRONT TYRE SIZE

28*9.0 R14

REAR TYRE SIZE

28*11.0 R14

STEEL HUB (MATTE BLACK)

OPTIONAL

STANDARD

SUSPENSION AND STEERING

DRIVE TYPE REAR-MOUNTED REAR-WHEEL DRIVE
FOUR WHEEL DRIVE TYPE PART-TIME 4WD
FRONT SUSPENSION TYPE DOUBLE WISHBONE INDEPENDENT SUSPENSION
REAR SUSPENSION TYPE DOUBLE WISHBONE INDEPENDENT SUSPENSION
ELECTRONIC POWER STEERING EPS

ELECTRIC SYSTEMS

MOTOR TYPE PERMANENT MAGNET SYNCHRONOUS
RATED / PEAK POWER 35 / 80 kW
RATED / PEAK TORQUE 90 I 230 N-M
NUMBER OF DRIVE MOTORS 1
BATTERY TYPE LITHIUM BATTERY
BATTERY COOLING METHOD LIQUID-COOLED
BATTERY CAPACITY 17.5 kWH
BATTERY PRE-HEATING STANDARD

BODY

ALUMINIUM HUB (MATTE BLACK)

WHEELBASE 2050 мм FRONT WHEEL TRACK 1365 мм REAR WHEEL TRACK 1256 мм MINIMUM GROUND CLEARANCE 280 MM (WHEN FULLY LOADED) MAXIMUM INCLINE ANGLE >60% MINIMUM TURNING RADIUS 4.2 M OVERALL VEHICLE STRUCTURE 2-Door, 3-SEAT DOOR OPENING STYLE FRONT-HINGED NUMBER OF DOORS NUMBER OF SEATS 785 L CARGO BOX CAPACITY 900 KG **CURB WEIGHT** MAXIMUM FULLY LOADED WEIGHT 1600 KG CARGO BOX LOAD CAPACITY 575 KG **BODY STRUCTURE** LOAD-BEARING



0333 358 2175



ENQUIRIES@VOLCONMOTORS.CO.UK



VOLCONMOTORS.CO.UK