

VL  
CN

## HFI - ULTIMATE

### KEY FEATURES:

17.5 kWh BATTERY  
28" TYRES WITH STEEL WHEELS  
575KG LOAD BED CAPACITY  
TOWBAR & 1500KG TOW CAPACITY  
THREE SEATS  
ELECTRONIC 4X2 TO 4X4 SYSTEM  
5000LBS WINCH  
GLASS WINDSCREEN WITH WASH WIPE

DOVER WHITE

FOREST GREEN

HARVEST TAN

STEEL GREY

### BASIC PARAMETERS

CATEGORY	FULL-SIZE UTV
ENERGY TYPE	LITHIUM BATTERY
RANGE	100KM (BASED ON AVE. SPEED OF 40KM/H)
CHARGING TIME	6 HRS AT 3.3 kW (US/EURO STANDARDS)
DIMENSIONS (L x W x H)	3149 x 1632 x 2010 MM
MAX. SPEED	90KM/H

### SUSPENSION AND STEERING

DRIVE TYPE	REAR-MOUNTED REAR-WHEEL DRIVE
FOUR WHEEL DRIVE TYPE	PART-TIME 4WD
FRONT SUSPENSION TYPE	DOUBLE WISHBONE INDEPENDENT SUSPENSION
REAR SUSPENSION TYPE	DOUBLE WISHBONE INDEPENDENT SUSPENSION
ELECTRONIC POWER STEERING	EPS

### ELECTRIC SYSTEMS

MOTOR TYPE	PERMANENT MAGNET SYNCHRONOUS
RATED / PEAK POWER	35 / 80 kW
RATED / PEAK TORQUE	90   230 N-M
NUMBER OF DRIVE MOTORS	1
BATTERY TYPE	LITHIUM BATTERY
BATTERY COOLING METHOD	LIQUID-COOLED
BATTERY CAPACITY	17.5 kWh
BATTERY PRE-HEATING	STANDARD

### BRAKES

FRONT BRAKE TYPE	DUAL HYDRAULIC VENTED DISC
REAR BRAKE TYPE	DUAL HYDRAULIC VENTED DISC
ELECTRONIC PARKING BRAKE	STANDARD
FRONT TYRE SIZE	28*9.0 R14
REAR TYRE SIZE	28*11.0 R14
STEEL HUB (MATTE BLACK)	OPTIONAL
ALUMINIUM HUB (MATTE BLACK)	STANDARD

### BODY

WHEELBASE	2050 MM
FRONT WHEEL TRACK	1365 MM
REAR WHEEL TRACK	1256 MM
MINIMUM GROUND CLEARANCE	280 MM (WHEN FULLY LOADED)
MAXIMUM INCLINE ANGLE	>60%
MINIMUM TURNING RADIUS	4.2 M
OVERALL VEHICLE STRUCTURE	2-DOOR, 3-SEAT
DOOR OPENING STYLE	FRONT-HINGED
NUMBER OF DOORS	2
NUMBER OF SEATS	3
CARGO BOX CAPACITY	785 L
CURB WEIGHT	900 KG
MAXIMUM FULLY LOADED WEIGHT	1600 KG
CARGO BOX LOAD CAPACITY	575 KG
BODY STRUCTURE	LOAD-BEARING



0333 358 2175



ENQUIRIES@VOLCONMOTORS.CO.UK



VOLCONMOTORS.CO.UK





# HF1 - ULTIMATE

## KEY FEATURES:

DOVER WHITE



FOREST GREEN



HARVEST TAN



STEEL GREY



17.5 kWh BATTERY  
28" TYRES WITH STEEL WHEELS  
575KG LOAD BED CAPACITY  
TOWBAR & 1500KG TOW CAPACITY  
THREE SEATS  
ELECTRONIC 4x2 TO 4x4 SYSTEM  
5000LBS WINCH  
GLASS WINDSCREEN WITH WASH WIPE

## BASIC PARAMETERS

CATEGORY	FULL-SIZE UTV
ENERGY TYPE	LITHIUM BATTERY
RANGE	100KM (BASED ON AVE. SPEED OF 40KM/H)
CHARGING TIME	6 HRS AT 3.3 kW (US/EURO STANDARDS)
DIMENSIONS (L x W x H)	3149 x 1632 x 2010 MM
MAX. SPEED	90KM/H

## SUSPENSION AND STEERING

DRIVE TYPE	REAR-MOUNTED REAR-WHEEL DRIVE
FOUR WHEEL DRIVE TYPE	PART-TIME 4WD
FRONT SUSPENSION TYPE	DOUBLE WISHBONE INDEPENDENT SUSPENSION
REAR SUSPENSION TYPE	DOUBLE WISHBONE INDEPENDENT SUSPENSION
ELECTRONIC POWER STEERING	EPS

## ELECTRIC SYSTEMS

MOTOR TYPE	PERMANENT MAGNET SYNCHRONOUS
RATED / PEAK POWER	35 / 80 kW
RATED / PEAK TORQUE	90   230 N-M
NUMBER OF DRIVE MOTORS	1
BATTERY TYPE	LITHIUM BATTERY
BATTERY COOLING METHOD	LIQUID-COOLED
BATTERY CAPACITY	17.5 kWh
BATTERY PRE-HEATING	STANDARD

## BRAKES

FRONT BRAKE TYPE	DUAL HYDRAULIC VENTED DISC
REAR BRAKE TYPE	DUAL HYDRAULIC VENTED DISC
ELECTRONIC PARKING BRAKE	STANDARD
FRONT TYRE SIZE	28*9.0 R14
REAR TYRE SIZE	28*11.0 R14
STEEL HUB (MATTE BLACK)	OPTIONAL
ALUMINIUM HUB (MATTE BLACK)	STANDARD

## BODY

WHEELBASE	2050 MM
FRONT WHEEL TRACK	1365 MM
REAR WHEEL TRACK	1256 MM
MINIMUM GROUND CLEARANCE	280 MM (WHEN FULLY LOADED)
MAXIMUM INCLINE ANGLE	>60%
MINIMUM TURNING RADIUS	4.2 M
OVERALL VEHICLE STRUCTURE	2-DOOR, 3-SEAT
DOOR OPENING STYLE	FRONT-HINGED
NUMBER OF DOORS	2
NUMBER OF SEATS	3
CARGO BOX CAPACITY	785 L
CURB WEIGHT	900 KG
MAXIMUM FULLY LOADED WEIGHT	1600 KG
CARGO BOX LOAD CAPACITY	575 KG
BODY STRUCTURE	LOAD-BEARING

