



SunValue

Capture the sun




Extend Your Swim Season with SunValue Solar Pool Heating!

Get the most out of your swimming pool with the SunValue Solar Pool Heating System. You'll be able to set your desired temperature and extend your swim season — allowing you to enjoy your pool even more throughout the year.

By going solar, you'll get all the perks of a heated pool while being environmentally friendly by using the power of the sun.


Designed with your roof in mind, our panels require less roof penetrations because they don't use straps. The slim, light weight design of SunValue also makes installation much easier.

With over 40 years of experience and a proven track record in manufacturing solar collectors, you can be ensured that SunValue is a reliable and efficient system.



How It Works

1. Using your existing pool pump, pool water is directed through a series of valves to your solar collectors.
2. Pool water enters the solar collectors at the bottom and rises to the top through the individual tubes of the collector.
3. As the water rises through the collector, it is heated by the sun's radiant energy.
4. The water is then returned to the pool to repeat the cycle until your pool has been warmed to your desired temperature.



Design Features

1. Unique Hexagon–Shaped Manifold

A flat aesthetic installation on a large range of roof types.

2. Reinforced Ribs

Ensures the manifold header withstands various pressure and temperature changes over time.

3. Over–Molding Manufacturing Method

Eliminate leaks from welding by fusing the header directly over the panel tubes.

4. Individual Tube Design

Minimize wind effects on the panel and allows for rapid moisture release.

5. Spacer Bars

Prevents the panel from warping over time and abrasion to the riser tubes.

Other Features

- **The Modular Structure** enables fast and firm connection between panels, creating any size absorption area over any type of roof imaginable.
- **Specially Formulated Polymer Material** stabilizes against sustained ultraviolet radiation, extreme weather and aging.
- **Alligator Clamps** can be positioned anywhere on the panel header and allows for direct drilling to various designs of roof truss structures.
- **All-Polymer Parts and Fittings** create simple connections between panels and standard plumbing pipes.

**Optional fittings to flex hose with a 2" adaptor.*

Costs of Operation

Annual costs to heat your pool can add up quickly if you use gas or electric heating options. However, with a SunValue Solar Pool Heating System, your only additional cost to your utility bill is running a pool pump at a fraction of the cost.

Pool Pump with SunValue

May increase your electric bill by \$30 to \$74 per year.

\$840

Electric Heat Pump

Annual Average of Heating Expenses**

\$1,704

Gas Heat Pump

Annual Average of Heating Expenses**

**Based on a 1,000 SF, uncovered outdoor pool in Atlanta, GA heated to 78° between April 1 and October 31. Figures provided by the U.S. Department of Energy website: www.energysavers.gov



Collector Data

Collector Model	SV-48	SV-40	SV-32
Size, Nominal	4' x 12'	4' x 10'	4' x 8'
Width	47.24"	47.24"	47.24"
Length	143.70"	119.69"	95.67"
Aperture Area	47.14 sq ft	39.26 sq ft	31.38 sq ft
Manifold Diameter	2"	2"	2"
Dry Weight	16.53 lbs	13.67 lbs	11.02 lbs
Volume Capacity	3.8 gal	3.1 gal	2.4 gal
Working Pressure	90 psi	90 psi	90 psi
Burst Pressure	135 psi	135 psi	135 psi
Typical Flow	5 - 7 gpm	4 - 6 gpm	3 - 5 gpm

Certification Data

Certifying Organization	National Standard SRCC
SV-48	47,135
SV-40	39,551
SV-32	28,279
Performance Expectations	$\eta = (0.909)(1 - 0.026u) - (2.1084 + 1.1254u)(P/G)$



SV-48

Solar Insolation

Category T(°F)	2,000 BTU/ft ²	1,500 BTU/ft ²	1,000 BTU/ft ²
Water Temp. Minus Air Temp. A (-9)	94.28	75.42	56.57
B (+9)	47.14	28.28	9.43
C (+36)	4.71	0	0
D (+90)	0	0	0

Thousands of BTU's per day per panel

SV-40

Solar Insolation

Category T(°F)	2,000 BTU/ft ²	1,500 BTU/ft ²	1,000 BTU/ft ²
Water Temp. Minus Air Temp. A (-9)	78.32	62.82	47.11
B (+9)	39.26	23.56	7.85
C (+36)	3.93	0	0
D (+90)	0	0	0

Thousands of BTU's per day per panel

SV-32

Solar Insolation

Category T(°F)	2,000 BTU/ft ²	1,500 BTU/ft ²	1,000 BTU/ft ²
Water Temp. Minus Air Temp. A (-9)	62.76	50.21	37.66
B (+9)	31.38	18.83	6.28
C (+36)	3.14	0	0
D (+90)	0	0	0

Thousands of BTU's per day per panel

KEY

- A - Pool Heating (Warm Climate) B - Pool Heating (Cool Climate)
- C - Water Heating (Warm Climate) D - Space & Water Heating

Distributed By:



a Magen eco-Energy Company

800.79.SOLAR • www.umasolar.com

For more information, contact your local SunValue Dealer or UMA Solar Representative.

9-9014-025 | 1902