

OUTDOOR VOICE DOWN

The Action-CS Voice Down adapter allows for easy and seamless integration of speakers, strobe lights, and microphone into a vandal-resistant and weatherproof housing for most Bosch camera applications.

This adapter can be ceiling, pole mounted, or bracket mounted onto new or existing IP cameras to enhance and update the security functionality of the property. With no additional wiring needed to power this device, only the camera's existing CAT5E/6 cable is necessary to power this voice down and control it while providing power to the existing camera via POE.

You can now trigger lights and audio by events through your NVR or manually through your NVR and have two-way or one-way communication through a camera location. This greatly enhances your security and deters any would be criminal activity from occurring. You have the ability to trigger strobe lights and communicate with a perpetrator through a camera location with ease by using their already installed and native NVR system.



GO LIVE WITH A FEW SIMPLE STEPS!

Simply mount the camera to the voice down

01

Plug in the network cable from the camera to the voice down adapter

02

Then plug in the original CAT5E/6 cable into the voice down input

03

Hook up the audio and alarm outputs and you are live!

04

SEAMLESS INTEGRATION

Action-CS seamlessly integrates the Bosch Audio Amplifier into the Action-CS Active Deterrence Unit (ADU), giving you full control and seamless integration of active crime deterrence into your existing Bosch Architecture.

YOU WON'T NEED TO WORRY ABOUT:

- Changing platforms
- Integrating third-party solutions
- Perform complex and time-consuming integrations

AMPLIFIER MODULE 15W, SIP OVERVIEW

- Full IP for power (PoE), communication (SIP) and control
- Low impedance loudspeaker connection and amplifier line out
- Class D amplifier and Digital Signal Processing (DSP)
- Remotely configurable via Web-GUI



Action-CS Active Deterrence Units work with nearly all Bosch cameras.



BULLET CAMERAS
DINION bullet cameras are designed for indoor and outdoor applications with a zoom lens and built-in infrared illuminator.



MULTI-IMAGER CAMERAS
FLEXIDOME multi-imager cameras provide multi-directional overviews for wide-area coverage applications.



FIXED DOME CAMERAS
FLEXIDOME cameras are discreet indoor or outdoor cameras in a dome housing. Available in micro dome, mini dome, or turret.



PANORAMIC CAMERAS
FLEXIDOME panoramic cameras give 360- or 180-degree overview without any blind spots.

AN OPTIONAL ACTION-CS HORN IS AVAILABLE ON THE EXTERIOR UNIT FOR ADDITIONAL DETERRENCE FOR APPLICATIONS WHERE AUDIO IS NEEDED UP TO 150'.



SPECIFICATIONS

SOUND	1 x 60 watt stereo amp output to 4 IP67 speakers
LIGHTS	(3) 18 watt LED red/blue strobe lights with (6) 3 watt LED's each in IP65 rated housing
MICROPHONE	(1) IP67 rated omni-directional condenser mic
DIMENSIONS	6.0" X 5.9" X 5.3" (HxWxD)
CASING	Aluminum powder coated, vandal-resistant housing (optional custom colors with min order of 10 units)
HOUSING	IP34 rated for outdoor environments
POWER	POE++ powered with POE pass through to the camera
CAMERA OUTPUT REQUIREMENTS	MIC, RJ45 POE
CAMERA INPUT REQUIREMENTS	Alarm out, 3.5mm audio, 2 - wire audio terminal

