

INTEGRATED BATTERY PACK MAGNETIC MOUNT INSTRUCTIONS

PLEASE MAKE SURE THE WEATHER PLUG IS CLOSED WHEN THE MOUNT IS NOT CHARGING

(The battery mount is NOT weather resistant without the plug installed)

ELECTRICAL NOTES

FOR THE MOST ACCURATE BATTERY LEVEL ESTIMATE, CHECK WITH THE DISH POWERED OFF AND UNPLUGGED FROM THE CHARGER

- We recommend charging your battery mount with the factory 110V cord and power supply that was supplied from Starlink with your Mini dish.
- The battery voltage display/gauge is only designed for general reference. The battery voltage display/gauge reads current voltage across the internal battery. When the charger is connected and supplying power to the internal battery, the battery display/gauge will read the elevated voltage across the battery, and once disconnected reads the actual voltage across the battery. Same goes for checking battery status with the dish powered on. Checking the battery status on the gauge while the dish is powered on will result in a lower reading than the actual battery status.

MOUNTING NOTES

- Mount on a roof location that DOES NOT POOL WATER, many RV roofs hold a lot of water near awnings, etc. The mount is sealed up, but not submersible.

WARRANTY

- Unique Componentry provides the original purchaser a one year warranty on Unique Componentry workmanship and parts. This does not cover improper installation or wiring (including hooking up to reverse polarity or over voltage).
- If you disassemble the mount in any way, you will void your warranty with Unique Componentry (example: removing the back door that is laser engraved.)
- Physical damage to the mount due to improper mounting, installation, dropping the mount, etc is not covered by Unique Componentry's warranty.
- Failure of Starlink OEM parts or components is not covered by Unique Componentry's warranty.

HOPE YOU ENJOY YOUR NEW BATTERY MINI MOUNT!

Please feel free to reach out with any questions/concerns to: info@uniquecomponentry.com
