

INSTRUCTIONS - DO NOT DISCARD

Here are some tips to help you enjoy your new all-in-one Starlink conversion

YOUR CONVERSION CAME STANDARD WITH REMOTES (UNLESS REQUESTED OTHERWISE OR YOU HAVE AN ETHERNET PORT) AND YOU MUST UTILIZE THESE TO TURN YOUR CONVERSION ON/OFF

NETWORK

- The DEFAULT Network Name will be the last name you provided on your order form in all capital letters with no password.
- Most units get the network name reset during the conversion process, to rename the network either login on your Starlink App or Power Cycle 6 times using the remote On/ OFF/ On/ Off/ On/ Off/ On/ OFF/ On/ Off/ On/ Off/ On waiting a second or two between each button press. This will factory reset the network, you will then be prompted to rename and issue a password.

ELECTRICAL

- *****PAY CLOSE ATTENTION TO THE + AND - POLARITY. WIRING IN REVERSE WILL RUIN THE UNIT WHICH IS NOT COVERED UNDER WARRANTY.*****
- Hardwire the provided receptacle and wiring harness DIRECTLY to the battery if at all possible **WITH THE PROVIDED 10GA WIRING HARNESS AND FUSE.**
- When plugging the power cable in to the four pin receptacle on the dish, line up the locating tab and thread in the metal collar.
- Once wired you will see the 2 pin connector will plug in then the twist collar will thread in and lock/seal it.
- For more flexible/temporary use, you can find the provided 12v cigarette lighter adapter tip that will also thread onto your Starlink's male plug, there is a replaceable fuse in this tip also.

SNOW MELT MODE

- **Turn Snow Melt OFF using the Starlink App.** You must be logged into your associated Starlink account within the app. Just brush it off, it will work MUCH FASTER and not drain your battery or potentially hurt the power supply.

MOUNTING

- Mount on a roof location that DOES NOT POOL WATER, many RV roofs hold a lot of water near awnings, etc. the unit is sealed up, but not submersible.
- The threaded inserts on the rear are 1/4-20 UNC thread. *****DO NOT OVER TIGHTEN TORQUE TO 5 FOOT POUNDS MAX*****
- *****USE BLUE LOCTITE AT MAXIMUM FOR THREADED INSERTS! DO NOT USE RED LOCTITE!*****
- One of the included remotes is a KEY FOB, the other is a WALL MOUNT.

HOPE YOU ENJOY YOUR NEW AND IMPROVED HARDWARE!

Please feel free to reach out with any questions/concerns to: info@uniquecomponentry.com

