

Hartwell Speedway

2020 Up Front Rules

WEIGHT MUST BE POSTED ON DRIVER SIDE A-PILLAR

MUFFLERS REQUIRED

NO MIRRORS OR RADIOS ALLOWED

- A. Any 4-cylinder front wheel drive allowed. NO ALL WHEEL DRIVE/ 4 WHEEL DRIVES
- B. DOT tires only. All 4 rims must be same size. No grooving, or softening allowed. May run 7in bead lock on right front.
- C. May slot strut towers/mounts
- D. May hull doors for bars
- E. Interior deck sheet metal optional
- F. Body – must have OEM top, hood and trunk. May use sheet metal or aluminum for sides. Must be stock appearing
- G. Sheet metal mud/rock deflector permitted on back of front fenders, doors, quarters. From bottom, up 4”
- H. May run stock appearing plastic nose/tail piece
- I. Tubular bumpers allowed. Must be capped.
- J. 160 HP engines max must have manual.
- K. Cold air intake permitted. Must remain under the hood
- L. No superchargers or blowers permitted
- M. Cars are to be raced the way they come from factory (OEM) unless otherwise stated. Header are allowed.
- N. Sheet metal doors, side fenders, & Quarters allowed.

WEIGHT

- A. 2300 at all times
- B. Full containment seat, head & neck restraint, on board fire suppression recommended.

PROTEST

- A. Complete car \$300 Track retains \$100.
- B. Tire \$125 per tire. Fee to be paid by both teams. Winner of protest will get their money back

- C. \$100 Claimer on Comp

#### VISUAL

- A. Must be made before event starts
- B. \$25 per item. Track retains all money

#### SAFETY

- A. Properly mounted fire extinguisher within drivers reach mandatory
- B. Full, approved fire suit and helmet mandatory
- C. Properly mounted quick release safety belts in good condition
- D. Must have securely mounted bucket type racing seat mandatory
- E. Securely mounted fuel tank. FUEL CELL PREFERRED
- F. Neck collar highly recommend
- G. Modifying right rear suspension for safety is recommended. Caravan right rear hub ok.