



TERRA COTTA



COLONIAL RED



REGAL RED *



BURGUNDY *



PATINA GREEN



HEMLOCK GREEN *



HARTFORD GREEN *



EVERGREEN




SLATE BLUE



REGAL BLUE *



SOLAR WHITE



REGAL WHITE



STONE WHITE



SURREY BEIGE

TLG MOONSTONE™ *

TLG CHARCOAL GRAY *

TLG MEDIUM BRONZE *

TLG DARK BRONZE *

TLG BLACK *

TEXTURED LOW-GLOSS (TLG) PVDF COLORS



SIERRA TAN



SANDSTONE



ASH GRAY



DOVE GRAY



SLATE GRAY




CHARCOAL GRAY



BURNISHED SLATE



MEDIUM BRONZE



MANSARD BROWN



DARK BRONZE



MATTE BLACK



VINTAGE® *



PRE-WEATHERED GALVALUME® *



COR-TEN AZP RAW® *

TLG BLACK

ACRYLIC GALVALUME

HARTFORD GREEN

REGAL BLUE

24 GAUGE PVDF COLORS

GIDEON

STEEL PANEL COMPANY

— EST 2005 —



SHERWIN-WILLIAMS
Coil Coatings

Sherwin-Williams® is a trademark of SWIMC LLC.

Colors shown are matched as accurately as possible, but may vary slightly from the finished product. These rich and vibrant colors are produced with PVDF resins, to provide superior color retention. Touch-up should only be done with a Gideon approved color matched PVDF air-dry paint pen.

* Available at a slight price premium * Metallic premium * Weathered premium




SILVER *



COPPER *



CHAMPAGNE *



ACRYLIC-COATED GALVALUME®

COOL Color	LEED V4.1	ISR	EMI	3-yr SRI	SRI
Acrylic Coated Galvalume	L	0.67	0.14	N/A	56
Ash Gray	-	0.32	0.83	31	31
Burgundy	-	0.31	0.86	29	32
Burnished Slate	-	0.25	0.83	22	22
Champagne Metallic	-	0.32	0.83	31	31
Charcoal Gray	-	0.25	0.83	22	22
Colonial Red	-	0.25	0.83	22	22
Copper Metallic	L	0.35	0.75	32	32
Cor-Ten AZP® Raw	-	0.32	0.89	N/A	34
Dark Bronze	-	0.25	0.83	22	22
Dove Gray	L	0.35	0.83	35	35
Evergreen	-	0.25	0.83	22	22
Hartford Green	-	0.25	0.83	22	22
Hemlock Green	-	0.25	0.83	22	22
Mansard Brown	-	0.25	0.83	22	22
Matte Black	-	0.25	0.83	22	22
Medium Bronze	-	0.25	0.83	22	22
Patina Green	-	0.32	0.83	31	31
Pre-weathered Galvalume	-	0.24	0.83	19	21
Regal Blue	-	0.25	0.83	22	22
Regal Red	L	0.35	0.83	35	35
Regal White	L	0.65	0.83	77	77
Sandstone	L	0.35	0.83	35	35
Sierra Tan	-	0.31	0.87	28	31
Silver Metallic	L	0.54	0.77	55	60
Slate Blue	-	0.25	0.83	22	22
Slate Gray	L	0.35	0.83	35	35
Solar White	L	0.65	0.83	77	77
Stone White	L	0.55	0.83	59	63
Surrey Beige	L	0.35	0.75	32	32
Terra Cotta	L	0.35	0.83	35	35
TLG Black	-	0.25	0.83	22	22
TLG Charcoal Gray	-	0.25	0.83	22	22
TLG Dark Bronze	-	0.25	0.83	22	22
TLG Medium Bronze	-	0.25	0.83	22	22
TLG Moonstone	-	0.32	0.83	31	31
Vintage®	-	0.30	0.70	N/A	22

GIDEON

STEEL PANEL COMPANY

— EST 2005 —



When Quality and Performance Matters!™
 (405) 942-7878 • www.gideonsteel.com

*Concealed Fastener
 Architectural Metal
 Roofing & Siding*

*Snap Lock & Mechanical Seam
 Standing Seam*

Fluropon® by **SHERWIN-WILLIAMS®** Coil
 Coatings is a 70% PVDF coating system.

Metal Roofing has never been **COOLER!**

- Factory made, packaged in crates.
- Manufactured at jobsite, stage on ground or direct to roof.
- Radius - Curved Panels and Trim.

L = LEED V4.1 Compliant
 ISR = Initial Solar Reflectance
 EMI = Emissivity
 SRI = Solar Reflectance Index

- Solar Reflectance Index (SRI) is used to determine compliance with LEED requirements using values for reflectance and emissivity.
- For low slope roofing (defined as ≤ 2:12) to meet LEED V4.1 requirements, the initial SRI must be ≥ 82 or the 3-year SRI must be ≥ 64. For steep slope roofing (defined as > 2:12) to meet LEED V4.1 requirements the initial SRI for 75% of the roof must be ≥ 39 or the 3-year SRI must be ≥ 32.
- FLUROPON® provided by Gideon Steel, is a two coat PVDF proprietary resin paint system with a .20 mil primer and .70 - .90 mil Top Coat of 70% PVDF resin-based coating. The reverse side has a .20 mil primer and .30 - .40 mil Backer Coating.
- Colors shown are matched as accurately as possible, but may vary slightly from the finished product. These rich and vibrant colors are produced with PVDF resins, to provide superior color retention. Touch-up should only be done with an Gideon approved color-matched PVDF air-dry paint pen.
- Paint warranty varies between the different coatings ie standard, matte, metallic and weathered. Metallic, Vintage and weathered coatings may vary from batch to batch and are directional. Use caution on the job site when mixing paint runs. Contact Gideon for details.
- Oil canning is aesthetic and is an inherent part of light gauge cold formed metal products. By designing for thermal movement, following stringent specifications for installation and proper handling, most oil canning can be eliminated. Oil canning is not grounds for coil/panel rejection.
- Galvalume is a registered trademark of BIEC. Sherwin-Williams® and Fluropon® are trademarks of SWIMC, LLC. Cor-Ten AZP® Raw is a trademark of United States Steel Corporation.