



This SDS comparison was compiled to show that Omstar DX1 is different from all of the popular fuel additives. Most of the products listed have very similar and even identical ingredients as you can see in the color call out in the ingredients area. At the very bottom of the chart you see those called out ingredients are the exact ingredients of some popular paint strippers and paint thinners.

Omstar DX1 is safe for the environment, and safe for your employees health. The other products are environmentally toxic and have ingredients with known health issues.

With the known issues of ULSD not having enough lubrication, why not use a product that doesn't utilize the same ingredients as paint strippers and paint thinners ?

When looking at any additives, ask to see their SDS.

PRODUCT COMPARISONS & SDS



Please note the highlighted ingredients Below

**Glycol Ethers (Ethylene
Glycol Monobutyl
Ether)
(Glycol Ether Compound)**

MINERAL SPIRITS

**LIGHT AROMATIC
SOLVENT NAPHTHA**

TRIMETHYLBENZENE

XYLENE

CUMENE

ETHYLBENZENE

ISOPROPANOL

STODDARD-SOLVENT


METHANOL

TOLUENE


ALPHATIC HYDOCARBON

(Paint Strippers and Paint Thinners Ingredients.)


SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		AMSOIL PERFORMANCE IMPROVER	AMSOIL DIESEL CONCENTRATE PERFORMANCE FUEL ADDITIVE	AMSOIL DIESEL CETANE BOOST	AMSOIL QUICKSHOT SE	BIOBOR Biobor JF	CERION ENERGY	Chevron Techron	CITGO Mystick Diesel Fuel Conditioner	CLEAN BOOST COMBUSTION CATALYST	CONKLIN 4-POWER D	CONKLIN DIESEL PLUS
FLASH POINT	338°F / 170°C	162°F / 72°C	117°F / 47°C	149°F / 65°C	165°F / 74°C	102°F / 38.8°C	199°F / 92°C	105°F / 41°C	113°F / 45°C	110°F / 43.3°C	6°F / -14°C	122°F / 50°C
FIRE & EXPLOSION HAZARDS	NO	N/A	N/A	N/A	N/A	N/A	N/A	N/A	YES	N/A	N/A	YES
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	YES	YES	N/A	YES	YES	NO	YES	YES	YES	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	YES	YES	N/A	YES	YES	N/A	YES	YES	YES	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	NONE	MARINE POLLUTANT	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
CATALYST/SOLVENT BASED INGREDIENTS	NONE	SOLVENT NAPHTHA, (PETROLEUM), HEAVY ALIPHATIC NAPHTHALENE, BENZENE	SOLVENT NAPHTHA, (PETROLEUM), TRIMETHYL-BENZENE, BENZENE, CUMENE, XYLENE	ETHYLHEXYL NITRATE	SOLVENT NAPHTHA, (PETROLEUM), HEAVY ALIPHATIC	PETROLEUM NAPHTHA, DIOXABORINANE	KEROSENE, OLEIC ACID, DIMETHYL ETHER-METHOXY, PROPANOL	XYLENE, CUMENE, SOLVENT NAPHTHA, TRIMETHYL-BENZENE, STODDARD-SOLVENT	OCTYLNITRATE, LIGHT AROMATIC SOLVENT NAPHTHA, TRIMETHYL-BENZENE, 1,2,4-TRIMETHYLBENZENE, PROPANOL, 1-METHOXY	SOLVENT NAPHTHA, TRIMETHYL-BENZENE	XYLENE, METHOXY, METHANOL, NAPHTHALENE, ETHYLBENZENE, TRIMETHYL-BENZENE, PETROLEUM NAPHTHA	METHOXY, PROPANOL, NAPHTHALENE, ETHYLBENZENE, TRIMETHYL-BENZENE, BUTOXY ETHANOL
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO


SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		DIESELEX GOLD	eeFule nanotechnology F2-21 FUEL ADDITIVE	EGO DIESEL BOOST	ENERTECK Enerburn	Esso	FPPF Total Power Diesel Fuel Treatment	FT Fuel Technology	HOWES LUBRICATOR PRODUCTS DIESEL TREAT	HOWES LUBRICATOR PRODUCTS LUBRICATOR FUEL SYSTEM	HOWES LUBRICATOR PRODUCTS MEANER POWER KLEANER	INNOSPEC ECOCLEAN POWER PLUS
FLASH POINT	338°F / 170°C	125°F / 52°C	180°F / 82°C	111°F / 44°C	110°F / 43.3°C	N/A	110°F / 48.3°C	106°F / 41°C	150°F / 65.5°C	173°F / 78.3°C	153°F / 67.2°C	180°F / 82°C
FIRE & EXPLOSION HAZARDS	NO	YES	YES	YES	N/A	N/A	YES	N/A	N/A	N/A	N/A	YES
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	NO	N/A	YES	N/A	YES	YES	YES	YES	N/A	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	N/A	N/A	YES	N/A	YES	YES	YES	YES	N/A	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	N/A	N/A	YES	N/A	YES	YES	YES	YES	N/A	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	MARINE POLLUTANT	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
CATALYST/SOLVENT BASED INGREDIENTS	NONE	PETROLEUM-DISTILLATE, SATURATED - HYDROCARBONS, AROMATIC - HYDROCARBONS, UNSATURATED - HYDROCARBONS, BENZENE	2-ETHYLHEXYL NITRATE, ETHYLENE GLYCOL, GLYCOL ETHER	XYLENE, MONOMER, NAPHTHALENE, ETHYLBENZENE, TRIMETHYL-BENZENE, VINYL ACETATE, ALKYL ALCOHOL, ETHYLENE GLYCOL-N-BUTYL ETHER	LIGHT AROMATIC NAPHTHA	SOLVENT NAPHTHA, TRIMETHYLBENZENE, XYLENE, CUMENE, 2-ETHYLHEXANOL	Aromatic hydrocarbon Ester Primary aliphatic alcohol 1,2,3-Trimethylbenzene Glycol Ether LIGHT AROMATIC SOLVENT NAPHTHA XYLENE TRIMETHYLBENZENE CUMENE	SOLVENT NAPHTHA	ALIPHATIC HYDROCARBON, TRIMETHYL-BENZENE, ETHYLBENZENE, VINYL ACETATE	ALIPHATIC HYDROCARBON	ALIPHATIC HYDROCARBON, TRIMETHYL-BENZENE, NAPHTHALENE	SOLVENT NAPHTHA, POLYETHY-BENZENE, NAPHTHALENE
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO


SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		LUBRIZOL LUBRIZOL 8090 CETANE IMPROVER FOR DIESEL FUEL	MARVEL MYSTERY OIL	MARYN POWERUP BLACKOUT	MARYN DIESEL-FX	MARYN GEN 49D WITH CI	POWER D SYL	POWER SERVICE DIESEL FUEL SUPPLEMENT +CETANE BOOST	POWER UP GEN 49D WITH CETANE	PRO ONE	PRIMEROSE FIRE POWER	PRIMEROSE POWER BLEND
FLASH POINT	338°F / 170°C	149°F / 65°C	140°F / 60°C	192°F / 88°C	163°F / 72°C	147°F / 63°C	100°F / 38°C	105°F / 41°C	153°F / 67°C	200°F / 93°C	102°F / 38°C	148°F / 64.4°C
FIRE & EXPLOSION HAZARDS	NO	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	YES	YES
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	N/A	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	N/A	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	NONE	MARINE POLLUTANT	MARINE POLLUTANT	MARINE POLLUTANT	NONE	NONE	NONE	Oxidizing agents, don't heat above flash point.	NONE	NONE
CATALYST/SOLVENT BASED INGREDIENTS	NONE	2-ETHYL-HEXYL NITRATE	KEROSENE, HYDRO-TREATED-MINERAL SPIRITS, NAPHTHENIC-DISTILLATE	SOLVENT NAPHTHA, (PETROLEUM) HEAVY AROM, NAPHTHALENE	ETHYLBENZENE, ETHYLENE-GLYCOL-MONOBUTYL, ETHER 2-ETHYL-HEXYL NITRATE, SOLVENT NAPHTHA, NAPHTHALENE	SOLVENT NAPHTHA, (PETROLEUM) HEAVY AROM, 2-ETHYLHEXYL-NITRATE, POLYMERIC-SUCCINIMIDE, XYLENE, MIXTURE OF ISOMERS, ETHYLENE GLYCOL-MONOBUTYL-ETHER, LONG CHAIN DICARBOXYLIC ACID	STODDARD-SOLVENT PETROLEUM SOLVENT, TRIMETHYL-BENZENE, NAPHTHALENE, ETHYLBENZENE, ACETATE, VINYL ACETATE	XYLENE, CUMENE, VINYL ACETATE, ETHYLBENZENE, NAPHTHALENE, TRIMETHYL-BENZENE	XYLENE, ETHYLHEXYL, HEAVY & LIGHT-AROMATIC-NAPHTHA, TRIMETHYL-BENZENE, VINYL ACETATE-MONOMER, ETHYLENE-GLYCOL-N-BUTYL ETHER	SOLVENT NAPHTHA, NAPHTHALENE	LIGHT NAPHTHENIC HYDROTREATED DISTILLATES, ORGANIC SOLVENT	LIGHT NAPHTHENIC HYDROTREATED DISTILLATES
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	25%	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO


SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		PRIMEROSE POWER MASTER PLUS	PRIMEROSE PROTECT O LUBE PLUS	SEAFOAM	SCHAEFFER'S BIO TREAT	SCHAEFFER'S DIESEL TREAT 2000 SUMMER	SCHAEFFER'S DIESEL TREAT 2000 ULS WINTER	SCHAEFFER'S PREMIUM SOY SHIELD	SCHAEFFER'S SOY SHIELD	SCHAEFFER'S SOY ULTRA GASOLINE ADDITIVE BULK	SCHAEFFER'S TOP TIER FUEL ADDITIVE	SFR LUBRICITY/CETANE IMPROVER DIESEL FUEL CONDITIONER
FLASH POINT	338°F / 170°C	142°F / 61°C	102°F / 38.9°C	55°F / 12.8°C	140°F / 60°C	131°F / 55°C	113°F / 45°C	273°F / 134°C	158°F / 70°C	122°F / 50°C	100°F / 38°C	145°F / 62.8°C
FIRE & EXPLOSION HAZARDS	NO	YES	YES	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
CATALYST/SOLVENT BASED INGREDIENTS	NONE	LIGHT NAPHTHENIC HYDROTREATED DISTILLATES	LIGHT NAPHTHENIC HYDROTREATED DISTILLATES, ORGANIC SOLVENT	NAPHTHA, ISOPROPANOL	XYLENE, BENZENE, NAPHTHALENE, BUTOXY-ETHANOL, ETHYLBENZENE, BUTOXYETHANOL, TRIMETHYL-BENZENE	XYLENE, NAPHTHA, CUMENE, BENZENE, ETHYLBENZENE, NAPHTHALENE, BUTOXYETHANOL, ETHYLHEXYL-NITRATE, TRIMETHYL-BENZENE	XYLENE, VINYL-ACETATE, NAPHTHALENE, ETHYLBENZENE, BUTOXY-ETHANOL	2-ETHYL-HEXYL NITRATE, LIGHT AROMATIC SOLVENT, NAPHTHA, METHYL SOYATE, XYLENE, CUMENE, 2,4-TRIMETHYLBENZENE, ETHYLBENZENE, BENZENE, VINYL ACETATE MONOMER	HEAVY AROMATIC SOLVENT NAPHTHA, 2-ETHYL-HEXYL NITRATE, LIGHT AROMATIC SOLVENT, NAPHTHA, METHYL SOYATE, XYLENE, CUMENE, 2,4-TRIMETHYLBENZENE, ETHYLBENZENE, NAPHTHALENE, BENZENE, 2-BUTOXYETHANOL, VINYL ACETATE MONOMER	XYLENE, ETHYLBENZENE, NAPHTHALENE, METHYL SOYATE, PETROLEUM-DISTILLATES	NAPHTHANENE, ETHYLBENZENE, XYLENE	ETHYLHEXL NITRATE, XYLENE, VINYL ACETATE MONOMER
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO


SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		SFR MULTIFUNCTIONAL DIESEL FUEL CONDITIONER	SFR PROTECTA FUEL SYSTEM TREATMENT	SLICK 50 FUEL SYSTEM TREATMENT	SOLTRON	STA-BIL FUEL STABILIZER	STANADYNE	STARBRITE STAR TRON	STP COMPLETE FUEL SYSTEM CLEANER	STP OCTANE BOOSTER	TRC DIESEL FUEL POUR DEPRESSANT	TRC DZL-LENE XL-10
FLASH POINT	338°F / 170°C	115°F / 46.1°C	145.5°F / 63°C	122°F / 50°C	158°F / 70°C	183°F / 83.88°C	124°F / 51.1°C	165°F / 73.8°C	129°F / 54°C	140°F / 60°C	145°F / 63°C	147°F / 64°C
FIRE & EXPLOSION HAZARDS	NO	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	N/A	YES	YES	YES	YES	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	YES	YES	YES	NO	N/A	YES	YES	YES	YES	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	YES	YES	YES	YES	N/A	YES	YES	YES	YES	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	NONE	NONE	NONE	Avoid strong Oxidizing agents.	NONE	NONE	NONE	NONE	NONE	AVOID STRONG OXIDIZERS
CATALYST/SOLVENT BASED INGREDIENTS	NONE	PETROLEUM NAPHTHA, TRIMETHYL-BENZENE, CUMENE, ETHYLBENZENE, XYLENE, PROPYLENE GLYCOL ETHER	PETROLEUM NAPHTHA, MINERAL SPIRITS, NAPHTHALENE, POLYETHERAMINE	DISTILLATES, SWEETENED-MIDDLE-NAPHTHA, HYDRODE-SULPHURISE, POLYETHER AMINE, SOLVENT NAPHTHA, TRIMETHYL-BENZENE	ALIPHATIC-PETROLEUM-DISTILLATES	PETROLEUM DISTILLATE	NAPHTHA, NAPHTHALENE, ETHYLENE-GLYCOL-MONO-BUTYL ETHER, TRIMETHYL-BENZENE	SOLVENT NAPHTHA, HEAVY ALIPHATIC (95%W/W)	XYLENE, KEROSENE, METHANOL, CUMENE, NAPHTHALENE, PROPYLBENZENE, TRIMETHYL-BENZENE, PETROLEUM-NAPHTHA	KEROSENE, PETROLEUM-NAPHTHA, TRIMETHYL-BENZENE, NAPHTHALENE, METHYL-CYCLOPENTADIENYL-MANGANESE, ETHYBENZENE	SOLVENT NAPHTHA, NAPHTHALENE, XYLENE, TRIMETHYL-BENZENE, ETHYBENZENE, VINYL ACETATE	SOLVENT NAPHTHA, NAPHTHALENE, HYDROTREATED (SEVERE) HEAVY PARAFFINIC
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO

SAFETY DATA SHEETS COMPARISONS

FUEL ADDITIVES		TRC DZL-PEP ARTIC WITH AAT	TRC DE-GEL	WYNN'S DIESEL CHARGE DIESEL TREATMENT	WYNN'S DIESEL INJECTOR PURGE	WYNN'S DIESEL PRO	WYNN'S EMISSION CONTROL +FUEL TREATMENT	WYNN'S FUEL INJECTOR CLEANER	WYNN'S PREMIUM DIESEL TREATMENT	WYNN'S PROFESSIONAL COMBUSTION CHAMBER CLEANER	WYNN'S VALVE INJECTOR COMBUSTION CHAMBER CLEANER	XLP FUEL PERFORMANCE BOOSTERS
FLASH POINT	338°F / 170°C	145°F / 62.8°C	75°F / 24°C	112°F / 44°C	125°F / 52°C	150°F / 66°C	101°F / 38°C	148°F / 64°C	151°F / 66°C	61°F / 16°C	61°F / 16°C	151°F / 66°C
FIRE & EXPLOSION HAZARDS	NO	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
CANCER CAUSING BY STATE OF CALIFORNIA	NO	YES	YES	YES	N/A	YES	YES	YES	YES	YES	YES	YES
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	YES	YES	YES	N/A	YES	YES	YES	YES	YES	YES	YES
KNOWN ISSUES STATED ON MSDS	NONE	NONE	AVOID STRONG OXIDIZERS	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
CATALYST/SOLVENT BASED INGREDIENTS	NONE	SOLVENT NAPHTHA, NAPHTHALENE, XYLENE, TRIMETHYL-BENZENE	SOLVENT NAPHTHA, NAPHTHALENE, BUTOXYETHANOL, ISOPROPANOL	LIGHT AROMATIC-NAPHTHA, PRIMINE AMINE, DI-TERT-BUTYL, PEROXIDE	4-METHYL-2-PENTONAL	HEXANE, BENZENE, TOLUENE, XYLENES, NAPHTHALENE	DI-TERT-BUTYL, PEROXIDE, NAPHTHALENE	LIGHT AROMATIC-SOLVENT NAPHTHA	SOLVENT NAPHTHA, NAPHTHALENE, ETHYLBENZENE	XYLENE, PHENYLETHANE, SOLVENT NAPHTHA, ETHYLBENZENE	XYLENE, ETHYLBENZENE, ISOPROPANOL, SOLVENT NAPHTHA	XYLENE, HIGH FLASH AROMATIC-NAPHTHALENE, TRIMETHYL-BENZENE, DIETHANOLAMINE, SOLVENT NAPHTHA
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO

SAFETY DATA SHEETS COMPARISONS

PAINT STRIPPERS AND THINNERS		ACE PAINT THINNER	KLEAN-STRIP STRIP X	KLEAN-STRIP VM&P NAPHTHA	KRYLON OFF PAINT & VARNISH STRIPPER	RUST-OLEUM AUTO STRIPPER	SAVOGRAN Strypeeze	SUNNYSIDE CNH THINNER CNH THINNER	SUNNYSIDE THINNER A THINNER A			
FLASH POINT	338°F / 170°C	105°F / 40.55°C	25°F / -3.88°C	50°F / 10°C	0°F / -17.77°C	200°F / 93°C	20°F / -6.66°C	79°F / 26.11°C	143°F / 61.6°C			
FIRE & EXPLOSION HAZARDS	NO	YES	YES	YES	YES	YES	YES	YES	YES			
ENVIRONMENTAL TOXICITY	NO	YES	YES	YES	YES	YES	YES	YES	YES			
COMPONENTS ON STATE REGULATORY LIST	NO	YES	YES	YES	YES	YES	YES	YES	YES			
CANCER CAUSING BY STATE OF CALIFORNIA	NO	YES	YES	YES	YES	YES	YES	YES	YES			
BIRTH DEFECTS BY STATE OF CALIFORNIA	NO	YES	YES	YES	YES	YES	YES	YES	YES			
KNOWN ISSUES STATED ON MSDS	NONE	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.	Avoid strong Oxidizing agents.			
CATALYST/SOLVENT BASED INGREDIENTS	NONE	STODDARD-SOLVENT, ALIPHATIC PETROLEUM DISTILLATES, 1,2,4-TRIMETHYL-BENZENE, RAFFINATES	XYLENE, TOLUENE, DICHLORO-METHANE, METHANOL, ACETONE, PLOYMER MIXTURE	HEXANE, LIGHT ALIPHATIC NAPHTHA, SOLVENT NAPHTHA	PROPANE, BUTANE, METHYLENE CHLORIDE, TOLUENE, METHANOL, METHYL ETHYL KETONE	METHYLENE CHLORIDE, ISOPROPANOL, MINERAL SPIRITS, PARRAFIN WAX	DICHLOR-OMETHANE, METHANOL, TOLUENE, ACETONE, ALPHATIC HYDOCARBON, PARRAFIN WAX	MINERAL SPIRITS, LIGHT AROMATIC SOLVENT NAPHTHA, TRIMETHYLBENZENE, XYLENE, CUMENE, ETHYLBENZENE	2-BUTOXYETHANOL Glycol Ethers (Ethylene Glycol Monobutyl Ether) (Glycol Ether Compound)			
APPLICATION COMPARISONS												
CAN BE ADDED TO MOST MOTOR OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO			
CAN BE ADDED TO MOST DIFFERENTIAL OIL	YES	NO	NO	NO	NO	NO	NO	NO	NO			
CAN BE ADDED TO MOST HYDRAULIC FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO			
CAN BE ADDED TO MOST TRANSMISSION FLUID	YES	NO	NO	NO	NO	NO	NO	NO	NO			