



How to Use a Battery Powered Autoscrubber

Auto-scrubbers come in many sizes and can be used on floors in many different ways. They are the most productive form of removing oily, 'stuck on' soils from all types of floor coverings.

Daily use of the auto-scrubber utilizes low pH chemicals and low impact pads or brushes, to loosen the day's soil load for the squeegee to remove as the machine covers the floor surface. Be sure to size the unit to the job for maximum performance.

Daily Auto-scrubber Use

- Unplug the charger from the wall outlet.
- Disconnect charger from the unit and check battery water levels (once per week), making sure that water level is above plates. Fill to bottom of ring with distilled water if needed. Note: Some units do not require water and may be sealed.
- Connect control panel to batteries and check that all motors work.
- Place pads or brushes on drivers and install onto unit.
- Install squeegee assembly on rear of unit.
- Fill auto-scrubber solution tank with low pH diluted chemical solution.
- Fill a clean mop bucket with the same solution.
- Dust/damp mop all floors prior to running unit. The smallest amount of debris will cause the squeegee blade to streak the floor.
- Place wet floor signs around area to be cleaned.

- Position the unit with **right** hand side against wall. Drop the pad driver/brush deck and squeegee to floor.
- Turn on vacuum.
- Turn on water, half - full on.
- Turn on pad driver/brush and start moving the machine forward. This process will put down cleaning solution and scrub the dirt loose from the floor, vacuuming 100% of this dirty solution into the recovery tank.
- Once the complete area has been scrubbed clean, use flat mop of choice to detail the edges and mop up any turns left by the unit.
- At the end of the shift, return the unit to the closet and flush both tanks.
- Leave the covers off of the tanks so that they will air dry. Clean recovery tank filter screen.
- Remove squeegee from the unit, clean and hang on wall.
- If unit is equipped with pad/driver, remove pad from pad driver and clean both.
- Unplug the control panel from the batteries and connect charger.
- Then plug charger into wall socket.
- Wipe down unit.
- Report any service issues to your supervisor.

www.AcademyOfCleaning.com
888-999-6059