

# HBRC RACING

# TT01



## EURO TRUCK RULES 2024

<b>Chassis</b>	<p>Tamiya TT01-E series chassis only. Kit must be assembled as per the instruction manual. Only modifications allowed:</p> <ul style="list-style-type: none"> <li>• Battery tray may be trimmed to accept 'square' battery packs.</li> <li>• You do not have to use the included motor heat guard.</li> </ul>
<b>Motor and ESC</b>	<p>Motor must be the Tamiya Torque-Tuned brushed motor (as supplied in the kit). Motor must not be modified or tampered with in any way. ESC must be the Tamiya TBLE 02S or Hobbywing HHBQ6021 WP-1040 (as supplied in the kit). You can use any type of battery connector.</p>
<b>Wheels &amp; Tyres</b>	<p>Must be the Tamiya Racing Truck rims (can be the Black, White or Chrome version). Tamiya Racing Truck tyres (#51589). No tyre inserts are allowed. Gluing of tyre sidewall is optional.</p>
<b>Gearing</b>	<p>Only the 61T spur gear (as supplied in the kit) must be used. A 19T pinion must be used. Can be upgraded to a hard annodised aftermarket version.</p>
<b>Batteries</b>	<p>Any 2S / 7.4V Lipo - including shorty packs.</p>
<b>Body</b>	<p><b>Tamiya Racing Truck bodies:</b> Team Hahn Racing MAN (#51606) / Buggra Fat Fox (#51613) / Mercedes Benz MP4 (#51654). <b>or Bittydesign IRON Euro Truck (BDTRK-190IRO).</b> Bodies must be trimmed to the manufacturers original trim lines as per the instructions. No lowering of the cab is allowed - by trimming, or heating &amp; reshaping. No rear wings are allowed (<i>also applies to the Bittydesign wing</i>). Screws may be used to strengthen the joining of the body panels. Additional foam may be added to the front bumper to support the body.</p>



<b>Hop-up Options</b>	<p>The following parts are the <b>ONLY</b> hop-up parts allowed:</p> <ul style="list-style-type: none"> <li>• Steel Bearings.</li> <li>• Aluminium Centre Shaft set (#54026).</li> <li>• Metal Motor Mount (#53666).</li> <li>• 2 degree Toe-in Rear uprights (#53673).</li> <li>• Any Servo Saver/Horn and suitable turnbuckle steering link (from servo saver only).</li> </ul>
-----------------------	---