



SPEC SERIES RULES V2.5

Chassis	Standard Tamiya TT02 series car kits only (not the 'S' or 'D' or any other variants). Kit must be assembled as per the instruction manual. Only modifications allowed: • The battery strap can be modified to accomodate 'Shorty' battery packs. • You don't have to use the included motor guard / fan holder.
Motor and ESC	Motor must be the Tamiya Torque-Tuned brushed motor (as supplied in the kit). Motor must not be modified or tampered with in any way. ESC must be the Tamiya TBLE 02S or HobbyWing Quicrun 1060 Brushed. You can use any type of battery connector.
Wheels & Tyres	Must be the Spec pre-mounted tyres, (Ride 24mm Pre Cut Slicks) which are sold by a number of different distributors: • RIDE 24025 IIC Spec Tyres, • HUDY 803040 Spec Tyres, • Gravity RC GRC124GTB Spec Tyres. <i>Note: They are all the same tyre & insert on different multi-spoked rims (in some cases there are optional black or white rims).</i>
Gearing	Only the 70T spur gear (as supplied in the kit) must be used. A maximum of 25T pinion must be used. Can be any aftermarket Brand.
Batteries	Any 2S / 7.4V Lipo - including shorty packs.
Body	Must be based on a 'real' race car, preferably a GT3 as run in many global GT series, or any 'real' racing sedan or rally car. Authentic paint schemes are encouraged. No generic 'soap-dish' RC Touring Car race bodies or LM Prototypes allowed.
Hop-up Options	The following parts are the ONLY hop-up parts ALLOWED: • Steel Bearings. • Aluminium Centre Shaft (#54501 or any manufacturer). • Metal Motor Mount (#54558 or any manufacturer). • Alloy shock absorbers (any manufacturer). • Alloy wheel hexes • Any Servo Saver and suitable turnbuckle steering link (from servo saver only). The following parts are NOT ALLOWED (from Tamiya or any other manufacturer): • CVD's (#53792) or alloy dogbones • Adjustable turnbuckles • Optional gear sets, spur gears or ball diffs (#54500) • Alloy steering rack (#54574 / 54575)