



8W ECO Fixed Small Downlight

Features

Economical Design
Multiple Current Settings
Class Leading Efficacy

Finish

Black/White/Custom Frame

Material

Glass Lens Cover
Aluminium Frame
PMMA Optics



IC-4

Technical Characteristics

Light Source


Output (W): 6.76W 150mA 36V
Total power consumption (W): 8W
Color temperature: 2700K/3000K/4000K
CRI: 95+
Photobiological risk: RG1
Delivered Lm: 640 lm 3000K
R9 Value: 77
Delivered lm/W : 94.72lm
Life Time: 50.000h L90B10
MacAdam steps: 3
UGR: <15

Gear

Flicker-Free Phase Cut Driver
Flicker-Free DALI Optional
Casambi Integral Driver Optional

Warranty

Luminaire: 5 Years
Control Gear: 5 Years



- Cutout: 75mm
- ▨ Plaster Depth 5-25mm
- ▨ Total Depth 76mm

LIGHT DISTRIBUTION for Medium 36°

	Cone Lx (Avg)	Cone Diameter (cm)
1.0m	1347.81 lx	78.90cm
2.0m	336.91 lx	157.40cm
3.0m	149.76 lx	236.74cm

COLOUR DISTRIBUTION Nm for 3000K

