

**INSYNC ENG – JACUZZI/ASTRAL/HURLCON SERIES PROTECTIVE METAL COVER INSTALLATION INSTRUCTIONS**

**TURN OFF POWER, REMOVE EXISTING PLASTIC, REMOVE BEZEL ASSY AND BE CAREFUL HANDLING PRINTED CIRCUIT BOARD ASSY! DAMAGE CAN RESULT**

**1. YOUR COVER KIT SHOULD CONTAIN A COVER AND ADHESIVE**




YOUR COVER WILL FIT THE FOLLOWING SHAPED PANELS



CENTER COVER & ALIGN HINGE KNUCKLE TO LINE INDICATED. MARK AS NECESSARY WITH PENCIL



APPLY ADHESIVE TO BACKSIDE OF INDICATED "FIXED" SECTION ON COVER HINGE. DO NOT GET ADHESIVE ON "SWINGING" SECTION OF COVER HINGE



POSITION BONDED COVER. ALLOW ADHESIVE TO DRY FOR 24 HOURS. YOU MAY NEED TO "PROP" OPEN THE SERVICE DOOR SO COVER DOES NOT SLIDE OFF WHILE DRYING



**TWO IMPORTANT NOTES:**

1. WE HIGHLY RECOMMEND YOU REMOVE ANY EXPOSED PARTS OF YOUR DECAL. IT IS GOING TO ROT OVER TIME ANYWAY. INDICATED BY **XXXXXXXXXXXXXXXX**
2. WE PROVIDE TWO HOLES FOR MOUNTING USING SCREWS. IF YOU DECIDE TO USE SCREWS TO ATTACH MAKE SURE SCREWS DO NOT DAMAGE YOU DISPLAY OR ELECTRONICS UNDERNEATH