

RIG 2

Hoisting and Rotating

Drawworks: National 110-UE (1,500 hp) powered by 2-GE 752 traction motors

Auxiliary Brake: Elmagco 6032

Rotary Table: Ideco 275-K with a 27 ½" opening

Top Drive: CanRig 1250 AC (1,150 hp, 500 Ton electric)

Power Package

Generators: 3-Kato 1,204 kW powered by CAT-3512C

Control House: Omron 4 – SCR 3 – Gen

Well Control:

Annular: 13 5/8" Horn Spherical 5,000 psi
Double Ram: 13 5/8" Cameron Type U 10,000 psi
Single Ram: 13 5/8" Cameron Type U 10,000 psi

Accumulator: Koomey 7 Station Choke Manifold: 4" x 2" 10,000 psi

Mud System

Mud Pumps: 3-HongHua HHF-1600HL powered by 2-752 traction motors

Mud Line: 5" Line, 7,500 psi system

Mud Pits: 2-pit system (1,340 bbl) with 6 agitators 120 bbl premix pit built into suction

Shale Shakers: 3-Derrick Hyperpool

Degasser: Atmospheric Separator: 5' x 16" Trip Tank: 110 barrels

Structural

Mast: Pyramid 142' 840,000 pounds static hookload on 12 lines

Substructure: Pyramid box on box 25' floor height

Fluid Storage

Diesel Tank: 1-tank 20,000 gallon total capacity
Water Tank: 2-tank 1,000 bbl total capacity

Tubulars Multiple Tubular Options Available

Miscellaneous

Rig Moving System: Veristic Walking System (1200 ton)

BOP Handling System: JD Neuhaus (40 Ton)

Iron Roughneck: NOV ST-80 Pipe Spinner: Gray Mark 10

Air Compressor: 2-Sullivan 50 UD/50 DGHW-TE 50hp Survey Instrument: Fivestar retriever wireline unit

Survey Instrument: Fivestar retriever wireline Automated Catwalk: CanRig PC-3000

Transport

Loads: 35 Loads (less tubulars)