



IMP PUMPS®
Intelligent Motor Pumps

IMP PUMPS
OEM
LINE



NMT
NEO



Follow us on LinkedIn:

www.imp-pumps.com

Main features:

- TE Super seal connector
- Even more compact than the classic program
- Key Ordering → we can match your needs
- Minimalistic and easy-to-use interface
- Hydraulics available in cataphoresis coating and stainless steel

COMMUNICATION VERSIONS

STANDARD

- Auto mode
- 3x proportional pressure curves
- 3x constant pressure curves
- 3x constant speed curves

PWM

- Option switching between PWM solar and heating profile
- 3x proportional pressure curves
- 3x constant pressure curves
- 3x constant speed curves
- PWM output (flow)


HEAT

- PWM Heating profile
- Constant speed mode
- PWM output (flow)

SOL

- PWM Solar profile
- Constant speed curve
- PWM output (flow)

2 MODEL OPTIONS



Technical specification	
DN	15/20/25/32/40/50
Threaded connection	G 1 / G1¼ / G1½ / G2
Flange connection	32/40/50
Cable lengths [mm]	50/100/150/200/500
Medium temperature	up to 110°C
Ambient temperature	up to 40°C

NMT NEO

flow up to 6 m³/h



NMT NEO HF

flow up to 12 m³/h

