



DYNAMO ULTRA[®] ALL-IN-ONE CETANE BOOSTER
DU-AIO-CB
Product Data Sheet

Performance Technology
Multifunctional Performance Diesel Fuel Additive

DYNAMO ULTRA[®] All-In-One Cetane Booster is a high-performance multifunctional diesel fuel additive that increases fuel economy, restores & improves torque & power, cleans and maintains pumps & injectors, (including newer model year engines operating high pressure common rail injectors), reduces carbon residue & sulfur, prevents sludging, improves lubricity and increase thermal efficiency burn.

For Use In:

- Large Trucks / Semi Tractors
- Generators
- Mining Equipment
- Marine Engines (Marine Cetane B)
- Construction Equipment
- Military & Emergency Vehicles
- Railroad Locomotive Engines
- Buses
- Farm Equipment
- Passenger Vehicles
- Boats of all sizes (Marine Cetane Booster)

Application

At Recommended Treat Rate of 640:1, DYNAMO ULTRA[®] AIO Cetane Booster provides the following performance benefits:

- Greatly improves fuel economy
- Increases cetane number: approx. 8-points
- Increased thermal efficiency burn
- Restores & Improves torque & power
- Cleans and prevents all types of injector deposits
- Provides superior wear protection for pumps and injectors
- Reduces cost of maintenance & downtime
- Improves cold-flow & cold weather starting
- Reduces engine noise – smoother idle
- Reduces exhaust emissions, (THC, CO, NOx, CO2, PM).
- Reduces carbon residue & sulfur content in diesel fuel, thereby reducing output of carbon, soot & ash, reducing DPF issues & regens, thereby reducing DEF consumption.
- Provides thermal and oxidative stability, lubricity, corrosion protection and water dispersancy.
- Corrosion Inhibitors & Lubricity Improvers work on a molecular level with surface active chemistry & long-chain molecules, approved under military specifications

Additional Information

DYNAMO ULTRA[®] AIO Cetane Booster may be continuously or batch blended into diesel fuel.

Dosing Systems

CyberFuels[™] Inc. offers both tank farm / bulk storage injection couplers and tractor onboard dosing systems.

Material Compatibility

DYNAMO ULTRA[®] AIO Cetane Booster is compatible with other commonly used fuel additives, and with engine & fuel systems materials of construction when dosed at the Recommended Treat Rate of 640:1. CyberFuels[™] has treated more than 60M gallons of fuel with no adverse issues.

EPA Registration

NO. 273620002
 40CFR80.591 Compliant
 LEGAL DIESEL Fuel Additive

Personal Safety, First Aid and Storage and Handling

See MSDS for full product specifics. Ideal Storage Conditions: Indoor clean, dry, ambient temperature, well ventilated. Keep away from heat, sparks & flame. Use spark-resistant tools. Outdoor Storage: Avoid direct sunlight, store in cool well-ventilated place. Keep container closed when not in use.

Typical Properties	
Appearance.....	Clear Amber Liquid
Physical State.....	Liquid
Density, lbs./gal 65°F (18.3°C).....	6.82
pH.....	8.4
Pour Point, °F (°C).....	<-40 (<-86)
Flash Point, °F (°C).....	~23 (~-5)
Recommended Treat Rate.....	640:1

