

## RESEPI™ Hesai XT-32M2X



### RESEPI Overview

RESEPI™ (Remote Sensing Payload Instrument) is a sensor-fusion platform designed for accuracy-focused remote sensing applications. RESEPI utilizes a high-performance Inertial Labs INS (GPS-Aided Inertial Navigation System) with a tactical-grade IMU and a high-accuracy single or dual-antenna GNSS receiver, integrated with a Linux-based processing core and data-logging software. The platform also provides a WiFi interface, optional imaging module, and external cellular modem for RTCM corrections. RESEPI can be operated by a single hardware button or from a wirelessly connected device via a simple web interface.

### RESEPI WITH HESAI XT-32M2X

RESEPI with HESAI's XT-32M2X makes use of Hesai's enhanced M2X LiDAR scanner features lighter weight and extended detection over the XT-32 LiDAR. It enables an M2X-equipped RESEPI to fly longer, combined with a higher recommended AGL and wider vertical FOV to more effectively map larger areas and sites with dense vegetation cover. It is an all-around desirable system, offering the benefits of best-in-class data accuracy, better detection range, high point density, and versatility.

### Applications

The RESEPI XT-32M2X was strategically designed for multiple application bases with mounting options for mobile vehicles, DJI supported drones (DJI M300, M600 Pro), custom drones, handheld platforms, vehicles, the Freefly Alta-X, and many more. Because of this diverse mounting portfolio, the RESEPI can be used for many services including utilities mapping (power lines), construction volumetrics, site surveying, precision agriculture, forestry, mining operations, and much more.

### System

System Vertical Accuracy	2 - 3 cm <sup>(1)</sup>
Precision	2 - 4 cm <sup>(2)</sup>
Precision (1 $\sigma$ Noise Removal)	1.5 - 2.5 cm <sup>(3)</sup>
Recommended AGL	Up to 150m
Weight	1.4 kg (with camera), 1.0 kg (without camera)
Dimensions	20.8 x 16.5 x 14.2 (cm)
Max Flight Time (DJI M300)	33 minutes
External Storage	256 GB USB Included
System Computer	Quad Core, 1GB RAM, 8GB eMMC
Operational Voltage Range	9-45V
Power Consumption	17W

## About Inertial Labs

Inertial Labs is at the forefront of developing and manufacturing position and orientation technologies for the commercial sector, government, defense, and aerospace. Inertial Labs' product catalog includes Inertial Measurement Units (IMU), Inertial Navigation Systems (INS), Motion Reference Units (MRU), and Wave Sensors (WS) along with RESEPI, our LiDAR scanning and mapping package. We supply solutions for land, sea, and air to exacting customers from some of the largest organizations in the world.

Laser Range Capabilities	80m @ 10% ref. (all channels); 0.05 to 300m
Range Accuracy	+/- 1 cm
FOV (Horizontal)	360°
FOV (Vertical)	40.3°
Scan Angle (Vertical)	-20.8° to 19.5°
Beam Divergence	0.056° (H), 0.1°(V) <sup>(3)</sup>
Number of Laser	32
Number of Returns	3
Pulse Rate	640k/s (single return); 1280k/s (dual return); 1920k/s (triple return)

Model	24MP RGB Mapping Camera
Lens	Sony E-Mount 16mm, 70° FOV
Max Trigger Rate	2 seconds
External Camera Support	Yes <sup>(4)</sup>

Field Checks	Yes, Included
Pre-Processing	Yes, Included
Post-Processing	Yes, Supported

GPS-Aided Inertial Navigation System	
IMU	Inertial Labs Tactical Grade IMU-P
GNSS	Single or Dual Antenna
Constellations	GPS, GLONASS, Galileo, BeiDou, QZSS, NavIC (IRNSS), SBAS, L-Band <sup>(5)</sup>
Frequencies	L1, L2, L5 <sup>(6)</sup>
Operation Modes	RTK and PPK
Output Rates	Up to 200Hz (INS); Up to 2,000Hz (IMU)
Pitch/Roll Accuracy	0.03° (RTK); 0.006° (PPK) <sup>(7)</sup>
Heading Accuracy	0.15° (RTK); 0.03° (PPK) <sup>(8)</sup>
Velocity Accuracy	<0.03 m/s
Position Accuracy	1cm + 1ppm (RTK); 0.5cm (PPK)

<sup>(9)</sup>Dynamic accuracy is dependent on type of motion; RTK with a 1-meter baseline.

