



SECTION 10: 2018 MOWER LINE-UP

MZ Series

- Width of cut 42"
- Price point compared with similar units.
- Engine Options: 540cc single cylinder Kohler, and 725cc Kohler Pro 7000 Twin cylinder.
- Quality of construction: 7 gauge fabricated deck with a 1/4" leading edge for additional strength.
- Fully welded 11 gauge 2x2 unitized steel frame that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Hydro-Gear ZT-2200 integrated drive system comprised of two independent drive units. Each unit with an integrated high efficiency 10cc piston pump, 10cc piston motor, gear reduction, hydraulic fluid, internal expansion tank, and integrated external cog brake.
- Adjustable Ogura PTO clutch brake has plenty of torque (100ft/lbs) for smooth blade engagement and plenty of power for cutting in heavy conditions. Adjustable air gap delivers long component life.
- Taller caster bearing retainers with flat caps.
- New dial-style deck height adjustment system.
- 5 gallon fuel capacity
- Ground speed up 6 mph
- 3/8" front forks
- Rubber discharge chute
- Standard hinged floorboard with a durable rubber mat.
- Optional electric deck lift

MZ Magnum Series

- Width of Cut 48" and 54"
- Price point compared with similar units.
- Engine Options: 725cc Twin cylinder Kohler Pro 7000 series & 726cc Kawasaki FR.
- Quality of construction: 7 gauge fabricated deck with a 1/4" leading edge for additional strength.
- Fully welded 11 gauge 2x2 unitized steel frame that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Hydro-Gear ZT-2200 integrated drive system comprised of two independent drive units. Each unit with an integrated high efficiency 10cc piston pump, 10cc piston motor, gear reduction, hydraulic fluid, internal expansion tank, and integrated external cog brake.
- Adjustable Ogura PTO clutch brake has plenty of torque (100ft/lbs) for smooth blade engagement and plenty of power for cutting in heavy conditions. Adjustable air gap delivers long component life.
- New taller caster bearing retainers with flat caps.
- Manual foot pedal deck lift.
- Dial-style deck height adjustment system.
- 5 gallon fuel capacity
- Ground speed up 6 mph.
- 3/8" front forks.
- Rubber discharge chute.
- Standard hinged floorboard with a durable rubber mat.
- Optional electric deck lift.

ZT Elite Series

- Width of cut 48", 54" and 60"
- Price point compared with similar units.
- Engine Options: 725cc Kohler Pro 7000 series, New 747cc Kohler Pro 7000 engine with Premium Air Filter(54" & 60" only), and 726cc Kawasaki FR.
- Quality of construction: 7 gauge fabricated deck with a 3/8" leading edge for additional strength. Deck is 5.5" deep to allow for higher capacity mowing.
- Deck cut height up to 4.5"
- Fully welded 11 gauge 2x2 unitized steel frame that is also used on our Maverick series and Compact Outlaw series.
- Hydro-Gear ZT-3100 commercial integrated drive system comprised of two independent drive units. Each unit with a high efficiency 10cc piston pump, 16cc piston motor, heavy duty steel gears, 1.0" axle, high pressure relief, internal brake, replaceable filter and hydraulic fluid with external expansion tank.
- Adjustable Ogura clutch brake has plenty of torque (200ft/lbs) for smooth blade engagement and plenty of power for cutting in heavy conditions.
- Tall caster bearing retainers with flat caps.
- Electric deck lift system
- Optional foot assist manual deck lift capabilities.
- Dial-style deck height adjustment system.
- Large Front and Rear tires.
- 6.5 gallon fuel capacity.
- Ground speed up to 7 mph.
- 3/8" front forks.
- Rubber discharge chute

Maverick Series

- Width of cut 48", 54" and 60"
- Price point compared with similar units.
- Engine Options: 747cc Kohler Confidant Quad-Clean™ air filtration and 726cc Kawasaki FS Twin cylinder.
- Quality of construction: 7 gauge fabricated deck with a 3/8" leading edge for additional strength. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 2x2 unitized steel frame that is also used on our ZT Elite series, and Compact Outlaw series.
- Hydro-Gear ZT-3200 commercial integrated drive system comprised of two independent drive units. Each unit with a high efficiency 10cc piston pump, 16cc piston motor, heavy duty steel gears, 1.125" axle, higher output torque rating, high pressure relief, internal brake, replaceable filter and hydraulic fluid with external expansion tank.
- Warner PTO clutch brake has plenty of torque (200ft/lbs) for smooth blade engagement and plenty of power for cutting in heavy conditions.
- Quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Front & Rear EZ Ride System
- Electric deck lift system
- Optional foot-assist manual deck lift capabilities.
- Dial-style deck height adjustment system
- 6.5 gallon fuel capacity
- Ground speed up to 9 mph
- Rubber discharge chute
- New redesigned floor board equipped with a rubber floor mat for more comfort and less vibration.



Compact Outlaw Series

- Width of cut 42" & 48"
- Price point compared with similar units.
- Engine Options: 810cc Vanguard and 726cc Kawasaki FX.
- Quality of construction: 7 gauge fabricated deck with a 3/8" leading edge for additional strength. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 2x2 steel frame that is also used on our ZT Elite Series and Maverick series.
- Hydro-Gear ZT-3400 commercial integrated drive system comprised of two independent drive units. Each unit with a high efficiency 12cc piston pump, 16cc piston motor, heavy duty steel gears, 1.125" axle, higher output torque rating, high pressure relief, internal brake, replaceable filter and hydraulic fluid with external expansion tank.
- Warner PTO clutch brake has plenty of torque (200ft/lbs) for smooth blade engagement and plenty of power for cutting in heavy conditions.
- Quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Manual deck lift system
- Dial-style deck height adjustment system
- 6.5 gallon fuel capacity
- Ground speed up to 9 mph
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration

Outlaw Series

- Width of cut 54" and 61"
- Price point compared with similar units.
- Engine Options: New 852cc 24.5hp Kawasaki FX, New 824cc 27.5hp Yamaha, and 747cc Kohler Confidant with Quad-Clean™ air filtration.
- ArmorTek5: 1/4" fabricated deck with steel bars reinforcing impact areas on leading edges. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 4 rail construction with 1/4" unitized steel main frame design that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Hydro-Gear ZT-4400 heavy commercial integrated drive system comprised of two independent drive units. Each unit with high efficiency 12cc piston pump, 16cc piston motor, heavy duty steel gears, and 1.375" axle. Also includes a 9" cooling fan on each unit, replaceable filter, and 4.0 quarts of hydraulic fluid per unit. This low pressure, low temperature system prolongs the life of the hydraulic units.
- SteerTek Precision Drive with quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Patented Swing Away design.
- Manual deck lift with 19 ranges of cutting heights.
- 13.8 gallon fuel capacity
- Ground speed up 11 mph
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration.
- Comes standard with front receiving hitch and bumper set.
- Optional Front EZ-Ride system
- Optional rear hitch
- Optional suspension seat.
- Sealed bearings and flush bearing covers on front casters

Outlaw Extreme Series

- Width of cut 54" 61" and 72"
- Price point compared with similar units.
- Engine Options: 852cc Kawasaki FX and 993cc Vanguard.
- ArmorTek 5: 1/4" fabricated deck with steel bars reinforcing impact areas on leading edges. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 4 rail construction with 1/4" unitized steel main frame design that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Hydro-Gear ZT-5400 Powertrain® heavy commercial integrated drive system comprised of two independent drive units. Each unit with a high efficiency 16cc piston pump, 21cc piston motor, heavy duty planetary reduction steel gears, and 1.375" axle. Also includes a 9" cooling fan on each unit, replaceable filter, and 5.0 quarts of hydraulic fluid per unit. This low pressure, low temperature system prolongs the life of the hydraulic units.
- SteerTek Precision Drive with quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Patented Swing Away design.
- Manual deck lift with 19 ranges of cutting heights.
- 13.8 gallon fuel capacity.
- Ground speed up to 13 mph
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration.
- Comes standard with front receiving hitch and bumper set.
- Optional Front EZ-Ride system
- Optional rear hitch
- Optional suspension seat..

Outlaw XP Series

- Width of cut 54" 61" and 72"
- Price point compared with similar units.
- Engine Options: 852cc Kawasaki FX, 993cc Vanguard, 824cc Yamaha EFI.
- ArmorTek 5: 1/4" fabricated deck with steel bars reinforcing impact areas on leading edges. Deck is 5.5" deep to allow for higher capacity mowing
- Fully welded 11 gauge 4 rail construction with 1/4" unitized steel main frame design that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Two independent Hydro-Gear 12cc high efficiency piston pumps with two independent 15 cubic inch orbital wheel motors. Each pump has an integrated fan cooling each pump, dual filters and two 4-quart hydraulic fluid reservoirs. This low pressure, low temperature system prolongs the life of the hydraulic units.
- SteerTek Precision Drive with quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Patented Swing Away design.
- Electric & Manual deck lift with 19 ranges of cutting heights.
- 13.8 gallon fuel capacity.
- Ground speed up to 12 mph
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration.
- Comes standard with front receiving hitch and bumper set.
- Front and rear EZ-Ride system
- Optional rear hitch
- Optional suspension seat.



AOS Compact Diesel Series

- Width of cut 61"
- Price point compared with similar units.
- Engine Options: 1100cc (24.9hp) Liquid Cooled 3 cylinder Caterpillar diesel engine with Donaldson air filter, & 1100cc (24.9hp) Liquid Cooled 3 cylinder Perkins engine with Donaldson air filter.
- Quality of construction: 1/4" fabricated deck with steel bars reinforcing impact areas on leading edges. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 4 rail construction with 1/4" unitized steel main frame design that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Two independent Hydro-Gear 16cc high efficiency piston pumps with two independent 18 cubic inch orbital wheel motors. Each pump has an integrated fan cooling each pump, dual filters and a 10-quart hydraulic fluid reservoir. This low pressure, low temperature design prolongs the life of the hydraulic drive system.
- SteerTek Precision Drive with quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Patented Swing Away design.
- Electric & Manual deck lift with 19 ranges of cutting heights
- 18 gallon fuel capacity
- Ground speed up to 12 mph
- Comes standard with front and rear receiver hitch, bumper set and suspension seat
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration.
- Front and rear EZ-Ride system

AOS Diesel Series

- Width of cut 61" and 72"
- Price point compared with similar units.
- Engine Options: 1500cc 35 hp Liquid Cooled 4 cylinder Perkins diesel engine with Donaldson air filter
- Quality of construction: 1/4" fabricated deck with steel bars reinforcing impact areas on leading edges. Deck is 5.5" deep to allow for higher capacity mowing.
- Fully welded 11 gauge 4 rail construction with 1/4" unitized steel main frame design that is stronger than "bolt together" or stamped frame designs. This frame is built to last.
- Two independent Hydro-Gear 16cc high efficiency piston pumps with two independent 18 cubic inch orbital wheel motors. Each pump has an integrated fan cooling each pump, dual filters and a 10-quart hydraulic fluid reservoir. This low pressure, low temperature design prolongs the life of the hydraulic drive system.
- SteerTek Precision Drive with quick fit adjustable steering control arms with dual dampers for smooth precise responsiveness increase operator comfort.
- Patented Swing Away design.
- Electric deck lift system
- 18 gallon fuel capacity
- Ground speed up to 12 mph
- Comes standard with front and rear receiver hitch, bumper set and suspension seat
- Rubber discharge chute
- Rubber floor mat for more comfort and less vibration.
- Front and rear EZ-Ride system