

Sport Trucks and Mini Trucks run together as one class.

FRAME:

- 1) Any American or Foreign made Truck that was originally manufactured as rear wheel drive with 4-cylinder option and leaf springs as rear suspension. For example, Chevy S10, Ford Ranger, Dodge Ram 50, etc. (Wheel base 110" maximum)
- 2) American Passenger Car - No Convertibles - Must be Rear Wheel Drive (Wheel Base 103" Max)

CHASSIS AND ROLLAGE:

- 1) Tech may disallow any car/truck with compromised structural integrity or protruding parts that may be dangerous to others.
- 2) Any chassis used must have come with a 4-cylinder engine option from factory.
- 3) Complete 6-point center section and rear down bars must be 1 ½" minimum diameter and .095 wall thickness minimum.
- 4) No exhaust tubing, or crimped exhaust pipe bends in main cage.
- 5) Main 4 points of roll cage must be welded to frame.
- 6) No tubular frames.
- 7) Minimum of 3 door bars on driver side, must have 1/8" metal plate welded to outside of bars.
- 8) Minimum of 3 door bars on passenger side.
- 9) Must have a minimum of 3 windshield bars in front of driver.
- 10) All perimeter bars and bumper bars must be shaped with safe/rounded ends to help prevent puncturing others.
- 11) All bars on drivers side must be padded, if within reach of driver.
- 12) Must have stock front cross member.
- 13) Rocker panels may be removed and replaced with tubing, provided the front and back of tubing are sealed.
- 14) Must have front and rear firewall 18 gauge minimum.

BODY

- 1) OEM body, sheet metal, aftermarket allowed.
- 2) Rear of trucks may be left open.
- 3) 65" wide Maximum.
- 4) Hood required, must have a minimum of 4 hood pins (one per corner).
- 5) No protruding bars or sheet metal that may cause damage or injury.
- 6) May run spoiler (8" max on truck - 4" max on car) No wider than the body.
- 7) Steel or aluminum body ok. Fiberglass roof is ok.
- 8) Fabricated bodies must look like a truck or factory car body.
- 9) Truck beds must be covered.
- 10) Aftermarket nose piece are fine, but must not protrude past body sides.
- 11) No mirrors allowed.
- 12) Numbers must be on both sides and top, must be large enough to see from the booth.

WEIGHT

- 1) 2200lb minimum with driver.
- 2) Any added weight must be securely mounted with 2 bolts minimum.
- 3) All weight must be painted white and marked with driver's number.
- 4) No bolt on weight in driver's compartment.

BUMPERS

- 1) 2" OD maximum, .095 maximum tube size.
- 2) No overbuilt type bumpers "Battering Rams" - No hang-up type ends, may loop back to frame.
- 3) Bumpers cannot extend outside of tires.
- 4) Must have one loop of chains on front and rear bumper for towing.
- 5) Front and rear bumpers required.
- 6) Front Bumpers: Minimum 36" wide, May have bar to protect radiator, must be behind nose piece.
- 7) Rear Bumpers: May weld one 8" tall loop on top of bumper, no wider than the center of tires., Must extend 1" below fuel cell. No sharp or cornered ends, Ends must loop back towards frame.