



2024 Cruiser Rules

GENERAL RULES

- 1) If you want to go fast, move up a class!
- 2) This is considered an entry level division.
- 3) Numbers must be clearly visible on both sides and roof

BODY & FRAME

- 1) 108" Minimum Wheelbase
- 2) Full OEM frames from center of rear end forward
- 3) Steel or aluminum body
- 4) No Mirrors
- 5) No ballasts
- 6) No Tube or Jig Frames
- 7) Rear Wheel Drive - No Convertibles
- 8) Stock Frame - Front to Rear except one upright loop between bumper and radiator
- 9) Bumpers must remain OEM - No Reinforcement other than welded to frame - ends must be welded to body with plates
- 10) Mandatory to have one loop of chain on both bumpers for tow hook

ROLL BARS

- 1) 6-point steel cage mandatory
- 2) 1½" diameter .095 wall thickness
- 3) May pass through firewalls
- 4) 3 bars in driver's door
- 5) No galvanized or exhaust tubing allowed
- 6) Approved padding must be used where driver/passenger contact can occur
- 7) Must have at least one cross bar in roof halo
- 8) 3 bars minimum in front of drivers

FUEL SYSTEM

- 1) Fuel cells mandatory - Must be securely mounted, two strap minimum.
- 2) Plastic tanks must be encased by metal.
- 3) Rollover valve required on fuel cells, Period.
- 4) Electric fuel pumps allowed. *Recommended: Wired through an oil pressure switch (10psi).*
- 5) Gasoline only, no alcohol or methanol.

SAFETY EQUIPMENT:

- 1) 2010 Minimum Snell-rated SA2010, SA2015 or SA2020 helmet required.
- 2) Roll bar padding required in driver compartment. *Recommended: Fire retardant padding.*
- 3) SFI-approved full fire suit required - Fire retardant gloves and neck brace (or head and neck restraint) required.
- 4) Right side seat head supports required, if not using head and neck restraint system.
- 5) Driver Side and Passenger Side window net required
- 6) Minimum two inch wide SFI-approved five point safety belt assembly required, must be mounted securely to main roll cage.
- 7) Leather Boots are OK - No tennis Shoes - *Recommended to have fire resistant race shoes*
- 8) Raceceiver is Required.



2024 Cruiser Rules

ENGINE

- 1) Maximum Compression level of 9 to 1
- 2) No Headers, Stock exhaust manifolds
- 3) No rollers (rocker arms or lifters)
- 4) OEM block only
- 5) No crankshaft work of any kind
- 6) Engine must be in original position
- 7) Rotary or turbo engines are not permitted
- 8) 2 Barrel Carburetor only

ELECTRICAL SYSTEM

- 1) Stock ignition only
- 2) OEM-HEI or OEM point distributor with 1 stock coil
- 3) 12 volt battery
- 4) We reserve the right to pull a plug wire before the start of any race.

STEERING

- 1) Steering column and steering box must remain OEM
- 2) Steering box must be in stock location
- 3) Quick release style OK
- 4) Steering wheel operation by left driver only

SUSPENSION

- 1) Stock - No Alterations
- 2) OEM shocks/springs only - OEM mounts
- 3) No racing shocks or springs allowed

REAREND / TRANSMISSION

- 1) Stock OEM rear-ends only; Locked ok
- 2) No floaters
- 2) OEM transmission only
- 3) Must have all working gears
- 4) Automatics must have working torque converter
- 5) Drive shaft must be painted white with car number on it
- 6) Drive shaft must have a safety loop around it, behind front U-Joint

Wheels / Tires / Brakes:

- 1) Max 8" wide steel wheels
- 2) No Bead Locks
- 3) No wheel spacers allowed
- 4) 1" lug nuts required for all wheels
- 5) Hoosier / American Racers OK - any DOT tire max 255/60/15 - no mud or snow tread
- 6) All brake components must be OEM in OEM locations - no alterations on brakes
- 7) All 4 wheels must stop - no brake bias
- 8) Brake pedal must be operated by left side driver only