


Industrial Safety Controls, Inc.

1706 - 22nd Avenue, Kenosha, WI 53140

Phone: 262.652.8660

 Email: safetysensing@earthlink.net

 Website: www.safeworkplace.org

FLAT CHROME PLUNGER PUSH BUTTON SWITCHES





Features/Applications

The following switches are hand operated, control circuit devices, rated 'Heavy Duty' normally for use with electromagnetic equipment. The cover, painted with a dry powder paint, and the chrome plated/painted plunger are made from die-cast zinc. Each captive terminal will accept (2) #14 AWG stranded wires and the contacts are gold plated to eliminate high resistance tarnishing. Each switch is supplied with all mounting hardware and a solid santoprene rubber gasket which

[+ more](#)


1

Item #	Item Photo	Plunger Color	Operating Force	Positive Opening Contact	Contact Arrangements (All Momentary)
02653-012	 02653-012	2.25" dia. Chrome	5.5 lb	Yes 	#09 NO + NC Positive Break, Slow-Make
02653-112		2.25" dia. Chrome	2.5 lb	Yes 	#09 NO + NC Positive Break,

Item #	Item Photo	Plunger Color	Operating Force	Positive Opening Contact	Contact Arrangements (All Momentary)
		Chrome			Slow-Make
	02653-112				
03727-012		2.25" dia. Chrome	3.3 lb	No	#10 NO + NO, Slow-Make
	03727-012				
04917-012		2.25" dia. Chrome	3.7 lb	No	#64 2 NO + 2 NC, Snap-Action
	04917-012				
04917-312		2.75" dia. Chrome	3.7 lb	No	#64 2 NO + 2 NC, Snap-Action
	04917-312				
04957-001		2.75" dia. Black	1.9 lb	No	#64 2 NO + 2 NC, Snap-Action
	04957-001				
04957-003		2.75" dia. Green	1.9 lb	No	#64 2 NO + 2 NC, Snap-Action
	04957-003				
04957-012		2.75" dia. Chrome	1.9 lb	No	#64 2 NO + 2 NC, Snap-Action
	04957-012				

