


Industrial Safety Controls, Inc.

1706 - 22nd Avenue, Kenosha, WI 53140

Phone: 262.652.8660

 Email: safetysensing@earthlink.net

 Website: www.safeworkplace.org


ROPE OPERATED SEQUENCE SWITCHES



Features/Applications

These switches are “slack cable” style with ‘Slow-Make’ contacts. The switches are not ‘Positive Transfer’ and they do not latch in any position. They should NOT be used for any Emergency Stop applications. The action of these devices is that when the switch actuating arm is pulled by a cable the switch contacts will change state, that is, the NO will be closed and the NC will go open. When the force on the cable is removed from the actuator arm, spring pressure will return

[+ more](#)


1

Item #	Item Photo	Trip Force	Operating Force Between 10 ft. Supports	Reset Type	Contact Arrangement
04945-000	 04945-000	10 lb	1.2 lb	Manual	NO + NC
04945-100		10 lb	1.2 lb	Manual	2 NO
04945-200		10 lb	1.2 lb	Manual	2 NO + 2 NC

Item #	Item Photo	Trip Force	Operating Force Between 10 ft. Supports	Reset Type	Contact Arrangement
04945-500	 <p>04945-500</p>	10 lb	1.2 lb	Manual	NO + NC
04945-800	 <p>04945-800</p>	10 lb	1.2 lb	Manual	NO + NC (make - before - break)
					1