

# PETRONAS HYDRAULIC FR SERIES

## Premium Performance Synthetic Fire Resistant Hydraulic Fluid

PETRONAS Hydraulic FR Series are premium performance, fire resistant, anti-wear hydraulic fluids specially developed for industrial hydraulic equipment operating under normal to heavy duty conditions, recommended whenever a major fire hazard exists associated with industrial hydraulic systems.

Formulated with high viscosity index synthetic base oil enhanced with advanced anti-wear, anti-oxidant, anti-rust and anti-foam additives, PETRONAS Hydraulic FR fluids provide high anti-wear protection, smooth operation of the hydraulic systems and contribute to mitigate the risks of violent explosions or fire in the immediate vicinity of flames or hot metal surfaces.

### Applications

PETRONAS Hydraulic FR Series are recommended for use in:

- various industrial and mobile hydraulic systems operating under high temperatures where a major fire hazard exists such as steel mills, blast furnaces, continuous casting machine and coke plants

Note: PETRONAS Hydraulic FR Series can only be mixed with phosphate ester based hydraulic fluids.

### Features and Benefits

Features	Benefits
Excellent Fire resistance / High temperature applications	Reduces risk of fire in high temperature and close to open flame applications, which can ensure safer working environment
High Viscosity Index	Ensures superior performance and protection over a wide temperature range
High anti-wear protection	Protects equipment components from excessive wear and provides long equipment life
Very good thermal and oxidation stability	Maintains performance levels under high temperatures and pressure, in specific application where this type of product is recommended
High rust & corrosion protection	Inhibits the corrosion process that occurs in presence of water, improving equipment life
Very good water separability	Due to good water separability the system is protected from water degenerative effects, maintaining hydraulic system efficiency at required level and reducing maintenance costs
Very good air release	Maintains good efficiency in hydraulic systems, ensures smooth operation due to fast air release. Protects the system from air degenerative effects reducing maintenance costs

# PETRONAS HYDRAULIC FR SERIES

## Premium Performance Synthetic Fire Resistant Hydraulic Fluid

Features	Benefits
High multi metal compatibility	Compatible with most metal alloys ensuring trouble free performance of the system

### Typical Properties

Characteristic	Method	Specification	46	68
Specific Gravity @15°C	ASTM D 4052	(1)	0,926	0,934
Kinematic Viscosity at 40 °C, cSt	ASTM D 445	±10%	46	68
Kinematic Viscosity at 100 °C, cSt	ASTM D 445	(1)	8,8	12,0
Viscosity Index	ASTM D 2270	(1)	174	175
Flash Point, °C	ASTM D 92	(1)	300	300
Manifold Ignition test, °C	ISO 20823	(1)	450	450
Pour Point, °C	ASTM D 97	(1)	-30	-27
TAN, mgKOH/g	ASTM D 974	Report	0,70	0,70
Water Separability, 40/37/3 - mins	ASTM D 1401	(1)	30	30
Copper Strip Corrosion	ASTM D 130	Report	1a	1a
Foam Sequence I, mL	ASTM D 892	Max. 300/10	30/0	30/0
Foam Sequence II, mL		Max. 300/10	0/0	0/0
Foam Sequence III, mL		Max. 300/10	30/0	30/0
Dry Tost, hours	ASTM D 943	(1)	850	850
Air Release, min	ASTM D 3427	**	10	15
Corrosion Protection	ISO 4404-2	Max. 3	Pass	Pass
RPVOT, min	ASTM 2272	(1)	290	185

All technical data is provided for reference only and all specification based on ISO 12922

\*\*Individual limits accordingly with each viscosity grade / (1): not required in specification / SS is available upon request including quality control limits

### Performance Levels

- Factory Mutual Approval
- HFD Fluid

# PETRONAS HYDRAULIC FR SERIES

## Premium Performance Synthetic Fire Resistant Hydraulic Fluid

### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

### Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.