

PETRONAS HYDRAULIC HV SERIES

Premium High Viscosity Index Anti-wear Hydraulic Fluids

PETRONAS Hydraulic HV Series are premium performance anti-wear hydraulic fluids specially developed for a wide range of mobile and industrial hydraulic equipment operating under normal to heavy duty conditions, subjected to high variations in operating and/or ambient temperatures, including cold start-ups.

Formulated with high quality selected base oils enhanced with high shear stable VI improver and advanced anti-wear, anti-oxidant, anti-rust and anti-foam additives, PETRONAS Hydraulic HV fluids provide high anti-wear protection, more stable performance across wide temperature range as compared to normal viscosity index products and over 3x longer lasting performance*.

PETRONAS Hydraulic HV Series meet or exceed key industrial specifications and OEM requirements.

*vs. minimum requirements of ISO 11158 HV for anti-wear hydraulic fluids based on TOST (ASTM D943)

Applications

PETRONAS Hydraulic HV Series are recommended for use in:

- various mobile and industrial hydraulic systems operating under normal to heavy duty conditions that demand good control of fluid viscosity during operating cycle
- hydraulic systems subjected to high and/or rapid variations in operating and/or ambient temperatures
- outdoor hydraulic systems operating in cold climates, where high protection is required in subzero temperatures and cold start-ups are frequently encountered
- hydraulic systems where high precision and stable efficiency of the system is required (e.g. moulding machines)

PETRONAS HYDRAULIC HV SERIES

Premium High Viscosity Index Anti-wear Hydraulic Fluids

Features and Benefits

Features	Benefits
High Viscosity Index	Ensures superior performance and protection over a wide temperature range
Low temperature protection	Ensures proper protection of equipment components during cold starts
High anti-wear protection	Protects equipment components from excessive wear and provides long equipment life
High wet and dry filterability	Maintains high filter efficiency without giving rise to undue pressure drop, thus increasing filter lifetime
High thermal and oxidation stability	Maintains performance levels under high temperatures and pressure, enabling long oil drain intervals
High rust & corrosion protection	Inhibits the corrosion process that occurs in presence of water, improving equipment life
High water separability	Due to good water separability the system is protected from water degenerative effects, maintaining hydraulic system efficiency at required level and reducing maintenance costs
High air release and foam stability	Maintains high efficiency in hydraulic systems, ensures smooth operation due to fast air release. Protects the system from air degenerative effects reducing maintenance costs
High multi metal compatibility	Compatible with most metal alloys ensuring trouble free performance of the system
High compatibility with most seal and elastomers	Compatible with most seals and elastomers, which prevents oil leaks and contamination due to seal erosion

PETRONAS HYDRAULIC HV SERIES

Premium High Viscosity Index Anti-wear Hydraulic Fluids

Typical Properties

Characteristic	Method	Specification	32	46	68
Specific Gravity @15°C	ASTM D 4052	(1)	0,873	0,877	0,880
Kinematic Viscosity at 40°C, cSt	ASTM D 445	±10%	32	46	68
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	6,2	7,9	10,5
Viscosity Index	ASTM D 2270	Min. 140	146	143	142
Flash Point, °C	ASTM D 92	**	220	220	230
Pour Point, °C	ASTM D 97	**	-33	-33	-30
TAN, mgKOH/g	ASTM D 664	(1)	0,60	0,60	0,60
FZG, Stages Passed	ISO 14635-1	Min. 10	12	12	12
Water Separability, 40/37/3 - mins	ASTM D 1401	**	15	15	15
Copper Strip Corrosion	ASTM D 130	Max. 2	1b	1b	1b
TOST life, hours	ASTM D 943	Min. 1000	3500	3500	3500
Foam Sequence I, mL	ASTM D 892	Max. 150/0	0/0	0/0	0/0
Foam Sequence II, mL		Max. 75/0	0/0	0/0	0/0
Foam Sequence III, mL		Max. 150/0	0/0	0/0	0/0
Characteristic	Method	Specification	100	150	
Density @ 15 °C, kg/m ³	ASTM D 4052	(1)	0,877	0,884	
Kinematic Viscosity at 40°C, cSt	ASTM D 445	±10%	100	150	
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	14,2	18,7	
Viscosity Index	ASTM D 2270	Min. 140	145	141	
Flash Point, °C	ASTM D 92	**	240	240	
Pour Point, °C	ASTM D 97	**	-27	-27	
TAN, mgKOH/g	ASTM D 664	(1)	0,60	0,60	
FZG, Stages Passed	ISO 14635-1	Min. 10	12	12	
Water Separability, 40/37/3 - mins	ASTM D 1401	**	20	20	
Copper Strip Corrosion	ASTM D 130	Max. 2	1b	1b	
TOST life, hours	ASTM D 943	Min. 1000	3500	3500	
Foam Sequence I, mL	ASTM D 892	Max. 150/0	0/0	0/0	
Foam Sequence II, mL		Max. 75/0	0/0	0/0	
Foam Sequence III, mL		Max. 150/0	0/0	0/0	

All technical data is provided for reference only and all specification based on DIN 51524-3 (2006) and ISO 11158 HV (FDIS 2008)

**Individual limits accordingly with each viscosity grade / (1): not required in specification / SS is available upon request including quality control limits

www.pli-petronas.com

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.

PETRONAS HYDRAULIC HV SERIES

Premium High Viscosity Index Anti-wear Hydraulic Fluids

Performance Levels

- ASTM D 6158 HV
- Bosch Rexroth RD90220
- DIN 51524 Part II HLP and III HVLP (2006)
- Eaton 03-401-2010
- Fives Cincinnati P-68/P-69/P-70
- GM LS-2 (2004)
- ISO 11158 HV (FDIS 2008)
- JCMAS HK P041 (2004)
- Parker Denison HF-0 / HF-1 / HF-2
- SAE MS1004
- SEB 181 222 (2007)
- U.S. Steel 126, 127 and 136

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.