

EDGE DEVICES - WIRELESS SENSORS

LaserTilt90

LS-G6-LAS-TIL90



Worldsensing LaserTilt90 is a 2-in-1 laser distance meter and tiltmeter. The laser measures the relative distance to a reference point that can be either natural surfaces or target foils. Meanwhile, the tiltmeter provides measurements of changes from the vertical level, either on the ground or in structures. This 2-in-1 wireless sensor is designed to provide robust data when monitoring inclinations, movements and differential settlements of slopes or infrastructures.

The LaserTilt90 can be easily located along the convergence cross sections up to the excavation front or until the measured relative displacements are stabilized when the required frequency of measurements is reduced.

FEATURES

- 2-in-1 Laser Meter + tiltmeter
- 3-axis inclination with respect to gravity's direction and a range of $\pm 90^\circ$
- Accurate distance measurement through a visible Laser Class II with 655 nm.
- Internal temperature (accuracy: $\pm 1^\circ\text{C}$), signal strength and gain collected and transmitted at each reading.
- Robust, compact design and IP68 grade weather-proof box.
- Long battery life (>10 years @1h sampling rate).
- Long range communications through LoRa communications.

SOFTWARE

- User-friendly Android configuration app included.
- Web browser software for network, device and data management.
- Single-gateway network setup with CMT Edge software (dataserver and radio server hosted in the gateway and data access through standard CSV downloads, FTP push, Modbus TCP, API REST and MQTT¹).
- Multi-gateway network setup with CMT Cloud software and advanced features with data access via standard CSV downloads, FTP push, API REST and MQTT push¹.

¹ MQTT available upon request.

It can also be used when permanent monitoring is required. The wireless sensor can also measure deformations in underground excavations and mining without causing work disruptions and delays.

Long-range and low-power

The LaserTilt90 is capable of transmitting data via long-range radio to a gateway connected to the Internet up to 9 miles/ 15 km. away. One gateway can also support dozens of data loggers in the same network, depending on the reporting period, through a star or tree network topology.

In terms of energy consumption, Worldsensing LaserTilt90 is an autonomous battery-powered device with C-size batteries that can last up to 10 years with minimal to zero maintenance required. It is IP68 certified and operating temperature from -20°C to 60°C .

APPLICATIONS

STRUCTURAL HEALTH

- Convergence monitoring for tunnels, shafts and galleries.
- Static deflections of piles, piers and decks of bridges and other structures

GEOTECHNICAL MONITORING

- Slope movements in landslides, embankments
- Ground movements in underground excavations

ADVANTAGES

- Suitable for unattended, large scale projects
- Very low maintenance equipment due to its robustness and low-power consumption.
- Provides complementary data for existing geospatial monitoring when high precision and robustness is needed.
- Easy configuration through the Worldsensing mobile application
- Customer support from a expert team of geotechnical monitoring
- Pioneer company in the field, long history in monitoring large-scale civil infrastructure



TECHNICAL SPECIFICATIONS

GENERAL

Sensor type	2-in-1 Laser Distance Meter + Tiltmeter
Reporting Period	Selectable from: 30 s 1, 2, 5, 10, 15, 30 min 1, 2, 4, 6, 12, 24 h
Time synchronization discipline by radio	Better than ± 30 seconds
Battery type	2 x 3.6V C-Size user-replaceable, high energy density batteries
Interfaces	Internal mini USB
Device configuration	Worldsensing App
App advanced functionalities	<ul style="list-style-type: none"> Laser pointing mode. Tiltmeter calibration parameters check using the app. Radio signal coverage tests for easy installation.

LASER DISTANCE METER

Sensor	Visible Laser Class II with 655 nm.	
Laser power	0.75 to 0.95 mW	
Resolution	0.1 mm	
Repeatability (±σ) ⁴	0.15 mm	
Measuring range at favorable conditions	0.05 to 150 m	
Typical measuring accuracy	±1 mm	
Time required for a reading	Up to 4 seconds, depending on distance.	
Accuracy f(d)		
Distance (d)	Under Favorable Conditions ²	Under Unfavorable Conditions ³
1 m	±1 mm	±2 mm
10 m	±1 mm	±2 mm
20 m	±1.5 mm	±3 mm
50 m	±4 mm	±7 mm
100 m	±9 mm	±15 mm
150 m	±16 mm	Not Applicable
Signal strength	Signal strength and gain are transmitted with each laser measurement. It can be used for maintenance purposes.	

TILTMETER

Sensor	3-axis MEMS accelerometer
Range ⁵	$\pm 90^\circ$
Axes	3-axis inclination measurement with respect to gravity's direction. Reports the two axes of rotation from the horizontal plane in any orientation
Resolution	0.0001°
Repeatability	$< 0.0003^\circ$
Time required for a reading	Up to 4 seconds, depending on distance.
Accuracy $f(\alpha)$	
Angle (α)	Accuracy
$\pm 2^\circ$	$\pm 0.0025^\circ$
$\pm 4^\circ$	$\pm 0.005^\circ$
$\pm 15^\circ$	$\pm 0.013^\circ$
$\pm 45^\circ$	$\pm 0.08^\circ$
$\pm 85^\circ$	$\pm 0.23^\circ$
Offset Temperature dependency	$\pm 0.002^\circ/\text{°C}$
Stability @ 14 h	$< 0.003^\circ$
Time required for a reading	9.6 s
Measure of dispersion	Standard deviation of the set of measurements collected during the reading and transmitted with each tilt measurement. It can be used to filter noisy data.
Temperature sensor resolution	0.1 °C

⁵ The recommended measuring range is $\pm 85^\circ$. Outside of this range, the margin of error increases. However, when one of the axes is close to 90° , the other axis will be close to 0° and measuring the same inclination.

² On natural objects. Low target illumination ($< 3\text{K lx}$), moderate temperatures.

³ On natural objects. High target illumination (3K lx), full specified operating temperature range.

⁴ Under favorable conditions and distances up to 10m.



MECHANICAL	
Box dimensions (WxLxH)	100x100x61 mm.
Overall dimensions	150x120x61 mm (excluding antenna).
Operating temperature ⁶	-20°C to 60°C
Storage temperature	-25°C to + 70°C
Weather protection	IP68 (at 2 m for 2 hours)
Weight (excluding batteries)	841 g
External Antenna	100 mm length (including connector)
Mounting options	<ul style="list-style-type: none"> • Clearance holes for M4 hexagon socket head cap screws in bottom. • Blind holes for M5 screws on the lateral side.
External Port	Mini USB port for configuration and data access; can also be used to power the node
Box material	Aluminium alloy
Batteries	1 to 2
Vibration resistance	ISO 9022-3 compliant. Method 36, Severity 05 (0.15mm, 10Hz..55Hz)
MEMORY	
Memory Structure	Circular Buffer
Maximum Memory Records	100 000 readings including time, distance and 3 axis tiltmeter measurements.

RADIO SPECIFICATIONS

Radio band	ISM sub 1GHz
Operating frequency bands	Adjustable
Bidirectional communications	Remote sampling rate change / Clock synchronization
Maximum link budget	151 dB / 157 dB
Configuration	LoRa Star/ LoRa Tree
Radio range ⁷	
Range open field	15 km
Range city street	4 km
Range manhole in a city street	2 km
Tunnel	4 km

BATTERY LIFE ESTIMATIONS⁸

Distance		25 m	65 m
Reporting Period	5 min	6 months	1.8 years
	1 h	5.1 years	10.2 years
	6h	12 years	14.3 years

⁶ Temperature range applicable to devices with serial numbers greater than 109401. Otherwise, the operating temperature range is -10°C to 50°C.

⁷ The distances have been tested by Worldsensing and have been accomplished in actual projects using the standard antenna. However, radio range depends on the environment so these distances are only indicative. Consult with us for your application.

⁸ Typical Europe radio configuration. Spreading factor 9, radio transmit power 14dBm. Considering laboratory conditions. Consumption varies depending on the sensor used, sampling rate and environmental and wireless network conditions.

Battery life estimations using recommended Saft batteries LSH14, based on the lifetime mathematical model using Barcelona weather profile. Average values provided.




Fig. 1: Different applications for the LaserTil90. (a) convergence monitoring in tunnels and galleries, (b) convergence monitoring in construction shaft, (c) crack monitoring in open pit mines and rock slopes.

ACCESSORIES

LS-ACC-CELL-1C	Saft LSH 14 C-size spiral cell (5.8Ah).
LS-ACC-IN15-VP ⁷	Mounting plate for vertical mounting; attachment option: anchor rods.
LS-ACC-IN15-HP ⁷	Versatile plate for horizontal surface mounting; attachment option: anchor rods or glue; includes a threaded hole available for installing a monitoring prism or a button head screw for precise levelling.
LS-ACC-LAS-AP	Adjustable mounting plate for vertical surface; attachment option: anchor rods. This support allows limited rotation in two axis with respect to the reference surface. This support is proper for fine aiming of the laser beam.
LS-ACC-LAS-SB ⁸	Swivel mounting bracket; attachment option: pole fixing 50 mm U-bolts, anchor rods or on a convergence bolt with G 3/8" male thread. The swivel mounting bracket allows swivelling around the vertical axis (+/- 90°) and a minor rotation of the enclosure on the plate (+/- 3°).
WS-ACC-LAS-NSB ⁸	Swivel mounting bracket; attachment option: pole fixing 50 mm U-bolts and anchor rods. The swivel mounting bracket allows swiveling around the vertical axis (+/- 90°) and a minor rotation of the enclosure on the plate (+/- 3°).
LS-ACC-ANC-H ⁹	Kit of 3 anchor rods for injection. M8, 110 mm Length, nuts and washers included.
LS-ACC-MAG ¹⁰	Kit of 3 magnets, Ø 32 mm, strength approx. 30 kg, screws included.
WS-ACC-LAS-TG	Laser target rotatable and swivelable 360° compatible with convergence bolt G 3/8" male thread, M8 anchor rods and M5 magnets.



Fig. 2: Inside view of the LaserTilt90.

7 The laser beam cannot be aimed using this mounting plate because the node is fixed.

8 The swivel mounting bracket allows swivelling and rotation but these degrees of freedom, even if the bracket is fixed in place with screws or fasteners, can adversely affect the inclination measurement specifications of the whole system.

9 The kit can be used to fix the following mounting kits: LS-ACC-IN15-HP, LS-ACC-IN15-VP, LS-ACC-LAS-AP, LS-ACC-LAS-SB.

10 The kit of 3 magnets can be used to fix the LS-ACC-IN15-VP mounting plate.



Fig. 3: LaserTilt90 mounted on a swivel mounting bracket WS-ACC-LAS-NSB on a vertical surface.


Fig. 4: LaserTilt90 mounted on a swivel mounting bracket WS-ACC-LAS-NSB on a horizontal surface.



Fig. 5: LaserTilt90 mounted on a swivel mounting bracket LS-ACC-LAS-SB that includes the attachment option of a convergence bolt with a G3/8" male thread.



Fig. 6: Laser target WS-ACC-LAS-TG. Recommended to increase laser readings accuracy when beam points the surface in an oblique angle.



FOR MORE INFORMATION
Scan to access the edge device user guide



GENERAL DISCLAIMER:

Specifications are subject to change without notice and should not be construed as a commitment by Worldsensing. Worldsensing assumes no responsibility for any errors that may appear in this document. In no event shall Worldsensing be liable for incidental or consequential damages arising from the use of this document or the systems described in this document.

All Content published or distributed by Worldsensing is made available for the purposes of general information. You are not permitted to publish our content or make any commercial use of our content without our express written consent. This material or any portion of this material may not be reproduced, duplicated, copied, sold, resold, edited, or modified without our express written content.

v.20240704