

DAEWOO PRODUCTS USE EXPLAINED

Engine Oil



DAEWOO 4T
SAE 20W50-20W40-10W40
API SN JASO MA 2 - API SL JASO MA 2



DAEWOO 4T
SAE 20W50-20W40
API SG JASO MA 1

Engine Oil



DAEWOO 4T
SAE 10W40
API SL JASO MB



Brake Fluid

DAEWOO Brake Fluid
DOT 3
DOT 4



Coolant

DAEWOO Coolant
33%



Gear Oil

DAEWOO TFX
SAE 80W90
API GL-5



Deawoo Fast **4T** SAE 5W40 API SN, JASO MA2

API SN; JASO MA2



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.855
Viscosity @ 100°C, cSt	ASTM D445	13.6
Viscosity @ 40°C, cSt	ASTM D445	79.6
Viscosity Index	ASTM D2270	175
Pour Point, °C	ASTM D97	-36
Flash Point, °C	ASTM D92	226
Total Base Number (TBN), KOH/g	ASTM D2896	8.4

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Speed **4T** SAE 10W60 API SN, JASO MA2

API SN; JASO MA2



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.860
Viscosity @ 100°C, cSt	ASTM D445	24.0
Viscosity @ 40°C, cSt	ASTM D445	156
Viscosity Index	ASTM D2270	185
Pour Point, °C	ASTM D97	-33
Flash Point, °C	ASTM D92	236
Total Base Number (TBN), KOH/g	ASTM D2896	8.0

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Race **4T** SAE 10W40 API SN, JASO MA2

API SN; JASO MA2



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.871
Viscosity @ 100°C, cSt	ASTM D445	13.82
Viscosity @ 40°C, cSt	ASTM D445	89.9
Viscosity Index	ASTM D2270	155
Pour Point, °C	ASTM D97	-33
Flash Point, °C	ASTM D92	236
Total Base Number (TBN), KOH/g	ASTM D2896	7.5

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Race **4T** SAE 20W40/50 API SL, JASO MA2

API SL; JASO MA2



TYPICAL PROPERTIES

		20W40	20W50
Density @ 15°C, kg/l	ASTM D1298	0.880	0.880
Viscosity @ 100°C, cSt	ASTM D445	15.0	18.5
Viscosity @ 40°C, cSt	ASTM D445	122	160
Viscosity Index	ASTM D2270	126	126
Pour Point, °C	ASTM D97	-30	-30
Flash Point, °C	ASTM D92	230	230
Total Base Number (TBN), KOH/g	ASTM D2896	7.5	7.5

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Eco **4T** SAE 20W40 API SG JASO MA1

API SG; JASO MA / MA1



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	14.0
Viscosity @ 40°C, cSt	ASTM D445	100
Viscosity Index	ASTM D2270	142
Pour Point, °C	ASTM D97	-30
Flash Point, °C	ASTM D92	230
Total Base Number (TBN), KOH/g	ASTM D2896	7.0

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Eco **4T** SAE 20W50 API SG JASO MA1

API SG; JASO MA / MA1



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	18.5
Viscosity @ 40°C, cSt	ASTM D445	160
Viscosity Index	ASTM D2270	126
Pour Point, °C	ASTM D97	-25
Flash Point, °C	ASTM D92	230
Total Base Number (TBN), KOH/g	ASTM D2896	7.0

AVAILABLE PACKS

1L, 208L, Bulk

Deawoo Race **4T HD** SAE 10W30/40 API SL, JASO MB

API SL / SJ / SH / SG; JASO MB



TYPICAL PROPERTIES

		10W30	10W40
Density @ 15°C, kg/l	ASTM D1298	0.880	0.880
Viscosity @ 100°C, cSt	ASTM D445	10.50	13.80
Viscosity @ 40°C, cSt	ASTM D445	69.0	90.0
Viscosity Index	ASTM D2270	140	155
Pour Point, °C	ASTM D97	-30	-30
Flash Point, °C	ASTM D92	230	225
Total Base Number (TBN), KOH/g	ASTM D2896	7.5	7.5

AVAILABLE PACKS

1L, 208L, Bulk



Daewoo Lina **2T** SAE 30 API TC, JASO FC

API TC; JASO FC

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.871
Viscosity @ 100°C, cSt	ASTM D445	13.8
Viscosity @ 40°C, cSt	ASTM D445	89.9
Viscosity Index	ASTM D2270	155
Pour Point, °C	ASTM D97	-33
Flash Point, °C	ASTM D92	226
Total Base Number (TBN), KOH/g	ASTM D2896	N/A

AVAILABLE PACKS

1L, 208L, Bulk



Daewoo Lina **2T** Outboard NMMA API TC-W3

API TC-W3; NMMA

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	8.3
Viscosity @ 40°C, cSt	ASTM D445	53
Viscosity Index	ASTM D2270	160
Pour Point, °C	ASTM D97	-35
Flash Point, °C	ASTM D92	230
Total Base Number (TBN), KOH/g	ASTM D2896	N/A

AVAILABLE PACKS

1L, 208L, Bulk