



Automatic Transmission Fluids



Daewoo ATF VI

Meets the requirements of General Motors' DEXRON-VI

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.860
Viscosity @ 100°C, cSt	ASTM D445	5.83
Viscosity @ 40°C, cSt	ASTM D445	29
Viscosity Index	ASTM D2270	145
Brookfield Viscosity @-40 °C, cP	ASTM D2983	11,500
Pour Point, °C	ASTM D97	-45
Flash Point, °C	ASTM D92	220

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk



Daewoo ATF III

Meets the requirements of GM DEXRON III H

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.860
Viscosity @ 100°C, cSt	ASTM D445	7.5
Viscosity @ 40°C, cSt	ASTM D445	34
Viscosity Index	ASTM D2270	199
Brookfield Viscosity @-40 °C, cP	ASTM D2983	<20,000
Pour Point, °C	ASTM D97	-42
Flash Point, °C	ASTM D92	>185

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk



Daewoo ATF II-D

Meets the requirements of GM DEXRON II D

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.870
Viscosity @ 100°C, cSt	ASTM D445	7.0
Viscosity @ 40°C, cSt	ASTM D445	37
Viscosity Index	ASTM D2270	≥160
Brookfield Viscosity @-40 °C, cP	ASTM D2983	<50,000
Pour Point, °C	ASTM D97	-44
Flash Point, °C	ASTM D92	210

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk



Daewoo ATF TYPE A Suffix A

Meets the requirements of General Motors type A Suffix A.

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.863
Viscosity @ 100°C, cSt	ASTM D445	7.5
Viscosity @ 40°C, cSt	ASTM D445	35.2
Viscosity Index	ASTM D2270	≥ 160
Brookfield Viscosity @-40 °C, cP	ASTM D2983	<50,000
Pour Point, °C	ASTM D97	-42
Flash Point, °C	ASTM D92	>185

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk



Transmission Fluids and Gear Oils



Daewoo ATF FS

Meets and exceeds: AISIN WARNER; BMW 4 and 5 speed European; CHRYSLER ATF +3/4; MAN 339; Type Z-1; MB 4 and 5 speed European; TOYOTA T-III/T-IV/WS Lifetime; VOITH ATs 556335; VW 4 and 5 speed European

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	846
Viscosity @ 100°C, cSt	ASTM D445	7.05
Viscosity @ 40°C, cSt	ASTM D445	34,5
Viscosity Index	ASTM D2270	172
Brookfield Viscosity @ -40 °C cP	ASTM D2983	13,100
Pour Point, °C	ASTM D97	-45
Flash Point, °C	ASTM D92	216

AVAILABLE PACKS

1L, 208L, Bulk



Daewoo RDA

Meets and exceeds: BMW Mini Cooper EZL 799; Dodge/Jeep NS-2, CVT+4; Ford CVT23, CVT30/Motorcraft XT-7-QCFT, Mercon C; GM/Saturn DEX-CVT; Honda HMMF, HCF-2; Hyundai/Kia CVT applications (SP-CVT I); Mazda CVT 3320; Mercedes Benz 23620; Mitsubishi CVT-FJ, CVT-FJ4; Nissan NS-2, NS-3; Shell Green IV/Subaru Lineartronic CVT (P/N K0425Y0710), CV-30, High Torque CVT, e-CVT; Suzuki TC, NS-2, CVT 3320, CVT Green I, CVT Green 2; Toyota TC, FE; Volkswagen/Audi TL 52180, G 052 180, G 052 516

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.848
Viscosity @ 100°C, cSt	ASTM D445	7,5
Viscosity @ 40°C, cSt	ASTM D445	34
Viscosity Index	ASTM D2270	175
Brookfield Viscosity @ -40 °C cP	ASTM D2983	12.000
Pour Point, °C	ASTM D97	-42
Flash Point, °C	ASTM D92	210

AVAILABLE PACKS

1L, 208L, Bulk



Daewoo FLY

Meets and exceeds: Audi, Seat, Skoda, Volkswagen (VW TL 052 182; VW TL 052 529), BMW 1, 3, 5, 6 series, Z4, X1 (BMW DCTF-I), Peugeot/Citroen 9734.S2, Ferrari TF DCT-F3, Fiat BOT 341, Ford/Nissan M2C936A (BOT 341), Mercedes-Benz A-Class, B-Class (MB 236.21; MB 236.25), Mitsubishi MZ320065 Dia-Queen SSTF-I, Porsche (ZF) Boxster, Cayman, 911, Panamera, Renault Getrag (BOT 450), Volvo C30, S40, S60, V40, V50, V60, V70 S80, XC30, XC60 (1161838 1161839)

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.852
Viscosity @ 100°C, cSt	ASTM D445	7,5
Viscosity @ 40°C, cSt	ASTM D445	36,3
Viscosity Index	ASTM D2270	170
Pour Point, °C	ASTM D92	-40
Flash Point, °C	ASTM D2896	190

AVAILABLE PACKS

1L, 208L, Bulk



Daewoo MSC

Used in automatic transmissions and manual transmissions, in torque converters and numerous power steering systems in accordance with the specifications of the manufacturer.

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.870
Viscosity @ 100°C, cSt	ASTM D445	8
Viscosity @ 40°C, cSt	ASTM D445	40
Viscosity Index	ASTM D2270	175
Pour Point, °C	ASTM D92	200
Flash Point, °C	ASTM D97	-36

AVAILABLE PACKS

1L, 208L, Bulk