



Agriculture And Forestry

Daewoo **GNY** 15W30 and 10W30

Meets the requirements of: API SF/GL 4, Caterpillar TO-2; John Deere J27, J20CI Ford's Super Tractor Oil Universal (STOU) applications (M2C 159B); Massey-Ferguson CMS 1135 and CMS 1139; Allison C-4.



TYPICAL PROPERTIES

		Oscar STOU 15W30	Oscar STOU 10W30
Density @ 15°C, kg/l	ASTM D1298	0.875	0.875
Viscosity @ 100°C, cSt	ASTM D445	11.5	11.0
Viscosity @ 40°C, cSt	ASTM D445	76	75
Viscosity Index	ASTM D2270	145	140
Flash Point (COC), °C	ASTM D92	228	225
TBN, mg KOH/g	ASTM D2896	8	8
Pour Point, °C	ASTM D6749	-40	-40

AVAILABLE PACKS

20L, 25L, 208L, Bulk

Daewoo **GNY** 10W40

Meets the requirements of: Allison C4, API CG-4/SF, API GL-4, Atlas Copco Kompressor, CASE IH-MS 1209, Caterpillar TO-2, FENDT KDM 41.2011, Ford ESN-M2C-134 B, Ford ESN-M2C-134 C, Ford ESN-M2C 134 D, Ford ESN-M2C-159 B, Ford ESN-M2C-159 C, Getriebeöl: SAE 80W, Hydrauliköl: HVL ISO VG 68-100, John Deere J20C, John Deere J27, Kompressorenöl: Holman Compair Kompressor, MAN 271, Massey-Ferguson M 1139, Massey-Ferguson M 1144, Massey Ferguson M 1145, MAT 3525, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Motorenöl: SAE 10W-40, New Holland NH 410B, Spezialtraktorenöl: John Deere J20C, ZF TE-M 06B, ZF TE-M 06C, ZF TE-M 06D, ZF TE-M 07B, ZF TE-ML 06A.

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.863
Viscosity @ 100°C, cSt	ASTM D445	14.3
Viscosity @ 40°C, cSt	ASTM D445	95
Viscosity Index	ASTM D2270	155
Flash Point (COC), °C	ASTM D92	228
TBN, mg KOH/g	ASTM D2896	8
Pour Point, °C	ASTM D6749	-42

AVAILABLE PACKS

20L, 25L, 208L, Bulk



Daewoo **Mlida** SAE 80W

Meets the requirements of: SAE 80W, ISO VG 46, API GL-4, HLP-D/HVLP-D (ISO VG 46-68), DENISON HF-0, HF-1, HF-2, SPERRY VICKERS I-286-S, M-2950-S, ALLISON C4, MIL-L-2105, CATERPILLAR TO-2, ZF TE-ML 05F, 17E, ALLISON C3, CASE MS-1204, MS-1205, MS-1206, MS-1207, MS-1209, MS-1210, CASE NEW HOLLAND MAT 3525, 3505, DEUTZ Hydraulic Trans Fluid, DENISON HF 1/2/3, JOHN DEERE J 20C/D, MASSEY FERGUSON M-1110, M-1127 A, B, M-1129 A; M-1135; M-1139; M-1141; M-1143; M-1145, VALMET/VOLVO BM, ZF TE-ML 03E/06.

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	9.8
Viscosity @ 40°C, cSt	ASTM D445	55
Viscosity Index	ASTM D2270	155
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D6749	-38

AVAILABLE PACKS

20L, 25L, 208L, Bulk



Daewoo **Mlida** SAE 50 TO-4

Meets the requirements of: API GL-4; CAT TO-4; KOMATSU KES 07.868.1

TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	18.0
Viscosity @ 40°C, cSt	ASTM D445	195
Viscosity Index	ASTM D2270	100
Flash Point (COC), °C	ASTM D92	245
Pour Point, °C	ASTM D6749	-20

AVAILABLE PACKS

20L, 25L, 208L, Bulk





Agriculture And Forestry

Daewoo **Mlida** WB101

Meets the requirements of: API GL 4, Case New Holland MAT-3525, M2C-134 A-D, FNHA-2- D.201.00, John Deere JDM-J20C, Massey-Ferguson M1143, M1145, Volvo WB 101, Transmission Oil 97303:015, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4.



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.870
Viscosity @ 100°C, cSt	ASTM D445	10.7
Viscosity @ 40°C, cSt	ASTM D445	68
Viscosity Index	ASTM D2270	147
Flash Point (COC), °C	ASTM D92	226
Pour Point, °C	ASTM D6749	-42

AVAILABLE PACKS

20L, 25L, 208L, Bulk

Daewoo **Mlida** WB101 & WB102

Meets the requirements of: API GL 4, Case New Holland MAT-3525, MAT 3540, MAT 3526, MAT 3505, M2C-134 A-D, M2C86-B, FNHA-2- D.201.00, John Deere JD20A, JD20B, JD20C, JD20D, JDM-J20C, Massey-Ferguson M1145, M1143, M1141, M1135, Volvo WB 101, WB 102, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4.



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.857
Viscosity @ 100°C, cSt	ASTM D445	8.8
Viscosity @ 40°C, cSt	ASTM D445	50
Viscosity Index	ASTM D2270	155
Flash Point (COC), °C	ASTM D92	226
Pour Point, °C	ASTM D6749	-42

AVAILABLE PACKS

20L, 25L, 208L, Bulk

Daewoo Lina 2T SAE 30

Meets the requirements of: API TC JASO FC



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.877
Viscosity @ 100°C, cSt	ASTM D445	11.6
Viscosity @ 40°C, cSt	ASTM D445	82
Viscosity Index	ASTM D2270	134
Flash Point (COC), °C	ASTM D92	190
Pour Point, °C	ASTM D6749	-30

AVAILABLE PACKS

100ml

Daewoo Hamr Oil 100

Meets the requirements of:



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.874
Viscosity @ 100°C, cSt	ASTM D445	12.4
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D6749	-33

AVAILABLE PACKS

4L, 20L, 25L, 208L, Bulk

Deawoo White Oil 68

Meets the requirements of:



TYPICAL PROPERTIES

Density @ 15°C, kg/l	ASTM D1298	0.884
Viscosity @ 100°C, cSt	ASTM D445	8.5
Viscosity @ 40°C, cSt	ASTM D445	68
Viscosity Index	ASTM D2270	95
Flash Point (COC), °C	ASTM D92	228
Pour Point, °C	ASTM D6749	-27

AVAILABLE PACKS

4L, 20L, 25L, 208L, Bulk