



Brake Fluid

Daewoo Brake Fluid DOT 5.1

Meets and exceeds: SAE J 1704; FMVSS 116 DOT 5.1; ISO 4925

TYPICAL PROPERTIES

FMVSS Grade	DOT 5.1
Color	Amber
Density @ 15 °C	1.05
pH	9.0
Kinematic Viscosity @ 100 °C, cSt	1.5
Equilibrium Reflux Boiling Point, °C	260
Wet Equilibrium Reflux Boiling Point, °C	180
Pour Point, °C	> -50

AVAILABLE PACKS

250mL, 500mL, 208L, Bulk



Daewoo Brake Fluid DOT 4 LV

Meets and exceeds: FMVSS No. 116 DOT 4 LV; SAE J1703; Ford M6C65-A2; JIS K 2233 Class 6; ISO 4925 Class 6; VW 501.14

TYPICAL PROPERTIES

FMVSS Grade	DOT 4 LV
Color	Amber
Density @ 15 °C	1.060
pH	9.0
Kinematic Viscosity @ 100 °C, cSt	1.5
Equilibrium Reflux Boiling Point, °C	260
Wet Equilibrium Reflux Boiling Point, °C	165
Pour Point, °C	> -50

AVAILABLE PACKS

250mL, 500mL, 208L, Bulk



Daewoo Brake Fluid DOT 4

Meets and exceeds: FMVSS No. 116 DOT 4; SAE J1703

TYPICAL PROPERTIES

FMVSS Grade	DOT 4
Color	Amber
Density @ 15 °C	1.060
pH	9.0
Kinematic Viscosity @ 100 °C, cSt	2.2
Equilibrium Reflux Boiling Point, °C	260
Wet Equilibrium Reflux Boiling Point, °C	148
Pour Point, °C	> -50

AVAILABLE PACKS

250mL, 500mL, 208L, Bulk



Daewoo Brake Fluid DOT 3

Meets and exceeds: FMVSS No. 116 DOT 3; SAE J1703

TYPICAL PROPERTIES

FMVSS Grade	DOT 3
Color	Amber
Density @ 15 °C	1.092
pH	9.0
Kinematic Viscosity @ 100 °C, cSt	2.2
Equilibrium Reflux Boiling Point, °C	240
Wet Equilibrium Reflux Boiling Point, °C	148
Pour Point, °C	> -50

AVAILABLE PACKS

250mL, 500mL, 208L, Bulk

