



Antifreeze-coolants-DL

Daewoo DL Coolant/Antifreeze Concentrate G13

Meets and exceeds: VW/Audi/Seat/Porsche, VW G13; VW G12; MB 325.3; MB 325.5; MB 325.6; MAN 324 Type SNF; ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; Ford WSS M97 B44-D; BMW N600.69.0; Toyota TSK 2601G-8A; G13.



TYPICAL PROPERTIES

Density @ 15°C, kg/l	106
Boiling Point, °C	163

Si-OAT
Technology

G13



ANTIFREEZE

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk

Daewoo DL Coolant/Antifreeze 50% G13

Meets and exceeds: VW/Audi/Seat/Porsche, VW G13; VW G12; MB 325.3; MB 325.5; MB 325.6; MAN 324 Type SNF; ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; Ford WSS M97 B44-D; BMW N600.69.0; Toyota TSK 2601G-8A; G13.WSS M97 B44-D; BMW N600.69.0; Toyota TSK 2601G-8A; G13.



TYPICAL PROPERTIES

pH	8.5
Freezing point °C	-36
Density @ 15°C, kg/l	107
Boiling point °C	109

Si-OAT
Technology

G13

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk

Daewoo DL Coolant/Antifreeze Concentrate G12

Meets and exceeds: VW/Audi/Seat/Porsche, VW G12; MB 325.3; MAN 324 Type SNF; ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; Ford WSS M97 B44-D. G12



TYPICAL PROPERTIES

Density @ 15°C, kg/l	110
Boiling Point, °C	163

Si-OAT
Technology

G12



ANTIFREEZE

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk

Daewoo DL Coolant/Antifreeze 50% G12

Meets and exceeds: VW/Audi/Seat/Porsche, VW G12; MB 325.3; MAN 324 Type SNF; ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; Ford WSS M97 B44-D. G12



TYPICAL PROPERTIES

pH	8.5
Freezing point °C	-36
Density @ 15°C, kg/l	107
Boiling point °C	109

Si-OAT
Technology

G12

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk



Antifreeze-coolants-DL

Daewoo DL Coolant/Antifreeze Concentrate G11

Meets and exceeds: ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; CM 1899M; GM 6043M; GM 1825M; Ford ESE-M97B44-A; Ford ESE-M97B18-C; Chrysler MS-7170; Freightliner 48-22880; Cummins 90T8-4; Waukesha 4-19470; White (GMC Div. Of Volvo); John Deere 8650-5; Case Corp. MS1710; Navistar B1 (B6-008GO); Cummins 3666132; Detroit Diesel 7SE298; FordNew Holland 9-86; John Deere H-5; Mack Truck 014CS17004; ATA RP 302A; G11



TYPICAL PROPERTIES

Density @ 15°C, kg/l	113
Boiling Point, °C	160



ANTIFREEZE

AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk

Daewoo DL Coolant/Antifreeze 33%/50% G11

Meets and exceeds: ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; CM 1899M; GM 6043M; GM 1825M; Ford ESE-M97B44-A; Ford ESE-M97B18-C; Chrysler MS-7170; Freightliner 48-22880; Cummins 90T8-4; Waukesha 4-19470; White (GMC Div. Of Volvo); John Deere 8650-5; Case Corp. MS1710; Navistar B1 (B6-008GO); Cummins 3666132; Detroit Diesel 7SE298; FordNew Holland 9-86; John Deere H-5; Mack Truck 014CS17004; ATA RP 302A; G11



TYPICAL PROPERTIES

pH	8.5
Freezing point °C	-36
Density @ 15°C, kg/l	105
Boiling point °C	109



AVAILABLE PACKS

1L, 4L, 5L, 20L, 25L, 208L, Bulk