

**AQUIFER LOW PROFILE CISTERNS**

PART NO.	CAPACITY	DESCRIPTION	WEIGHT	TANK DIMENSIONS
ACT1000-LPB	1000 Gallon	Low Profile Cistern w/Burial Lid	559	98" x 111" x 36"
ACT1000-LPG	1000 Gallon	Low Profile Cistern w/Ground Access Assembly	595	98" x 111" x 36"
ACT1500-LPB	1500 Gallon	Low Profile Cistern w/Burial Lid	702	98" x 111" x 48"
ACT1500-LPG	1500 Gallon	Low Profile Cistern w/Ground Access Assembly	738	98" x 111" x 48"
ACT2000-LPB	2000 Gallon	Low Profile Cistern w/Burial Lid	917	98" x 158" x 45"
ACT2000-LPG	2000 Gallon	Low Profile Cistern w/Ground Access Assembly	953	98" x 158" x 45"
ACT2500-LPB	2500 Gallon	Low Profile Cistern w/Burial Lid	1031	98" x 158" x 54"
ACT2500-LPG	2500 Gallon	Low Profile Cistern w/Ground Access Assembly	1067	98" x 158" x 54"

**AQUIFER LOW PROFILE CISTERN ACCESSORIES**

PART NO.	DESCRIPTION	WEIGHT	DIMENSIONS
ACT-16053	Aquifer 24" Burial Lid & Gasket	17	35" x 8"
ACT-16052	Aquifer Ground Access Assembly - 28" Riser, 24" Locking Lid & Gasket	53	34" x 38"



Tanks can be stacked for shipping and storage.



**Den Hartog**  
INDUSTRIES, INC.

4010 Hospers Drive South • P.O. Box 425 • Hospers, IA 51238-0425  
(712) 752-8432 • (800) 342-3408 • FAX (712) 752-8222 • www.denhartogindustries.com

(Pub. 6/10)

**Aquifer**  
LOW PROFILE CISTERNS



**Ace Roto-Mold**  
A DIVISION OF DEN HARTOG INDUSTRIES, INC.

Low Profile Cistern Tanks



# Aquifer

LOW PROFILE CISTERNS

## Aquifer Low Profile Cistern Tanks

- Strong, durable, quality construction
- Low profile design, for bulk collection and storage of potable or non-potable water
- Bury up to 28" deep
- Tank can be backfilled empty
- Tank can be used in both below and above ground applications
- Manufactured from high-density polyethylene with U.V. inhibitors
- Tanks can be stacked for shipping and storage
- Sectional ribbing designed to withstand up to 400 PSF load pressure
- Manufactured from FDA compliant resins
- Low profile design with multiple fitting flats to accommodate a variety of plumbing configurations
- Manufactured for containment of liquids up to 1.7 specific gravity
- Serial code, fully documented from date of manufacture
- Aquifer Installation Guidelines, Product Specifications and Warranty information is available at [www.denhartogindustries.com](http://www.denhartogindustries.com)

### The Ace Roto-Mold Difference

Only Ace Tanks feature a custom-molded gasket in the lid. Manufactured from extruded Nitrile rubber, the gasket snaps into the lid and ensures a water-tight seal.




#### Exclusive Lid Design

Only Ace Tanks have double-walled access covers that lock securely to the tank body and can be secured using nylon ties, eliminating the need for metal fasteners that can corrode and fail.



**Ground Access Assembly**  
28" riser and Locking Lid with flats for fitting installation.



**Closed Cell Foam Gasket**  
provides secure seal between lid or riser and tank.



**Eyelets**  
Lifting ears provide ease in transport and can be used to anchor tanks during installation.



**Fitting Flats**  
on tank top accept fittings up to 3".

**Burial Lid**  
with flats to accommodate up to a 3" fitting.



**Fitting Flats**  
accept fittings up to 4", allow additional drainage options and enable the connection of multiple tanks in a series.



**Support Columns**  
Molded in columns and intermediate 4" PVC supports throughout the tank provide additional structural strength.



All sizes available with Ground Access Assembly or Burial Lid options.

