

## Electric Vehicle AC Charger Stand or Wall Mount, 1 Gun

AC-07SL AC-07S



Picture for reference only. Actual product may vary. Tolerance ±10mm.

## **Electric Vehicle AC Charger**

The AC-07SL and AC-07S Electric Vehicle AC Chargers can provide AC charging for commercial electric vehicles. The power range is 7kW, suitable for public parking lots, highway service areas, office building, etc.



WWW.cic-ltd.com.tw IF, No. 46, Ln. 80, Sec. 3, Nangang Rd., Nangang Dist., Taipei City 115, TAIWAN Tel : + 886-2- 27883368 Fax : + 886-2-27883319 E-Mail : global@cic-Itd.com.tw

## Feature Index

ltem		Description	
Model		AC-07SL	AC-07S
Dimensions (mm)		H×W×D: 445×333×145	
Input	Input Voltage Range	200-240 VAC, Max 32A single-phase (L + N + PE)	
	Frequency	50/60Hz	
Output	Output Voltage Range	200-240 VAC	
	Maximum Output Current	Max 32A	
	Output Power	7kW	
	Connection Standard	SAE J1772, Cable Length: 5M	
	Communication	Ethernet (OCPP1.6)	
Environmental	Operating Temperature	<b>-20~50</b> ℃	
	Humidity	95% Max	
	Above Sea Level	≤2000m	
	НМІ	4.3" Touch Screen	Х
	Status LED	Stand By (Flashing Blue Light); Charging (Flashing Green Light); Finished Charging (Static Green Light); Warning (Static Red Light)	
	User Authentication	RFID (ISO/IEC 14443-A, MIFARE)	
	Electric Meter	MID 1%	
	Certification	CNS15511	
	Safty	current overload, surge protection, leakage detection, voltage-drop detection, ground detection, temperature detection	
	IP	IP55	
	Installation	Wall mount / Stand (optional)	



T. +886-2-2788-3368 / F. +886-2-2788-3319 1F., No. 46, Ln. 80, Sec. 3 Nangang Rd. Nangang Dist., Ì. Taipei City 11570, Taiwan Email: global@cic-ltd.com.tw Website: www.cic-ltd.com.tw



