



TRUMETAL CUSTOM ORDER COLOR OFFERINGS

				
Artic White SR .69 SRI 84	Bone White SR .61 SRI 72	Ivory SR .69 SRI 84	Taupe SR .38 SRI 41	Buckskin SR .33 SRI 34
				
Antique Bronze SR .24 SRI 22	Light Brown SR .38 SRI 41	Brown SR .33 SRI 34	Black SR .31 SRI 31	Old Town Gray SR .41 SRI 45
				
Charcoal Gray II SR .35 SRI 37	Charcoal Blue Gray SR .29 SRI 29			
				
Rural Red SR .34 SRI 35	Dark Red SR .36 SRI 39	Crimson Red SR .31 SRI 31	Berry SR .29 SRI 29	
				
Ivy Green SR .28 SRI 27	Fern Green SR .29 SRI 29	Colony Green SR .28 SRI 27	Hawaiian Blue SR .31 SRI 31	Gallery Blue SR .26 SRI 24
				
Charcoal Gray CRINKLE SR .33 SRI 35	Black CRINKLE SR .29 SRI 29	Evergreen CRINKLE SR .33 SRI 35	Rustic Red CRINKLE SR .32 SRI 33	Burnished Slate CRINKLE SR .30 SRI 31
				
Koko Brown CRINKLE SR .33 SRI 34	Copper Metallic SR .51 SRI 58			

TRUMETAL
& STEEL COMPONENTS
trumetalandsteel.com
505.362.7136

> Final color selection should be made from actual color chips.

> For the most current information, visit unitedsteelsupply.com

> A 40-Year limited paint warranty is available for all colors upon written request. Please inquire. (Outside the continental United States, please inquire).

> Solar Reflectivity (SR): Solar reflectivity or reflectance is the measure of a materials ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance. ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit energystar.gov.

> Solar Reflectance Index (SRI): The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit usgbc.org.