

Sigma's Vortex film is tough. It's been designed to handle the most demanding applications like hard to package "C" type loads, high speed ring wrappers for carpet and fibers, extraordinarily heavy pallets, or extremely valuable products that require exceptional unitization. Vortex is a highly engineered, co-extruded, one side cling blown film that combines superior extrusion technology with metallocene resins. Vortex—It'll make even the most demanding applications seem like a walk in the park.

500	MM	

Product	Length (M)	Gauge	Roll Weight (Lbs)	Rolls/Pallet
MVT5001230	1220	120	37.8	40
MVT5001425	1430	100	37	40
MVT5001523	1525	90	35.5	40
MVT5001820	1830	80	37.8	40
MVT5001917	1980	70	35.8	40

## 750 MM

Product	Length (M)	Gauge	Roll Weight (Lbs)	Rolls/Pallet
MVT7501230	1220	120	56.7	20
MVT7501425	1430	100	55.3	20
MVT7501523	1525	90	53.1	20
MVT7501820	1830	80	56.7	20
MVT7501917	1980	70	53.6	20

More sizes and gauges are available. Your Sigma Sales Pro will be pleased to discuss your requirements.

Vortex will provide exceptional load containment compared to conventional blown or cast films, making it a perfect fit with our Rite-Gauging® process. Vortex has extraordinary containment attributes and is significantly stiffer, with excellent puncture resistance, compared to competitive products. Based on these unique properties, there is an outstanding opportunity for clients to reduce film thickness while increasing the containment force and improving their overall package.

## Σ Sigma Stretch Film

PO Box 808, Lyndhurst, NJ 07071 T: 201-507-9100 F:201-507-0447 www.siamastretchfilm.com

Email: stretch.info@sigmaplastics.com