

# **Sigma Stretch Film**<sup>®</sup> THE INDUSTRY LEADER

## Technical Information and Typical Properties

### MVA One Side Cling Bio-assimilation Cast Machine Film

# 55G



#### Product Description

Sigma Vanish is Sigma's revolutionary high performance one-side cling cast film "Powered by Smart Plastic Technology's Eclipse Bio-assimilation Technology." Designed to completely bio-assimilate back into nature without any microplastics or toxins, in aquatic and terrestrial environments. Also suitable for recycling.

#### General

Applications: • High Volume • High speed wrapping • One-side cling required  
 Revision Date: 2021-06-15 Available in 500mm and 750mm widths

Film Properties	Typical Value		Test Method
	(English)	Tolerance	
Tensile Strength at Yield MD	1350 psi	± 15%	ASTM D882
Tensile Strength at Yield TD	1250psi	± 15%	ASTM D882
Tensile Strength at Break MD	6700psi	± 15%	ASTM D882
Tensile Strength at Break TD	4000psi	± 15%	ASTM D882
Elongation at Break MD	470%	± 15%	ASTM D882
Elongation at Break TD	590%	± 15%	ASTM D882
Protrusion Puncture	10.0 lbs	± 15%	ASTM D5748
Protrusion Puncture Energy	17.1 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	300 g/mil	± 15%	ASTM D1922
Elmendorf Tear Strength TD	600 g/mil	± 15%	ASTM D1922
Cling - Outside to Inside @ 225%	min 150 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance
Core ID	3.05 inches	± 0.05 in
Film Thickness	55 Gauge	

Manufactured with pride in the USA and Canada by

#### Sigma Stretch Film

Page & Schuyler Aves. Bldg #8

Phone: 800-672-9727 • 201-507-9100

Email: stretch.info@sigmaplastics.com

[www.sigmastretchfilm.com](http://www.sigmastretchfilm.com)

©Copyright 2018 Sigma Stretch Film



SPTek ECLIPSE™ is a Trademark of  
Smart Plastic Technologies, LLC