

NON-STAINING

20-0-14 PROMAX

SYSTEMIC CARBON TECHNOLOGY

FEATURES & BENEFITS

Enhanced foliar delivery

Increased uptake

High PH breakthrough

Reduced plant stress

Enhances tank mix suspension

Enhances compatibility of tank mixes

GUARANTEED ANALYSIS

Total Nitrogen (N)..... 20%

6.00% Urea Nitrogen

14.00% Other water soluble nitrogen

Derived from: Urea Triazone Solution, 5% Urea slow

release derived from Methylene Urea Solution

Soluble Potash (K)..... 14%

Total Magnesium (Mg)..... 0.15%

0.15% Water Soluble Magnesium

Total Iron (Fe)..... 2.50%

2.50% Chelated Iron

Total manganese (Mn) 1.50%

1.50 Chelated Manganese

Derived from: magnesium glucoheptonate, manganese glucoheptonate, iron glucoheptonate.

Potassium derived from potassium thiosulfate

Also contains non-plant food ingredients:

Nanotized carbon.....20%

DIRECTIONS FOR USE

Lawns, Turf, Golf course: Add 2-4 quarts per 100gl water.

Compatible with all insecticide, herbicide, fungicide.

Ornamental and shrubbery: Add 1 pint to 1 quart in 50gl water. Can be used in a drench or foliar application.

Compatible with all insecticide, fungicide and other nutritional.

Palms, hardwoods, fruit trees: Add 1 pint to 1 quart per 50gl. water. Apply as a drench under the drip line plus foliar application. Can be added to arbor jet systems for enhanced delivery into xylem.

CAUTION: Avoid getting in eyes, mucus membranes or on skin. Use with adequate ventilation. Keep container capped when not in use.

KEEP AWAY FROM CHILDREN.

ANTIDOTES: Skin or eye contact. Flush thoroughly with water and see a physician. Internal: Induce vomiting and get medical attention.

CAUTION: Avoid over spray of concrete surfaces and painted surfaces. Do not contaminate water supplies.

Conditions of Sale: Seller warrants that this product meets or exceeds the ingredients specified and is reasonably fit for the purpose stated on this label when used in accordance with directions under normal conditions of use. No one, other than the officer of seller is authorized to make any warranty, guarantee or directions concerning this product. Because the time, place, rate of application and other conditions of use are beyond the seller's control, seller's liability from handling storage and use of this product is limited to replacement of product or refund of purchase price.

Net Wt. 25.5 lbs

AMP LIQUIDS

792 State Road 26 Melrose, FL 33666
Ampliquids.com
F003652