



PREMIUM SPRAY PAINTS AND ENAMELS

PREMIUM ENAMEL

- Quick-drying multi-purpose enamels for interior/exterior use
- Superior coverage, durability and rust-resistant finish
- Resists chipping and peeling
- Use on metal, wood, plaster and masonry surfaces that have been primed with primer below
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only (148 cs per pallet)**

OSHA *MFR # 419-0900 Gloss Purple Control # 5687100	 *MFR # 419-0901 Gloss Pink Control # 5687101	OSHA MFR # 419-0905 Gloss Candy Apple Red Control # 5687102	OSHA MFR # 419-0920 Gloss White Control # 5687103	OSHA MFR # 419-0921 Gloss Black Control # 5687104	 MFR # 419-0922 Flat Black Control # 5687105
 MFR # 419-0924 Aluminum Metallic Control # 5687107	 MFR # 419-0925 Gold Metallic Control # 5687108	 *MFR # 419-0926 Gloss Forest Green Control # 5687109	 *MFR # 419-0927 Gloss Light Blue Control # 5687110	 MFR # 419-0928 Flat White Control # 5687111	OSHA MFR # 419-0929 Gloss Canary Yellow Control # 5687112
OSHA MFR # 419-0930 Danger Orange Control # 5687113	 *MFR # 419-0931 Gloss Rich Brown Control # 5687114	 *MFR # 419-0932 Gloss Clear Coat Control # 5687115	 MFR # 419-0936 Gloss Royal Blue Control # 5687116	 *MFR # 419-0937 Gloss Deep Red Control # 5687117	 MFR # 419-0938 Satin Black Control # 5687118
 *MFR # 419-0940 Gloss Machinery Gray Control # 5687119	 MFR # 419-0941 Dull Aluminum Control # 5687120	OSHA *MFR # 419-0942 Gloss Ocean Blue Control # 5687121	OSHA *MFR # 419-0943 Gloss Medium Gray Control # 5687122	OSHA *MFR # 419-0944 Gloss Light Green Control # 5687123	



WARNING: This product can expose you to chemicals including ethylbenzene which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

PREMIUM PRIMER

- Fast-drying formula seals, primes, adds protection against rust for interior/exterior use
- Improves adhesion of the color coat and provides base for a smoother finish
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only (148 cs per pallet)**

PRIMER *MFR # 419-0934 Red Metal Primer Control # 5687135	PRIMER *MFR # 419-0935 Gray Metal Primer Control # 5687136
---	--

WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov



* Manufacturer Discontinued - Limited Quantity Available

INVERTED PAINT

- Fast-drying water based formula
- Top-down-only valve designed for use with wands below or manual application
- Indoor/outdoor use to mark hazards, playing fields, landscaping, surveying, construction areas, underground utilities
- For use on grass, gravel or paved surfaces
- APWA (American Public Works Association) and fluorescent colors available
- For use with wands 419-4831 or 419-4832 below
- Dry time: 30 minutes to touch
- Case contains: 12 - 20 oz (17 oz net wt) cans - **Sold by case only** (72 CS per pallet)

FLUORESCENT COLORS



*MFR # 419-4801
Fluorescent Blue
Control # 5697100



*MFR # 419-4811
Fluorescent Orange
Control # 5697106




*MFR # 419-4803
Fluorescent Yellow
Control # 5697102

APWA COLORS



Potable water

*MFR # 419-4853
APWA Blue
Control # 5697123



Proposed excavation,
construction boundaries

*MFR # 419-4856
APWA White
Control # 5697126



Temporary survey

*MFR # 419-4854
APWA Pink
Control # 5697124



Electric Lines

*MFR # 419-4857
APWA Red
Control # 5697127



Reclaimed or
non-potable water

*MFR # 419-4855
APWA Purple
Control # 5697125



General purpose

MFR # 419-4858
APWA Black
Control # 5697128



* Manufacturer Discontinued - Limited Quantity Available



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

WANDS

- For use with only inverted spray paints above
- Pistol trigger handle
- Tool free assembly
- Sold by each

MFR #	SIZE	CONTROL #
419-4831	34.5" LENGTH	5697190
419-4832	12.5" LENGTH	5697191



419-4831



419-4832

ROOF ACCESSORIES PAINT

- Flat finish, rust-resistant spray that camouflages and protects gutters, flashing, vents, soil stacks, and other roof accessories
- For use on metal, masonry, wood, vinyl, and PVC (not for use on asphalt shingles)
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only** (148 cs per pallet)



MFR # 419-4860
Charcoal
Control # 5687150



MFR # 419-4862
Cedar
Control # 5687151



MFR # 419-4864
Weathered Wood
Control # 5687152



MFR # 419-4866
Tile Red
Control # 5687153



MFR # 419-4868
Slate
Control # 5687154



MFR # 419-4870
Forest Green
Control # 5687155



MFR # 419-4872
Hickory
Control # 5687156



MFR # 419-4874
Wedgewood
Control # 5687157



MFR # 419-4876
Birchwood
Control # 5687158



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov



HIGH HEAT PAINT

- Formulated to withstand temperatures of 1200°F with excellent adhesion
- Use on all indoor and outdoor surfaces exposed to high temperatures, including radiators, barbecues, stoves, car exhaust manifolds, engines, boilers, heaters and steam pipes
- Dry time: 1 hour to touch
- Case contains: 6 - 16 oz (12 oz net wt) cans - **Sold by case only** (148 cs per pallet)



MFR # 419-0979
Aluminum
Control # 5687165



MFR # 419-0981
Black
Control # 5687166



FLUORESCENT PAINT

- Quick-dry, fade-resistant indoor/exterior formula
- Provides optimum brilliance and outstanding durability
- Use to mark hazards in the home and workplace, including curbs, steps, house numbers, trucks, cars, boats, helmets
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (12 oz net wt) cans - **Sold by case only** (148 cs per pallet)



*MFR # 419-0974
Hot Orange
Control # 5687170



MFR # 419-0978
Red
Control # 5687174



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov



* Manufacturer Discontinued - Limited Quantity Available

COLD GALVANIZE (95% ZINC)

- Complete zinc metal spray which rustproofs any metal surface with thorough protection that lasts for years
- It is equivalent to a hot galvanizing treatment as it fuses and adheres to all metal surfaces, stopping corrosion immediately
- Coated surfaces can be welded safely without fire or fumes
- Resistant to abrasion, cracking or peeling, and oxidation
- Heat resistant up to 400° F & does not contain lead
- Conforms to military specifications MIL-P-21035 USAF, MIL-P-26915A, MIL-P-46105 for primer coatings and galvanizing repair
- Case contains: 6 - 16 oz (12 oz net wt) cans - **Sold by case only** (148 CS per pallet)

MFR # 419-T3408	CONTROL # 5697170
---------------------------	-----------------------------

WARNING: This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



GALV-OFF

- Removes the buildup of galvanization, softening it so that it flakes off by itself
- Even stubborn deposits can be removed with frequent application
- When used daily, it not only prevents harmful deposits from accumulating, but it also lubricates and protects rollers and dies
- The SprayAnyWay™ valve sprays from any direction, even upside down, for ease of application
- Use on forming machine rollers, punch press dies, and other surfaces where galvanization builds up. Formulation for factory, institutional, industrial and commercial use
- Case contains: 12 - 16 oz (12 oz net wt) cans - **Sold by case only** (72 CS per pallet)

MFR # 5117	CONTROL # 5697171
----------------------	-----------------------------

WARNING: This product can expose you to chemicals including ethylbenzene which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

